
TOOLING SYSTEM

General Catalog




MST corporation

Vol. 4
1901

Individuality and creation


Since its inauguration in 1937, MST has been developing new products with forward-looking creativity. We have a basic philosophy of "Personality and Creation", and we pursue of originality and try to improve brand value as we strive to meet the needs of our customers.




■ Fusing humans and machines

By fusing the automated machining proceses and by-hand processes at a high level, we are aiming to produce even higher quality products.










A new challenge


By making the most of our accumulated knowledge and experience, we are developing new processing technologies and providing new service.

■ Graphite Machining














Thailand factory


We make graphite electrodes to your specifications. State-of-the-art facilities and production systems offer our customersquick delivery and large-volume order fulfillment.

■ Micromachining











Slimline UNO finishing process


We meet our customers' needs using micron-precision process technology which have been cultivated throughout history.

RELIABLE TOOLING


MST's tooling is subject to its own MST's 4 accuracy standards: taper contact, roundness, surface roughness and heat treatment. These are more precise than JIS or MAS standards. We provide trustworthy products under strict quality control.

● MST's 4 accuracy standards.


1 Taper contact		%	90
2 Roundness		μm	0.8
3 Surface roughness (Rmax)		μm	0.6
4 Heat treatment	Material		SCM415
	Carburized depth	mm	0.8 ~1.0
	Hardness	HRC	55° ± 2°












SHRINK-FIT HOLDER SLIMLINE


SLIMLINE contributes to the improvement of machining accuracy and cost reduction in 5-axis machining, micro-precision machining, and heavy duty applications.







If you would like more detailed information, please contact MST and ask for a SLIMLINE catalog.









The SLIMLINE shrink-fit holder provides the perfect solution.

A simple chucking mechanisem without any parts.


Stable gripping force.
No gaps.
No parts.
A cutter does not fall off even if vibrated.





Super-slim shape


Allows the holder to enter a workpiece. Can be used with a standard tool.




High accuracy

Twice the tool life.
Slim tools are also no problem.
Anyone can use them...


✖ Short cutter life.




✖ Small tools break soon!



✖ Cutter run-out adjustment is troublesome!




✖ The end mill slips or falls off!



The workpiece is ruined.

✖ The applicable tools are special!




✖ The coolant leaks.



MST


Master Index

ANGLE HEAD




HALF	6
STANDARD type	14

M/C Tool



DETa-1 Collet Holder	22
COLLET HOLDER	32
Hi-ART MILLING CHUCK	40
SUMMIT	43
FMH RIGID type	46
RED SCREW arbor	48
Cutter arbor with spindle-through coolant	53
MICRO HEAD	55
Retention knob	64

HSK-T Tooling Systems for Turning Mill



Set screw holders for Round shank	69
Insert holders for Square-shank	70

General Purpose Tool



Universal Facing Boring Head	73
SMART GRIP	75
GOO checker	82
Centering bar	84

JIG



6S DESK	86
CLEAN BOX	88
TEST BAR CHECKMATE	90
TOOL CAP	91
Tool set up stand	94
PALETTE	96
ENDMILL HOUSE	97
TOOL HOLDER STORING CABINET	98

Measuring Equipment



MIDDLE VISE	99
Wire Cut Unit	101

Maintenance Tool



PARTS	103
ANGLE HEAD HALF PARTS LIST	105
Technical support	114
Instructions for use	115
For high-speed spindle rotation	118
HSK SHANK	119
Technical data	120
OVERSEAS NETWORK	128

Wire EDM fixture




Technical Information

For High-accuracy, and High-efficiency machining 5 Points


End-mill


Small size drill

1 The shortest



Length becomes 2 times


Deflection becomes 8 times

Use shrink-fit holders with a slim-tip!

As short as possible

Deflection amount is proportional to projection length^3.

2 Selection



Stronger than collet holders

Clamping force **3** times

Run-out accuracy within **3** microns


Use shrink-fit holders with strong clamping force and high accuracy!

Choose a tool holder that can clamp a cutting tool securely and with high accuracy.

3 Quality

Machining quality and speed


Down



Replace!

Do not use worn cutting tools.

4 Cleanliness




Cutting chips and oil are **your main enemies.**

Use a tool holder washing machine,

CLEAN BOX!

Clean your tool holders and cutting tools.

5 Accuracy



Check the spindle condition

Use a test bar for dedicated machine spindle maintenance,

CHECKMATE!

Machine spindle run-out accuracy should be within 10 microns (.0004").

The shrink fit holder with the slim design, superior gripping force and run-out accuracy.



SHRINK-FIT HOLDER

SLIMLINE



If you would like more detailed information, please contact MST and ask for a SLIMLINE catalog.



Thickness 1.5mm (.06")

3 µm (.0001")

Tool holder washing machine



CLEAN BOX

Washes tool holders, collets, nuts and cutting tools thoroughly to maintain their high accuracy

P.88


TEST BAR

CHECKMATE

Ideal for easy machine spindle run-out accuracy checks.


P.90








ANGLE HEAD

You can carry out 5-surface machining, such as side face and inside surface, without needing to change the positioning of the work-piece.









Voluminous variety

■ New concept Angle head HALF for drilling and tapping applications Affordable•Lightweight•Shorte delivery!


Type	Angle	MODEL	Application	Chucking range(φD)		MAX. (min-1) [Main spindle : Angle shaft]	ATC	Kg
90°type ➔P.8   mini type ➔P.10	90°	HFCS6	Drill Endmill	φ3, 4, 6	FCS6	5680:5000 [1 : 0.88]	○	1.8
		HFD 7		φ1 ～ 7	D 7	6000:6000 [1(CCW):1(CW)]		
		HFD12		φ2.5～13	D12	4000:4000 [1(CCW):1(CW)]		2.9
		HFA10		φ2.4～10	C10	6000:6000 [1(CCW):1(CW)]		1.8
		HFA20		φ5.8～20	C20	6000:5000 [1(CCW):0.83(CW)]		4.4
		HFCS6	Tap	M4, 5, 6	FCS6	5680:5000 [1 : 0.88]		1.8
		HFT 4		M2 ～ 8	TA4	6000:6000 [1(CCW):1(CW)]		2.3
		HFT 6		M3 ～12	TA6	4000:4000 [1(CCW):1(CW)]		2.9
		HFT12		M3 ～16	TA6/12	6000:5000 [1(CCW):0.83(CW)]		4.4
UNIVERSAL type (Free setting of cutting directions) ➔P.11 	0° ～ 120°	HUD 7	Drill Endmill	φ1 ～ 7	D 7	6300:3000(BT30:7200:4000) [1(CW):0.48(CW)][BT30:1(CCW):0.56(CW)]	○	1.8
		HUA10		φ2.4～10	C10	6300:3000 [1(CW):0.48(CW)]		3.9
		HUA20		φ5.8～20	C20			4.8
		HUT 4	Tap	M2 ～ 8	TA4	6300:3000 (BT30:7200:4000) [1(CW):0.48(CW)][BT30:1(CCW):0.56(CW)]		3.8
		HUT 6		M3 ～12	TA6	6300:3000 [1(CW):0.48(CW)]		4.8

■ High-rigidity STANDARD type


(※Use the BT30 tooling system with the Quick Change system.)

MODULAR type (Recombination type) ➔P.15  	90°	AHB 5	Drill Endmill	φ0.5～ 5	ER8	6000:6000 [1(CCW):1(CW)]	○	5.5
		AHB 7		φ0.5～ 7	ESX12			5.3
		AHB10		φ2.4～10	C10			6.2
	45°	AHC10	Drill Endmill					
SOLID type ➔P.16  	90°	AHA20	Drill Endmill	φ5.8～20	C20	3000:2430 [1(CCW):0.81(CW)]	○	7.3
		AHA25		φ5.8～25	C25	2500:2400 [1(CCW):0.96(CW)]		13.6
		AHD30		BT30※	BT30			14.7
FLANGE type (Mounting directly on machine spindle) ➔P.17	90°	AHA20	Drill Endmill	φ5.8～20	C20	3000:2430 [1(CCW):0.81(CW)]	×	18.0
		AHA25		φ5.8～25	C25	2500:2400 [1(CCW):0.96(CW)]		18.5
		AHD30		BT30※	BT30			19.6
UNIVERSAL type (Free setting of cutting directions) ➔P.18	0° ～ 90°	AHU10	Drill Endmill	φ2.4～10	C10	3000:4500 [1(CW):1.5(CW)]	○	9.6
		AHU20		φ5.8～20	C20	3000:3000 [1(CW):1(CW)]		15.8

Custom-made products ➔P.19


Twin cut type

Extra long type




Parallel Head



Slim and extended type

ANGLE HEAD HALF

PAT.


Affordable 2,300USD~ | Speedy Shorter delivery | Lightweight 1.8kg~ | Compact φ36~ | Repair it yourself

Drilling and tapping account for 80% of angle head operation.

The Angle Head HALF was redesigned to achieve the necessary rigidity and accuracy, it allows;

AFFORDABLE (Price : 1/2)
QUICK DELIVERY (Lead Time : 1/2)
LIGHTWEIGHT (Weight : 1/2)


NEW CONCEPT




90° type
BT30/40/50
HSK-A63
DIN40/50,
CAT.40/50

HFD/HFA
φ1~20mm
HFT
M2~16



mini type
Extra-compact head

BT30/40/50
DIN40/50
CAT.40/50


HFCS
φ3,4,6mm
M4,5,6




UNIVERSAL type
Angle can be set arbitrarily

BT30/40/50
DIN40/50
CAT.40/50

HUD/HUA
φ1~20mm
HUT
M2~12



Compact design



Type	MODEL	Q	A	B
90° type	HFD 7	72	68	38
	HFD12	98	93	58
	HFT 4	75	73	38
	HFT 6	97	92	58
	HFA10	90	87	38
	HFA20	119	111	64
	HFT12	97	96	64
		116	115	
mini type	HFCS6	36	31.5	31


Auto Tool Changer (A.T.C) is available on BT30 machine.



BT30
1.8kg

Easy installation

The positioning pin allows an in-use positioning block to be used is now a standard feature.
Can be used with a variety of machining centers.



Easy disassembly and assembly




- The number of parts (22 pcs.) is half that of conventional angle heads.
- No need for fine matching and adjustment.
- Makes use of commercial items such as bearings. Affordable and readily available.
- An informative video and an instruction manual for disassembly and reassembly are provided.




Running cost is reduced by 90% as a result of reduced repair costs and machine down time.


Easy to reassemble




Positioning block and positioning pin



Positioning block




Positioning pin



Bracket


- S dimension can be changed by reassembling the bracket.
- The positioning pin can be easily adjusted in length and replaced.



Semi-finished positioning block



CODE
HB-01



■**Note**

- Please confirm with the machine tool manufacturer about the dimensions of the positioning block.
- We have a semi-finished positioning block with a taper hole available. (→P.19)

Positioning block for machines

● FANUC

ROBODRILL
α-DiB series



CODE
ABF005



● MAZAK

SUPER VELOCITY CENTER
2000L/120-II 2000L/200-II



- Available from Yamazaki Mazak Corp.

● BROTHER

SPEEDIO
Compact machining center



CODE	NOTE
ABF213	S300X1/X2, S500X1/X2, S700X1/X2
ABF259	S1000X1
ABF176	TC-S2, S2A※, S2B, S2C, S2D, R2B※

■**Caution**

- TC-S2A※ (Tapping center),The user needs to confirm whether the positioning block can be mounted on the machine (spindle surface) or not.Please contact us.
- TC-R2B※ (Tapping center) machining area is limited to some extent due to interference between the positioning block and the internal part cover of the machine. For more information, please contact us.

■**A product code example when ordering Angle Head HALF.**

- FANUC BT30-HFD7-122-S65
- BROTHER BT30-HFD7L-120-S50C

Kit Package

- Learning Kit to understand gear and bearing mechanism.
- There are only 22 parts and anyone can assemble them in about 10 min.
- Spare/consumable parts and assembly tools are included.







Contents of kit	CODE	
	BT40-HF12-LK	BT50-HF12-LK
Complete unit	BT40-HFD12-180-S65 (1pc.)	BT50-HFD12-195-S80 (1pc.)
Angle shaft (For tapping)	FR-T6 (1pc.)	
Tap sleeve	TA6-3, 4, 5, 6, 8 (each1pc.)	
DETa-1 Collet	D12-4, 6, 8, 10, 12, 13 (each 1pc.)	
Positioning pin	HP-50T(1pc.)	HP-62T(1pc.)
Spare bearing	7005ADB (1set), 6805 (1pc.), 51106 (1pc.)	

HALF 90°type

Drill · Endmill

Fig. 1
HFD7
( )···HFD7L




Fig. 2
HFD12






Fig. 3
HFA10





Fig. 4
HFA20





Tap

Fig. 5
HFT4
( )···HFT4L




Fig. 6
HFT6






Fig. 7
HFT12



DETa-1 Collet (HFD,HUD)






CODE	ϕD	ϕD1	L	H	H1	Holder type
D 7- 1.5	1 ~ 1.5	17	50	7	36	HFD 7
- 2	1.5~ 2			10		HUD 7
- 2.5	2 ~ 2.5			12		
- 3	2.5~ 3					
- 4	3 ~ 4			14		
- 5	4 ~ 5			16		
- 6	5 ~ 6					
- 7	6 ~ 7					
D12- 4	2.5~ 4	26	70	16	50	HFD12
- 6	4 ~ 6			20		
- 8	6 ~ 8			22		
-10	8 ~10					
-12	10 ~12					
-13	11 ~13					

Tap sleeve (HFT,HUT)






CODE	ϕD	L	ϕD1	H	Holder type
TA 4-M 2	M 2	67.5	16	19	HFT 4
-M 3	M 3			20	HUT 4
-M 4	M 4			21	
-M 5	M 5				
-M 6	M 6				
-M 8	M 8				
TA 6-M 3	M 3	92	19	21	HFT 6
-M 4	M 4			22	HUT 6
-M 5	M 5				HFT12
-M 6	M 6				
-M 8	M 8			23	
-M10	M10				
-M12	M12			24	
TA12-M14	M14	111.5	25	33	HFT12
-M16	M16			35	

■Note
- Above products meet JIS standards. We can produce other standard Tap sleeves, such as ANSI, ISO, DIN and others. For more information, please contact us.

Spring collet (HFA,HUA)





CODE	ϕD	ϕD1	L	H	Holder type
C10-D	2.6 2.8 3 ... (0.2Steps) ... 9.6 9.8 10	17.2	26	16 (ϕD=2.6~5) Except for 18 ※3, 4 (ϕD=3, 4, 20 5.2~5.8) (ϕD= 6~10)	HFA10 HUA10
C20-D	6 6.2 6.4 ... (0.2Steps) ... 19.8 20	29.5	50	32 (ϕD= 6~ 9.8) 35 (ϕD=10~15.8) 40 (ϕD=16~20)	HFA10 HUA10

Ex. ϕD C10-6

CODE (Master holder)	Fig.	φD	L	M	Kg
BT30-HFD 7 -122	1	1 ~ 7	122	70	2.3
-182			182	130	3.0
-HFD 7L-120			120	57	1.8
-HFD12 -122	2	2.5~ 13	122	70	2.9
-HFA10 -120	3	2.4~ 10	120	65	1.8
-HFT 4 -122	5	M2~M 8	122	70	2.3
-182			182	130	3.0
-HFT 4L-120			120	57	1.8
-HFT 6 -122	6	M3~M12	122	70	2.9
BT40-HFD 7 -120	1	1 ~ 7	120	70	3.0
-180			180	130	3.3
-HFD12 -120	2	2.5~ 13	120	70	3.6
-180			180	130	4.9
-HFA20 -135	4	5.8~ 20	135	77	4.4
-195			195	137	5.6
-HFT 4 -120	5	M2~M 8	120	70	3.0
-180			180	130	3.3
-HFT 6 -120	6	M3~M12	120	70	3.6
-180			180	130	4.9
-HFT12 -135	7	M3~M16	135	77	4.4
-195			195	137	5.6
BT50-HFD 7 -195	1	1 ~ 7	195	130	6.4
-255			255	190	6.8
-HFD12 -135	2	2.5~ 13	135	70	6.3
-195			195	130	7.6
-255			255	190	8.9
-HFA20 -150	4	5.8~ 20	150	77	7.1
-210			210	137	8.3
-270			270	197	9.4
-HFT 4 -195	5	M2~M 8	195	130	6.4
-255			255	190	6.8
-HFT 6 -135	6	M3~M12	135	70	6.3
-195			195	130	7.6
-255			255	190	8.9
-HFT12 -150	7	M3~M16	150	77	7.1
-210			210	137	8.3
-270			270	197	9.4
A63 -HFD 7 -183	1	1 ~ 7	183	130	3.5
-243			243	190	3.9
-HFD12 -123	2	2.5~ 13	123	70	3.3
-183			183	130	4.7
-243			243	190	6.0
-HFA20 -198	4	5.8~ 20	198	137	5.4
-258			258	197	6.5
-HFT 4 -183	5	M2~M 8	183	130	3.5
-243			243	190	3.9
-HFT 6 -123	6	M3~M12	123	70	3.3
-183			183	130	4.7
-243			243	190	6.0
-HFT12 -198	7	M3~M16	198	137	5.4
-258			258	197	6.5

■ A product code example when ordering.

BT40-HFD7-120 - S 65

Holder

Positioning pin type

S : Straight pin
W : Expansion pin
T : Taper pin

Dimension S

50, 60, 65,
80, 85, 110 ...

CODE (Master holder)	Fig.	φD	L	M	Kg (lbs)
DN40A-HFD 7-135	1	1 ~ 7	135	70	3.1
-195			195	130	3.4
-HFD12-135	2	2.5~ 13	135	70	3.7
-195			195	130	5.0
DIN -HFA20-150	4	5.8~ 20	150	77	4.7
-210			210	137	5.8
-HFT 4-135	5	M2~M 8	135	70	3.1
-195			195	130	3.4
-HFT 6-135	6	M3~M12	135	70	3.7
-195			195	130	5.0
-HFT12-150	7	M3~M16	150	77	4.7
-210			210	137	5.8
DN50A-HFD 7-195	1	1 ~ 7	195	130	5.9
-255			255	190	6.3
-HFD12-135	2	2.5~ 13	135	70	5.8
-195			195	130	7.1
-255			255	190	8.4
-HFA20-150	4	5.8~ 20	150	77	6.6
DIN -210			210	137	7.8
-270			270	197	8.9
-HFT 4-195	5	M2~M 8	195	130	5.9
-255			255	190	6.3
-HFT 6-135	6	M3~M12	135	70	5.8
-195			195	130	7.1
-255			255	190	8.4
-HFT12-150	7	M3~M16	150	77	6.6
-210			210	137	7.8
-270			270	197	8.9
CT40 -HFD 7-135	1	0.4~.28	5.31	2.75	6.8
-195			7.68	5.11	7.5
-HFD12-135	2	2.5~ 13	5.31	2.75	8.2
-195			7.68	5.11	11.0
-HFA20-150	4	.23~ .79	5.91	3.03	10.4
CAT. -210			8.27	5.39	12.9
-HFT 4-135	5	M2~M 8	5.31	2.75	6.8
-195			7.68	5.11	7.5
-HFT 6-135	6	M3~M12	5.31	2.75	8.2
-195			7.68	5.11	11.0
-HFT12-150	7	#4 ~ 5/8	5.91	3.03	10.4
-210			8.27	5.39	12.9
CT50 -HFD 7-195	1	0.4~.28	7.68	5.11	13.0
-255			10.04	7.47	13.8
-HFD12-135	2	.10~ .51	5.31	2.75	12.8
-195			7.68	5.11	15.6
-255			10.04	7.47	18.5
-HFA20-150	4	.23~ .79	5.91	3.03	14.7
-210			8.27	5.39	17.3
-270			10.63	7.76	19.8
CAT. -HFT 4-195	5	M2~M 8	7.68	5.11	13.0
-255			10.04	7.47	13.8
-HFT 6-135	6	M3~M12	5.31	2.75	12.8
-195			7.68	5.39	15.6
-255			10.04	7.47	18.5
-HFT12-150	7	#4 ~ 5/8	5.91	3.03	14.7
-210			8.27	5.39	17.3
-270			10.63	7.76	19.8

■ **Option**
- DETa-1 Collet (HFD) ● Spring collet (HFA) ● Tap sleeve (HFT)
- Retention knob→P.64 ● Tools for assembly

■ **Std. Access.**
- Coolant duct (HSK-A) ● Fixing spanner(Except for HFA10/HFT4L)
- Hexagonal wrench set ● Spanner(HFA)
- Single-ended wrench (HFD7L/HFA10) ● Spanner(HFA) ● Low head bolt


■ **Note**
- Other shanks are also available upon request.


Cutting data ➔ P. 13
Parts list ➔ P. 105


HALF mini type



BT40-HFCS6-205








Cutter mounts in two directions

A cutting tool can be mounted both ways, inward or outward, by reassembling the angle shaft.




Allows maximum tool holder diameter limitation even when using a long cutting tool.

Minimal interference with face of workpiece.

Collet exchange system

Shaft exchange system for Shrink-fit collet for carbide cutter (end-mill, drill) or Tap collet for Tap.



CODE (Master holder)	φD	L	L1	M	Kg (lbs)
BT30 -HFCS6-155	Drill・Endmill φ3, 4, 6 / Tap M4, 5, 6	155	50	100	1.8
BT40 -HFCS6-160		160	50	110	2.8
-205		205	95	155	3.0
BT50 -HFCS6-175		175	50	110	5.6
-220		220	95	155	5.8
DN40A-HFCS6-175	Drill・Endmill φ3, 4, 6 / Tap M4, 5, 6	175	50	110	3.0
-220		220	95	155	3.2
DN50A-HFCS6-175		175	50	110	5.1
-220		220	95	155	5.3
CT40 -HFCS6-175	Drill・Endmill φ3, 4, 6 / Tap M4, 5, 6	6.89	1.97	4.33	6.61
-220		8.66	3.74	6.10	7.28
CT50 -HFCS6-175		6.89	1.97	4.33	11.24
-220		8.66	3.74	6.10	11.68

■**Option**
- Shrink-fit collet ●Tap collet
- Retention knob→P.64 ●Tools for assembly


■**Std. Access.**
- Fixing spanner ●Hexagonal wrench set ●Low head bolt

■**Note**
- When shipping, the head direction is inward. The tool for assembly (pliers for retaining ring) is required to reassemble the collet to allow for outward positioning of the cutting tool.
- Other shanks such as HSK are also available upon request.

■**Caution**
- The angle axis rotating direction is different due to its mounting direction, inward and outward.

Shrink-Fit Collet






CODE	φD	Holding length
FCS6- 3	3	11～13
- 4	4	
- 6	6	12～13

■**Caution**
- The dedicated shrink-fit collet for the Angle Head Half Mini.
- A shrink-fit heating device is required to insert and remove cutting tools.

Tap collet






CODE	φD	Holding length
FCS6-M4	M4	16
-M5	M5	
-M6	M6	

■**Note**
- Tap collets meet JIS standards. We can produce ANSI standard tap collet. For more information, please contact us.

■Procedure of cutter insertion to shrink-fit collet



Shrink-fit Heater (HRB-01)

1.Attach the shrink-fit collet to the adapter(ADH-SLK).
2.Heat the shrink-fit collet with the shrink-fit heater.
3.Attach a stopper to the carbide cutter.
After finishing heating, insert the cutter to the shrink-fit collet.
4.Cool the shrink-fit collet with the shrink-fit heater.

CODE	Power
HRB-01	100V

■A product code example when ordering.

BT30-HFCS6-155 - S 65

Holder

Positioning pin type
- **S** : Straight pin
- **W** : Expansion pin
- **T** : Taper pin

Dimension S
50, 60, 65, 80, 85, 110 …

Cutting data ➔P. 13
Parts list ➔P. 105

HALF UNIVERSAL type

Drill · Endmill

Fig. 1
HUD7
( )···BT30




Fig. 2
HUA10





Fig. 4
HUT4
( )···BT30





BT40-HUA20-135

Fig. 3
HUA20





Fig. 5
HUT6



Tap



CODE (Master holder)		Fig.	ϕD	L	M	ϕC	ϕE	Kg (lbs)	Moment kgf·mm
BT30	-HUD 7-102	1	1 ~ 7	102	39	46	64	1.8	116
	-HUT 4-102	4	M2 ~ M 8						
BT40	-HUD 7-135	1	1 ~ 7	135	85	60	72	3.8	251
	-HUA10-135	2	2.4 ~ 10					3.9	268
	-HUA20-135	3	5.8 ~ 20		77	78	88	4.8	392
	-HUT 4-135	4	M2 ~ M 8		85	60	72	3.8	251
	-HUT 6-135	5	M3 ~ M12		77	78	88	4.8	392
BT50	-HUD 7-150	1	1 ~ 7	150	85	60	72	6.6	277
	-HUA10-150	2	2.4 ~ 10					6.7	295
	-HUA20-150	3	5.8 ~ 20		77	78	88	7.5	440
	-HUT 4-150	4	M2 ~ M 8		85	60	72	6.6	277
	-HUT 6-150	5	M3 ~ M12		77	78	88	7.5	440
DN40A	-HUD 7-150	1	1 ~ 7	150	85	60	72	3.8	251
	-HUA10-150	2	2.4 ~ 10						268
DIN	-HUA20-150	3	5.8 ~ 20		77	78	88	5.0	392
	-HUT 4-150	4	M2 ~ M 8		85	60	72		
	-HUT 6-150	5	M3 ~ M12		77	78	88		
DN50A	-HUD 7-150	1	1 ~ 7	150	85	60	72	6.6	277
	-HUA10-150	2	2.4 ~ 10					6.7	295
DIN	-HUA20-150	3	5.8 ~ 20		77	78	88	7.0	440
	-HUT 4-150	4	M2 ~ M 8		85	60	72	6.6	277
	-HUT 6-150	5	M3 ~ M12		77	78	88	7.0	440
CT40	-HUD 7-150	1	.04 ~ .28	5.91	3.3	2.4	2.8	8.4	251
	-HUA10-150	2	.09 ~ .39		3.3	2.4	2.8	8.6	268
CAT.	-HUA20-150	3	.23 ~ .79		3	3.1	3.5	11.0	392
	-HUT 4-150	4	M2 ~ M 8		3.3	2.4	2.8	8.4	251
	-HUT 6-150	5	#4 ~ 1/2		3	3.1	3.5	11.0	392
CT50	-HUD 7-150	1	.04 ~ .28	5.91	3.3	2.4	2.8	14.6	277
	-HUA10-150	2	.09 ~ .39		3.3	2.4	2.8	14.8	295
CAT.	-HUA20-150	3	.23 ~ .79		3	3.1	3.5	15.4	440
	-HUT 4-150	4	M2 ~ M 8		3.3	2.4	2.8	14.6	277
	-HUT 6-150	5	#4 ~ 1/2		3	3.1	3.5	15.4	440

※Distance from a gage line to center of gravity × weight (kg・mm)

■**Option**
- DETa-1 Collet (HUD)→P.8 ●Spring collet (HUA)→P.8
- Tap sleeve (HUT)→P.8 ●Retention knob→P.64 ●Tools for assembly

■**Std. Access.**
- Fixing spanner ●Hexagonal wrench set ●Spanner (HUA) ●Low head bolt

■**Note**
- Other shanks such as HSK are also available upon request.

Cutting data ➔P. 13

Parts list ➔P. 105

■A product code example when ordering.

BT50-HUA20-150 - S 65

Holder

Positioning pin type

S : Straight pin
W : Expansion pin
T : Taper pin


Dimension S

50, 60, 65,
80, 85, 110 ...

Cutting data


90°type

S55C — ϕ12 Drill
n 670 min-1
Vf 80 mm/min
Vc 25.5 m/min
f 0.12 mm/rev




BT40-HFD12-120

S55C — M12 Tap
n 184 min-1
Vf 322 mm/min
Vc 7 m/min




BT40-HFT6-120

S50C — M16 Tap
n 60 min-1
Vf 120 mm/min
Vc 3 m/min




BT40-HFT12-135

S55C — ϕ10 Endmill 2-flutes
n 350 min-1
Vf 50 mm/min
Vc 11 m/min
fz 0.07 mm/t



BT40-HFD12-120


S50C — ϕ20 Endmill 2-flutes
n 158 min-1
Vf 32 mm/min
Vc 10 m/min
fz 0.10 mm/t



BT40-HFA20-135


mini type

S50C — ϕ6 Carbide drill
n 5000 min-1
Vf 250 mm/min
Vc 94 m/min
f 0.05 mm/rev




BT30-HFCS6-155

S50C — ϕ6 Carbide endmill 2-flutes
n 3500 min-1
Vf 210 mm/min
Vc 66 m/min
fz 0.03 mm/t



BT40-HFCS6-205


A7075 — ϕ6 Carbide endmill 2-flutes
n 5000 min-1
Vf 300 mm/min
Vc 94 m/min
fz 0.03 mm/t



BT30-HFCS6-155


UNIVERSAL type

S50C — ϕ10 Endmill 2-flutes
n 900 min-1
Vf 100 mm/min
Vc 28 m/min
fz 0.06 mm/t




BT50-HUA10-150

S50C — M8 Tap
n 250 min-1
Vf 312 mm/min
Vc 6.3 m/min




BT40-HUT4-135

S50C — M12 Tap
n 184 min-1
Vf 322 mm/min
Vc 7 m/min




BT40-HUT6-135

SUS304 — ϕ10 Drill
n 314 min-1
Vf 16 mm/min
Vc 9.9 m/min
f 0.05 mm/rev



BT50-HUA10-150

S50C — ϕ16 Endmill 2-flutes
n 140 min-1
Vf 40 mm/min
Vc 7 m/min
fz 0.14 mm/t




BT40-HUA20-135

ANGLE HEAD STANDARD type


High-rigidity standard type for end-milling appliications

MODULAR type
Shank and head can be combined freely to match the application.




AHB
AHC

SOLID type
The popular type that can chuck small- to large-diameter cutters.




AHA
AHD

FLANGE type
Heavy-duty type that mounts directly on the machine spindle surface.



F-AHA
F-AHD

UNIVERSAL type
Cutting angle can be adjusted arbitrarily.




AHU




Use of collet holder

To chuck a cutting tool, the collet chuck system is used, which has a long history of good performance. This product is applicable to all the types of machining, including drilling and milling.



Compact design

Ideal for internal machining.



Type	Model	Q	A	B
MODULAR type	AHB 5	62	57	46
	AHB 7	76	72	56
	AHB10	96	88	62
SOLID type FLANGE type	AHA20	171	160	88
	AHA25	193	180	90
UNIVERSAL type	AHU10	156	154	55
	AHU20	192	188.5	70

Body-through coolant

Coolant can be feed from a closer position to the cutting edge.Prevents heat generation inside the body to achieve high-speed rotation.
(MODULAR type、UNIVERSAL type)





MST's Quick Change system(AHD type)


By adopting the BT30 Quick Change mechanism at the angle axis, a large variety of machining applications are made possible.




Highest Guaranteed Accuracies

All standard type angle heads have passed an accuracy test and rotation test.

Squareness



Runout accuracy





Type	Model	L
MODULAR type	AHB 5 AHB 7 AHB10 AHC10	40
UNIVERSAL type	AHU10	
SOLID type FLANGE type	AHA20 AHA25 AHD30	50
UNIVERSAL type	AHU20	

Shank and head can be combined freely to match the application.

▷ Various types of shanks and heads are freely combined to meet your machining needs.







MODEL	Chucking range	Gear ratio Main spindle:Angle shaft	MAX. (min-1) Main spindle(CCW) : Angle shaft (CW)
AHB 5	ϕ0.5～ 5	1 : 1	5,000 : 5,000
AHB 7	ϕ0.5～ 7		6,000 : 6,000
AHB10	ϕ2.4～10		(When using body thru-coolant)
AHC10			

Fig. 1
AHB





Fig. 2
AHC



CODE	Fig.	ϕD	L	ϕC	L1	M	A	B	G	ϕQ	Kg	
BT40-AHB 5-210	1	0.5～ 5	210	12	20	85	25	32	46	62	5.5	ER8
-270			270			145					6.4	
-AHB 7-180		0.5～ 7	180	19	22	60	29	43	56	76	5.3	ESX12
-240			240			120					6.6	
-AHB10-195		2.4～10	195	36	29	80	38	50	63	96	6.2	C10
-255			255			140					7.9	
-AHC10-230	2		230		—	110	45	32.5	65	—	6.2	
BT50-AHB 5-225	1	0.5～ 5	225	12	20	85	25	32	47	62	8.8	ER8
-285			285			145					9.7	
-AHB 7-195		0.5～ 7	195	19	22	60	29	43	57	76	8.6	ESX12
-255			255			120					9.9	
-AHB10-210		2.4～10	210	36	29	80	38	50	62	96	9.5	C10
-270			270			140					11.2	
-AHC10-245	2		245		—	110	45	32.5	66	—	9.5	

Available for DIN / CAT.

Cutting data ➔P. 20

■**Option**
- Spring collet→P.19 ●Retention knob →P.64
- Semi-finished positioning block→P.19

■**Std. Access.**
- A complete set of spanners and wrenches.

■**Note**
- The phase of the drive key and the positioning pin is set freely.
- Standard specifications:
  S = 60 mm, 65 mm (BT40), 80 mm, 85 mm, and 110 mm (BT50).
- Other shanks such as HSK are also available upon request.

■**Caution**
- For the shape and mounting position of the positioning block, contact the machine manufacturer or MST.
- The height of the positioning pin depends on the shape of the positioning block.
- The machine spindle and angle shaft should rotate in reverse directions, so make sure the spindle rotates in the reverse direction.
- For precautions and maintenance, refer to page 115.

Shank / Head reference list

CODE	Shank	Head
BT40-AHB 5-210	BT40-MS- 98	MB 5-112
-270		-172
-AHB 7-180		MB 7- 82
-240		-142
-AHB10-195		MB10- 97
-255		-157
-AHC10-230		MC10-132
BT50-AHB 5-225	BT50-MS-113	MB 5-112
-285		-172
-AHB 7-195		MB 7- 82
-255		-142
-AHB10-210		MB10- 97
-270		-157
-AHC10-245		MC10-132

STANDARD type SOLID type

The popular type that can chuck small- to large-diameter cutters.




AHD



BT30 Quick-change type

AHA



BT50-AHA25-195

MODEL	Chucking range	Gear ratio Main spindle : Angle shaft	MAX. (min-1) Main spindle(CCW):Angle shaft(CW)
AHA20	ϕ5.8~20	1:0.81	3000:2430
AHA25	ϕ5.8~25	1:0.96	2500:2400
AHD30	BT30 tools		

Fig. 1
AHA





Fig. 2
AHD



CODE	Fig.	ϕD	L	L1	M	A	B	G	ϕC	J	ϕQ	Kg	
BT40-AHA20-160	1	5.8~20	160	40	85	65	95	88	50	65	171	7.3	C20
BT50-AHA20-195	1	5.8~20	195	40	89	65	95	88	50	65	171	13.1	C20
-250			249									14.8	
-AHA25-195		5.8~25	195	44	93	70	110	90	62	70	193	13.6	C25
-250			249									15.3	
-AHD30-195	2	—	195				112.6					14.7	—

■Option
- Spring collet→P.19 ●Retention knob →P.64 ●Semi-finished positioning block→P.19

■Std. Access.
- A complete set of spanners and wrenches

■Note
- The phase of the drive key and the positioning pin is set freely.
- Standard specifications: S = 60 mm, 65 mm (BT40), 80 mm, 85 mm, and 110 mm (BT50).
- Other shanks such as HSK are also available upon request.


■Caution
- For the shape and mounting position of the positioning block, contact the machine manufacturer or MST.
- The height of the positioning pin depends on the shape of the positioning block.
- The machine spindle and angle shaft should rotate in reverse directions, so make sure the spindle rotates in the reverse direction.
- For precautions and maintenance, refer to page 115.

Available for **DIN / CAT.**

Cutting data
P. 20

STANDARD type **FLANGE** type







MODEL	Chucking range	Gear ratio Main spindle : Angle shaft	MAX. (min⁻¹) Main spindle(CCW):Angle shaft(CW)
AHA20	ϕ5.8～20	1:0.81	3000:2430
AHA25	ϕ5.8～25	1:0.96	2500:2400
AHD30	BT30 tools	1:0.96	

Fig. 1
AHA





Fig. 2
AHD



CODE	Fig.	ϕD	L	L1	L2	M	A	B	G	ϕC	J	ϕQ	Kg	
F190-AHA20-200	1	5.8～20	200	40	160	89	65	95	88	50	65	171	18	C20
-350			350		310								28	
-AHA25-200		5.8～25	200	44	160	93	70	110	90	62	70	193	18.5	C25
-350			350		310								28.5	
-AHD30-200	2	—	200		160					66			19.6	—
-350			350		310			112.6					29.8	

■**Option**
- Spring collet→P.19 ●Retention knob →P.64

■**Std. Access.**
- A complete set of spanners and wrenches
- Standard mounting plate(No mounting holes are provided.)
- Mounting bolts for ANGLE HEAD

■**Note**
- NT50U shank is also available.

■**Caution**
- For mounting plate shapes and mounting bolt location, contact the machine manufacturer or MST.
- The machine spindle and angle shaft should rotate in reverse directions, so make sure the spindle rotates in the reverse direction.
- For precautions and maintenance, refer to page 115.


STANDARD type UNIVERSAL type

Machining at every angle is possible with just this one unit.


Splash coolant-through body

Whatever machining angle is set, coolant is properly supplied to the cutting edge.






AHU



MODEL	Chucking range	Gear ratio Main spindle : Angle shaft	MAX. (min⁻¹) Main spindle(CW):Angle shaft(CW)
AHU10	ϕ2.4~10	1 : 1.5	3000 : 4500
AHU20	ϕ5.8~20	1 : 1	3000 : 3000



CODE	ϕD	L	L1	M	A	B	K	G	ϕC	ϕQ	Kg	
BT40-AHU10-175	2.4~10	175	42	96	49	105	95	55	32	156	9.6	C10
BT50-AHU10-190	2.4~10	190	42	90	49	105	95	55	32	192	13.9	C10
-AHU20-200	5.8~20	200	54	112	58.5	130	120	70	50		15.8	C20

■**Option**
- Spring collet →P.19 ●Retention knob →P.64 ●Semi-finished positioning block →P.19 ●Test bar

■**Std. Access.**
- A complete set of spanners and wrenches

■**Note**
- The phase of the drive key and the positioning pin is set freely.
- Standard specifications: S = 60 mm, 65 mm (BT40), 80 mm, 85 mm, and 110 mm (BT50).
- Products other than BT shanks can be manufactured upon request.

■**Caution**
- For the shape and mounting position of the positioning block, contact the machine manufacturer or MST.
- The machine spindle and angle shaft should rotate in reverse directions, so make sure the spindle rotates in the reverse direction.
- The machine spindle and angle shaft should rotate in forward directions, so make sure the spindle rotates in the forward direction.
- For precautions and maintenance, refer to page 115.

Test bar

Use for super accurate angle adjustment.


CODE	Holder type
TBU10	AHU10
TBU20	AHU20



Available for **DIN / CAT.**

Cutting data ➔P. 20

SPRING COLLET




CODE	φD	φD1	L	H	Holder type
ER8-D	1 ～ 5 (0.5 Steps)	8.5	13.5	-	AHB 5
ESX12-D	1 ～ 3 (0.5 Steps)	12	19.5	-	AHB 7
	4 ～ 7 (1.0 Steps)				
C10-D	2.6～ 5.8 (0.2 Steps)	17.2	26	18	AHB10 AHC10 AHU10
	6 ～10 (0.2 Steps)			20	
C20-D	6 ～ 9.8 (0.2 Steps)	29.5	50	32	AHA20 AHU20
	10 ～15.8 (0.2 Steps)			35	
	16 ～20 (0.2 Steps)			40	
C25-D	6 , 8	36.5	68	38	AHA25
	10 ～15 (0.5 Steps)			48	
	15.5～20 (0.5 Steps)			54	
	20.5～25 (0.5 Steps)			57	

■Option
- Collet remover (C10 , C20) →P.38

Semi-finished positioning block

The semi-finished positioning block must be modified to the appropriate shape by the customer after delivery. Determine the shape and dimensions as follows, and then modify the positioning block as necessary.



CODE	A	B	C	W	H	d	Spindle	Material
AB-15	15	43	58	92	58	20	BT40	S50C
-12	20		63	120	63	28	BT50	

1. Obtain the machine manufacturer's drawing for the positioning block and modify the positioning block in accordance with that drawing.
2. Determine the dimensions as shown in the instruction and then modify.
   - This block may not be applicable for dimensional reasons. Carefully check to see whether the positioning block is applicable.
   - The positioning block exclusively for your machine may also be available on request.
   - For further information, please contact MST.

Custom-made products

We are proud of our over 35 years of experience custom making products for our customers. We can produce the best product for you depending on your applications such as O.D and I.D machining thanks to our accumulated know-how.


35 years — Manufacturing history

1 unit — Production starting from just 1 unit


2~4 months — Delivery

19,300 units — Custom : 1,300 units Design
Standard : 18,000 units


ANGLE HEAD CUSTOM DESIGN



For more information, please contact us.




Dual side machining ANGLE HEAD




Medical equip-ment
AL
MAX 1500min-1
BT50

Side face machining ANGLE HEAD




0.57
MAX 400min-1
Direct mount

Internal bore surface machining ANGLE HEAD



AL
1.76
MAX 2650min-1
BT50

Internal bore surface machining ANGLE HEAD




3
MAX 4500min-1
Direct mount


Cutting data

MODULAR type


SUS304 | ϕ10 Endmill 2 flutes
n 640 min-1
Vf 60 mm/min
Vc 20 m/min
fz 0.05 mm/t



A2017 | ϕ10 Carbide endmill 2 flutes
n 4000 min-1
Vf 400 mm/min
Vc 126 m/min
fz 0.05 mm/t




S50C | ϕ10 Endmill 2 flutes
n 640 min-1
Vf 60 mm/min
Vc 20 m/min
fz 0.05 mm/t




SOLID type


A2017 | ϕ16 Endmill 2 flutes
n 1800 min-1
Vf 130 mm/min
Vc 90 m/min
fz 0.04 mm/t




SUS304 | ϕ12 Endmill 2 flutes
n 527 min-1
Vf 20 mm/min
Vc 60 m/min
fz 0.06 mm/t




SUS304 | ϕ16 Endmill 2 flutes
n 570 min-1
Vf 40 mm/min
Vc 29 m/min
fz 0.04 mm/t




S55C | ϕ12 Drill 2 flutes
n 527 min-1
Vf 39 mm/min
Vc 20 m/min
f 0.07 mm/rev



FC30 | ϕ12 Endmill 2 flutes
n 816 min-1
Vf 60 mm/min
Vc 31 m/min
fz 0.04 mm/t




S50C | ϕ16 Endmill 2 flutes
n 630 min-1
Vf 80 mm/min
Vc 32 m/min
fz 0.06 mm/t




UNIVERSAL type

A2017 | ϕ10 Endmill 2 flutes
n 2000 min-1
Vf 200 mm/min
Vc 63 m/min
fz 0.07 mm/t



S50C | ϕ20 Carbide endmill 2 flutes
n 350 min-1
Vf 70 mm/min
Vc 22 m/min
fz 0.1 mm/t



M/C Tool

Pull collet type collet chuck
DETa-1 Collet Holder



DTA
DTB
DTE

P. 22

Retension knob

P. 64

Taper collet chuck
COLLET HOLDER



CTH
CTA

P. 32

Needle-roller type chuck
Hi-ART MILLING CHUCK



ART

P. 40


End-mill holder for ultra-heavy duty application
SUMMIT



SLZ

P. 43


The face mill arbor for through-spindle coolant
FMH RIGID type



FMH-H

P. 46

The arbor for screw-in End Mill
RED SCREW arbor



RSG

P. 48

Cutter arbor with spindle-through coolant



FMH

P. 53

Fine adjustment boring holder
MICRO HEAD



MFA
MBH
MBJ

P. 55


DETa-1 Collet Holder

Pull collet type collet chuck


2mm collapsibility with just one collet !!

- Just 6 collets is all it takes to chuck 106 sizes of drills.
- Slim design due to no tightening nut at the tip of holder.
- Compatible with synchronized tapping. Provides simple tooling lay-out.






Pull collet design



DTA

Nut-tightening type of easy operation






DTB

For high-speed cutting, High cost performance




Coolant-through





DTE


Fully applicable for coolant-through



3 types of coolant-through systems available using coolant cap & spacer ➔ P.30

Coolant-through

	ϕD
DTE 7	29
DTE12	40



DETa-1 Collet

Using a high-precision collet will increase the life of your tools.
P. 117


Highest guaranteed accuracies throughout entire chucking range (100% inspection).

Both large collapsibility and precise chucking achieved by the pull collet design.



Collet	Run-out accuracy(μm)	
	D3	D7/D12
Precision Collet	3 (6)	5 (10)
Standard Collet	5 (10)	10 (15)

※Accuracy of collet alone,
( ) means collapsibility usable.



D	L
~10	4×D
10~13	40

Reduces the number of conventional collets needed by 90% (in-house comparison)




Ten collets

Only one collet !

D3 Collet

DTA3
DTB3

Uses a maraging steel. Initial accuracy lasts for a long period of time.






ϕ0.5~3.175 — 8 pcs.

D7 Collet

DTA7
DTB7
DTE7





ϕ1~7 — 8 pcs.

D12 Collet


DTA12
DTB12
DTE12





ϕ2.5~13 — 6 pcs.


Slim and compact without the nut at the tip.



Size	ϕD
3 type	10
7 type	21
12 type	30

Pre-balanced design (DTE type)

The collet holder is pre-balanced by previously designing the holder to be as axisymmetrical as possible.
When used with the precision collet, it enables stable machining during high-speed machining.




Longer cutter life using through-spindle capability
P. 117

Coolant-through system

Pressure 7 Mpa


Multiple coolant supply systems.
The best methods can be chosen from three options.



Coolant-through cutter

For a cutting tool with oil holes. The shank of the cutting tool is sealed with an O-ring, enabling reliable coolant supply. Compatible with small-diameter cutting tools starting from 3 mm.

DTE type



"SUKIMA-through" coolant-around tool

High-pressure coolant performance can be obtained even when using a cutting tool without oil holes.

DTE type




Coolant-through collet

Coolant is supplied through the slits in the collet. No dedicated optional parts are required.

DTB type
DTE type

DETa-1 Collet Holder A type (DTA)



BT30-DTA3-90


BT50-DTA12-135


S32-DTA12-100

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5





Fig. 6



CODE	Fig.	ϕD	L	ϕC	L1	L2	L3	ϕC1	ϕC2	ϕD1	Kg	N
BT30-DTA 3- 90	1	0.5～ 3.175	90	10	27	26	15	22	25	—	0.5	2.4
-DTA 7- 90		1 ～ 7		21	30	37	1	38	42		0.7	6.7
-120			120		60						0.8	7.9
-DTA12-120		2.5 ～13		30	52.5	42	3.5	45	45		1.0	10.4
BT40-DTA 3- 95	1	0.5～ 3.175	95	10	27	26	15	22	25	—	1.1	3.9
-125			125				45				1.2	4.3
-DTA 7-105		1 ～ 7	105	21	38	37	3	38	60		1.3	8.5
-135			135		60		11		43		1.4	9.5
-165			165				41				1.7	10.8
-195			195				71				2.1	12.1
-DTA12-120		2.5～13	120	30	52.5	40	0.5	45	58		1.5	11.6
-150			150		75		8		50		1.7	13.8
-180			180				38				2.1	15.5
-210			210				68				2.6	17.1
BT50-DTA 7-105	1	1 ～ 7	105	21	30	37	—	38	—	—	3.8	15.5
-135			135		60						3.9	16.6
-165			165				30		43		4.0	18.0
-195			195				60				4.4	19.5
-255			255				120				5.0	18.2
-315	2		315								5.9	19.1
-DTA12-135	1	2.5～13	135	30	52.5	40	4.5	45	50		4.1	19.4
-165			165		75		12				4.3	21.6
-195			195				42				4.7	23.4
-255			255				102				5.5	22.3
-315	2		315								6.6	23.3
A63 -DTA 3- 90	3	0.5～ 3.175	90	10	27	26	11	22	25	—	0.8	3.0
-120			120				41				1.0	3.4
-DTA 7-105		1 ～ 7	105	21	30	37	12	38	50		1.1	17.3
-120			120		38		19				1.3	18.3
-150			150		60		27				1.7	20.3
-DTA12-120		2.5～13	120	30	52.5	40	1.5	45			1.2	21.9
-150			150		75		9				1.4	25.2
-180			180				39				1.8	27.7

CODE	Fig.	φD	L	φC	L1	L2	L3	φC1	φC2	φD1	Kg (lbs)	N
A100 -DTA 7-135	3	1 ～ 7	135	21	30	37	39	38	50	—	2.7	33.8
-165			165		60						2.8	35.5
-225			225				99				3.7	33.6
-DTA12-135		2.5～13	135	30	52.5	40	13.5	45			2.7	37.1
-165			165		75		21				2.9	40.4
-225			225				81				3.8	39.7
E32 -DTA 3- 75	4	0.5～ 3.175	75	10	27	26	2	22	25	—	0.2	1.8
E40 -DTA 3- 75	4	0.5～ 3.175	75	10	27	26	2	22	25	—	0.3	1.7
E50 -DTA 3- 80	4	0.5～ 3.175	80	10	27	26	1	22	25	—	0.5	2.1
F63 -DTA 3- 90	4	0.5～ 3.175	90	10	27	26	11	22	25	—	0.8	2.3
-120			120				41	27	26		0.9	2.7
DN40A-DTA 3- 95	1	0.5～ 3.175	95	10	27	26	10.8	22	25	—	1.1	4.6
-125			125				40.8				1.2	5.0
DIN -DTA 7-105		1 ～ 7	105	21	30	43.8	12.1	38	45		1.2	11.9
-135			135		60	37	18.9				1.3	14.4
-DTA12-130		2.5～13	130	30	52.5	56.9	—	45	—		1.5	18.0
-160			160		75	66.4					1.7	20.0
DN50A-DTA 7-135	1	1 ～ 7	135	21	60	37	3	38	50	—	3.4	20.1
-165			165				33		43		3.6	20.0
DIN -195			195				63				3.9	20.6
-DTA12-135		2.5～13	135	30	52.5	40	7.5	45	50		3.6	21.5
-165			165		75		15				3.8	25.8
-195			195				45				4.2	26.4
CT40 -DTA 3- 95	1	.02～.13	3.74	0.39	1.06	1.02	.28	.87	.98	—	2.4	4.4
-125			4.92				1.46				2.7	4.8
CAT. -DTA 7-102		.04～.28	4.01	0.83	1.18	1.46	.63	1.49	1.75		2.8	8.1
-132			5.19		2.36						2.9	9.3
-DTA12-130		.10～.51	5.11	1.18	2.08	1.57		1.77			3.3	11.7
-152			5.98		2.95		.61				3.8	13.5
CT50 -DTA 7-102	1	.04～.28	4.01	0.83	1.18	1.46	.63	1.49	2.75	—	7.1	11.8
-132			5.19		2.36						7.3	13.0
CAT. -152			5.98				.71			1.69	7.7	13.9
-203			7.87				2.71				8.6	14.0
-DTA12-130		.10～.51	5.11	1.18	2.08	1.57	.73	1.77		—	7.7	15.6
-152			5.98		2.95		.71				7.9	17.5
-203			7.87				2.09		1.97		9.3	18.3
ST16 -DTA 3	5	0.5～ 3.175	60	10	27	60	—	22	25	16	—	—
ST20 -DTA 3	5	0.5～ 3.175	60	10	27	60	—	22	—	20	—	—
ST32T-DTA 7- 75	6	1 ～ 7	75	21	31.5	100	—	38	—	32	—	—
-105			105		61.5							
-DTA12-105		2.5～13		30	52.5			45				
-135			135		75							
S32 -DTA 7- 75	6	1 ～ 7	75	21	31.5	70	—	38	—	32	—	—
-DTA12-100		2.5～13	100	30	52.5			45				

■**Option**
- DETa-1 collet→P.31 ●Spanner→P.31 ●Retention knob(BT)→P.64
- Cleaning tool→P.31


■**Std. Access.**
- Coolant duct(Fixed)(HSK-A)→P.104 ●Rod(DTA3)

■**Note**
- Swing type coolant ducts are available upon request(HSK-A). For details, please contact us.


■**Caution**
- HSK-E and F shank don't come with a coolant duct and cannot be attached.
- ATC may not be possible for some machining centers with BT30-DTA12-120.
- For precautions and maintenance, refer to page 115.

Rod (DTA3 type)

These are necessary when attaching a collet to the holder (DTA3).




CODE	Holder type	Q'ty
PR-DTA3	DTA3	2pcs.



Cutting data ➔P.29

DETa-1 Collet Holder B type (DTB)



BT40-DTB7-105

Fig. 1





Fig. 2




E40-DTB3-70

Fig. 3





Fig. 4




S32-DTB7-15

Fig. 5





Fig. 6



CODE	Fig.	ϕD	L	ϕC	L1	L2	L3	L4	ϕC1	ϕD1	Kg	N
BT30-DTB 3- 90	1	0.5～ 3.175	90	10	27	13	28	—	25	—	0.6	1.7
-DTB 7- 75		1 ～ 7	75	21	53	—	—		—		0.5	2.4
-105			105		83							3.4
-DTB12- 75		2.5～13	75	30	53							
-105			105		83						0.7	5.6
BT40-DTB 3- 80	1	0.5～ 3.175	80	10	27	13	13	—	25	—	1.3	2.8
-110			110				43				1.4	3.2
-110L					57		13				1.3	2.8
-DTB 7- 60		1 ～ 7	60	21	33	—	—		—		1.0	3.7
-105			105		78						1.1	4.8
-135			135		75	11.8	21.2		30		1.3	5.2
-165			165		75.5	35.3	27.2		40		1.6	5.4
-195			195				57.2				1.9	5.6
-DTB12- 90		2.5～13	90	30	63	—	—		—		1.2	5.3
-120			120		93						1.3	7.6
-150			150		105	11.8	6.2		40		1.5	8.4
-180			180				36.2				1.8	8.7
-210			210				66.2				2.1	8.9
BT50-DTB 7- 75	1	1 ～ 7	75	21	37	—	—	—	—	—	3.5	11.7
-105			105		67						3.7	12.3
-135			135		75	11.8	10.2		30		3.8	18.6
-195			195			58.8	23.2		50		4.6	25.0
-255			255		75.5	82.3	59.2		60		6.1	27.6
-315	2		315		75	58.8	43.7	99.5	50		7.4	33.9
-DTB12- 75	1	2.5 ～13	75	30	37	—	—	—	—		3.7	12.5
-105			105		67						3.9	14.8
-135			135		97						4.0	15.3
-195			195		105	35.3	16.7		50		4.7	24.3
-255			255			58.8	53.2		60		5.9	28.4
-315	2		315				50.2	63			7.5	34.1
A63 -DTB 3- 75	3	0.5～ 3.175	75	10	27	13	4	—	25	—	0.8	6.9
-105			105				34				0.9	7.5
-105L					57		4				0.8	7.0

CODE	Fig.	φD	L	φC	L1	L2	L3	L4	φC1	φD1	Kg (lbs)	N
E25 -DTB 3- 58	3	0.5～ 3.175	58	10	27	16	4.6	—	18	—	0.1	0.4
E32 -DTB 3- 65	3	0.5～ 3.175	65	10	27	16	4.5	—	20	—	0.2	0.6
-DTB 7- 65K	4	1 ～ 7		21	30	14.2	10.8		26			0.9
E40 -DTB 3- 70	3	0.5～ 3.175	70	10	27	13	—	—	20	—	0.3	0.9
-DTB 7- 95	4	1 ～ 7	95	21	50	11.8	13.2		30		0.4	1.6
-DTB12-110		2.5～13	110	30	90	—	—		—		0.5	2.8
E50 -DTB 3- 75	3	0.5～ 3.175	75	10	27	16	1.5	—	20	—	0.5	1.7
-DTB 7-100	4	1 ～ 7	100	21	50	11.8	12.2		30		0.6	3.2
-DTB12-115		2.5～13	115	30	89	—	—		—		0.8	4.2
F63 -DTB 3- 75	3	0.5～ 3.175	75	10	27	13	4	—	25	—	0.8	2.1
-105			105				34				0.9	2.5
-105L					57		4				0.8	2.1
F63M-DTB 7-100	4	1 ～ 7	100	21	50	11.8	12.2	—	30	—	0.9	3.3
-DTB12-120		2.5～13	120	30	70				40		1.1	4.8
DN40AD-DTB 3- 80	1	0.5～ 3.175	80	10	27	13	18.8	25	—	—	1.2	3.5
-110			110				38.8				1.3	3.6
DIN -110L					57		18.8				1.2	3.9
-DTB 7-105		1 ～ 7	105	21	74	—	12.1	—	44.45		1.1	4.8
-135			135		75	11.8	17		30		1.2	5.0
-DTB12-105		2.5～13	105	30	74	—	12.1		44.45		1.2	5.7
-135			135		104						1.3	8.0
DN50AD-DTB 7-135	1	1 ～ 7	135	21	75	11.8	13.2	15.9	30	—	3.3	14.9
-195			195			58.8	26.2		50		4.1	21.5
DIN -DTB12-135		2.5～13	135	30	100	—	—		—		3.5	11.7
-195			195		105	35.3	19.7		50		4.2	20.8
CT40 -DTB 3- 80	1	.02～.13	3.15	.39	1.06	.51	.20	.98	—	—	2.4	3.3
-110			4.33				1.38				2.7	3.7
CAT. -110L					2.24		.20				2.4	3.3
-DTB 7-105		.04～.28	4.13	.83	2.76	—	.63	—	1.75		2.4	4.6
-135			5.31		2.95	.46	.52		1.18		2.9	5.2
-DTB12-120		.10～.51	4.72	1.18	3.34	—	.63		1.75		1.3	7.5
-150			5.91		3.66	.88	.62				3.5	8.5
CT50 -DTB 7-135	1	.04～.28	5.31	.83	2.91	.46	.52	—	1.18	—	7.3	14.8
-195			7.68			2.31	1.03		1.97		9.0	21.4
CAT. -DTB12-135		.10～.51	5.31	1.18	3.94	—	.63		2.75		7.7	11.6
-195			7.68		4.13	1.39	.78		1.97		9.0	20.8
ST12 -DTB 3	5	0.5～ 3.175	29	10	25	61	—	—	—	12	—	—
ST16 -DTB 3	5	0.5～ 3.175	38.5	10	27	81.5	—	—	—	16	—	—
ST20 -DTB 3	5	0.5～ 3.175	48	10	27	102	—	—	—	20	—	—
ST25T-DTB 7- 15	6	1 ～ 7	15	21	110	—	—	—	—	25	—	—
- 45			45									
- 75			75									
ST32T-DTB 7- 15	6	1 ～ 7	15	21	92	—	—	—	—	32	—	—
- 45			45									
- 75			75									
-DTB12- 15		2.5～13	15	30								
- 45			45									
- 75			75									
S32 -DTB 7- 15	6	1 ～ 7	15	21	70	—	—	—	—	32	—	—
-DTB12- 40		2.5～13	40	30								


■**Option**
- DETa-1 collet→P.31 ●Wrench→P.31 ●Retention knob(BT)→P.64
- Cleaning tool→P.31

■**Std. Access.**
- Coolant duct(Fixed)(HSK-A)→P.104

■**Note**
- Swing type coolant ducts are available upon request(HSK-A). For details, please contact us.
- BT30-DTB12 requires the dedicated retention knob,which has the feature of draw bolt. Please choose P-538 or P-535.

■**Caution**
- For the E32-DTB7-65K, collet collapsibility is not available. The clamping diameter applies only to nominal end-mill shank size.
- HSK-E shank doesn't come with a coolant duct and cannot be attached.
- For precautions and maintenance, refer to page 115.

Retention knob for BT30-DTB12



CODE	φD	φd	θ	Note
P-538	8	4	45	In accordance with MAS-1
-535	7.5	2.5	60	In accordance with MAS-2

Cutting data ➔P. 29

DETa-1 Collet Holder E type (DTE)



BT40-DTE7-120

Fig. 1





Fig. 2




A63-DTE12-120

Fig. 3





Fig. 4



CODE	Fig.	φD	L	φC	L1	L2	L3	φC1	φC2	Kg	N
BT30-DTE 7- 60-MAS1	1	1 ～ 7	60	24	38	11.5	—	29	—	0.6	3.2
-MAS2											
-DTE12- 75-MAS1		2.5～ 13	75	34	53	14		40		0.9	4.9
-MAS2											
BT40-DTE 7- 90	1	1 ～ 7	90	24	63	11.5	—	29	—	1.3	4.9
-120	2		120		70		23		40	1.5	6.2
-150			150				53		50	1.9	7.2
-180			180				83			2.4	8.9
-210			210				113			2.9	9.8
-DTE12- 90	1	2.5～ 13	90	34	63	14	—	40	—	1.5	6.1
-120			120		93					1.8	7.4
-150			150		123					2.1	9.4
-180	2		180		140		13		50	2.5	9.6
-210			210				43			2.9	11.7
BT50-DTE 7-105	1	1 ～ 7	105	24	67	11.5	—	29	—	3.9	15.6
-135	2		135		70		27		40	4.2	16.5
-165			165				57		50	4.6	18.7
-225			225				117		60	6.0	24.4
-285			285				177			7.3	30.1
-DTE12-105	1	2.5～ 13	105	34	67	14	—	40	—	4.2	16.6
-135			135		97					4.5	18.9
-165			165		127					4.8	21.0
-225	2		225		140		47		60	5.7	24.5
-285			285				107		70	7.6	27.1
A40 -DTE 7- 95	3	1 ～ 7	95	24	75	11.5	—	29	—	0.6	4.4
-DTE12-105		2.5～ 13	105	34	85	14		40		0.9	14.4
A50 -DTE 7-105	3	1 ～ 7	105	24	79	11.5	—	29	—	0.7	9.8
-DTE12-120		2.5～ 13	120	34	94	14		40		1.1	12.5
A63 -DTE 7-105	4	1 ～ 7	105	24	70	11.5	9	29	40	1.1	12.3
-120			120				24			1.2	12.8
-150			150				54		50	1.7	14.3
-180			180				84			2.1	15.7
-DTE12-120	3	2.5～ 13	120	34	94	14	—	40	—	1.5	14.9
-150			150		124					1.8	16.0
-180	4		180		140		14		50	2.3	19.1
A100-DTE 7-135	4	1 ～ 7	135	24	70	11.5	36	29	40	2.7	31.0
-165			165				66		50	3.2	32.4
-225			225				126		60	4.7	35.7
-DTE12-135	3	2.5～ 13	135	34	106	14	—	40	—	3.0	33.1
-165			165		136					3.3	36.2
-225	4		225		140		56		60	4.4	40.3

CODE	Fig.	ϕD	L	ϕC	L1	L2	L3	ϕC1	ϕC2	Kg (lbs)	N
DN40AD-DTE 7- 90	2	1 ～ 7	90	24	58	11.5	12.9	29	45	1.2	5.4
-120			120		70		30.9			1.4	6.4
DIN -DTE12- 90		2.5～13	90	34	58.8	14	12.1	40		1.3	6.1
-150			150		118.8					1.9	9.3
DN50AD-DTE 7-105	2	1 ～ 7	105	24	70	11.5	15.9	29	70	3.4	12.0
-165			165				60		50	4.2	15.1
DIN -DTE12-105		2.5～13	105	34		14	15.9	40	70	3.6	12.6
-165			165		130					4.2	17.0
CT40-DTE 7- 90	2	.04～.28	3.54	.94	2.17	.45	.63	1.14	1.75	2.7	5.2
-120			4.72		2.75		1.22			3.3	6.2
CAT. -DTE12- 90		.10～.51	3.54	1.34	2.17	.55	.63	1.57		3.1	6.1
-150			5.91		4.53					4.2	9.6
CT50-DTE 7-105	2	.04～.28	4.13	.94	2.75	.45	.63	1.14	2.75	7.5	11.8
-165			6.5				2.36		1.97	9.0	15.0
CAT. -DTE12-105		.10～.51	4.13	1.34		.55	.63	1.57	2.75	7.9	12.9
-165			6.5		5.12					9.3	17.3

■**Option**
- DETa-1 collet→P.31 ●Wrench→P.31 ●Retention knob(BT40/50)→P.64
- Tap rod (DTE12) →P.30 ●Spacer ●Coolant cap
- Spacer set ●Coolant-through system

■**Std. Access.**
- Coolant duct(Fixed)(HSK-A)→P.104 ●Retention knob(BT30)

■**Note**
- Swing type coolant ducts are available upon request(HSK-A). For details, please contact us.


■**Caution**
- A dedicated retention knob is supplied with the BT30-DTE as a standard accessory. When ordering, specify whether a MAS-1 or MAS-2 retention knob is required. To replace the retention knob, please contact us.
- For precautions and maintenance, refer to page 115.

Cutting data


DTA type

S50C — ϕ3 Carbide drill 3 flutes
n 9000 min-1 | Vf 900 mm/min | Vc 85 m/min | f 0.1 mm/rev


E32-DTA3-75

S50C — ϕ3 Carbide Square endmill 3 flutes
n 6000 min-1 | Vf 150 mm/min | Vc 60 m/min | fz 0.013 mm/t


E32-DTA3-75

Aluminum — ϕ8.5 Carbide drill
n 10000 min-1 | Vf 5000 mm/min | Vc 267 m/min | f 0.5 mm/rev


BT40-DTA12-165


DTB type

A6061 — ϕ0.8 Straight drill
n 6000 min-1 | Vf 60 mm/min | Vc 15 m/min



BT40-DTB3-110L

A5052 — ϕ0.8 Straight drill
n 10000 min-1 | Vf 400 mm/min | Vc 25 m/min


※234 pcs.
A63-DTB3-75

S50C — R1.5 Carbide ball endmill
n 12500 min-1 | Vf 1560 mm/min | Vc 120 m/min | f 0.125 mm/rev


E32-DTB3-65

S50C — ϕ3 Carbide Square endmill 2 flutes
n 6000 min-1 | Vf 150 mm/min | Vc 60 m/min | fz 0.013 mm/t



E32-DTB3-65

S50C — R1.5 Carbide ball endmill
n 12500 min-1 | Vf 1560 mm/min | Vc 120 m/min | f 0.125 mm/rev



E32-DTB3-65

STAVAX(42HRC) — ϕ0.6 Carbide straight drill
n 3715 min-1 | Vf 30 mm/min | Vc 7 m/min | f 0.01 mm/rev


F63-DTB3-75


SKD61(46HRC) — R3 Carbide ball endmill 2 flutes
n 5000 min-1 | Vf 1500 mm/min | Vc 94 m/min | fz 0.15 mm/t


BT40-DTB7-105


SKD61(46HRC) — ϕ10 Carbide endmill 2 flutes
n 4500 min-1 | Vf 1500 mm/min | Vc 141 m/min | fz 0.17 mm/t


BT40-DTB12-90

DTE type

S50C — ϕ6 Carbide drill
n 6369 min-1 | Vf 1592 mm/min | Vc 120 m/min | f 0.25 mm/rev


A63-DTE7-105


SKD61(53HRC) — R5 Carbide ball endmill 2 flutes
n 20000 min-1 | Vf 6000 mm/min | Vc 628 m/min | fz 0.15 mm/t



A63-DTE12-120

Tap rod (DTE12type)

To be used as a stopper for synchronized tapping.








CODE	Applicable taps	φD	W	Collet
TR-5	JIS M 8	10.5	5	D12-12
-5.5	JIS M10		5.5	
-6	OSG M 8 M10		6	
-6.5	JIS M12		6.5	
-8	OSG M12	12	8	-13

COOLANT-THROUGH SYSTEM (OPTION)


Spacer

EA type




CODE	Holder type	φD	Q'ty
7EA- 3.5-3	DTE 7	3 ~ 3.5	3pcs. 1set
- 4 -3		3.5~ 4	
- 4.5-3		4 ~ 4.5	
- 5 -3		4.5~ 5	
- 5.5-3		5 ~ 5.5	
- 6 -3		5.5~ 6	
- 6.5-3		6 ~ 6.5	
- 7 -3		6.5~ 7	
12EA- 3.5-3	DTE12	3 ~ 3.5	3pcs. 1set
- 4 -3		3.5~ 4	
- 4.5-3		4 ~ 4.5	
- 5 -3		4.5~ 5	
- 5.5-3		5 ~ 5.5	
- 6 -3		5.5~ 6	
- 6.5-3		6 ~ 6.5	
- 7 -3		6.5~ 7	
- 8 -3		7 ~ 8	
- 9 -3		8 ~ 9	
-10 -3		9 ~10	
-11 -3		10 ~11	
-12 -3		11 ~12	
-13 -3		12 ~13	

EBM type (Groove-type)



CODE	Holder type	φD	Q'ty
7EBM- 3-3	DTE 7	3	3pcs. 1set
- 4-3		4	
- 6-3		6	
12EBM- 3-3	DTE12	3	3pcs. 1set
- 4-3		4	
- 6-3		6	
- 8-3		8	
-10-3		10	
-12-3		12	

EBS type (Round-type)



CODE	Holder type	φD	S	Q'ty
7EBS- 3.6-3	DTE 7	3	3.1	3pcs. 1set
- 4.5-3		4	3.3	
- 6.4-3		6	3.9	
12EBS- 3.6-3	DTE12	3	3.1	3pcs. 1set
- 4.5-3		4	3.3	
- 6.4-3		6	3.9	
- 8.4-3		8	4.6	
-10.3-3		10	4.8	
-12.3-3		12		

Spacer blank type

Depend on cutter or application, please modify.




CODE	Holder type	Q'ty
7EBF-BL-5	DTE 7	5pcs. 1set
12EBF-BL-5	DTE12	

Spacer set


CODE	Holder type	Contents of set			
		Spacer	Q'ty	Coolant cap	Q'ty
7ES-A	DTE 7	7EA -3.5~7	(1ea.) total 14pcs.	CLP- 7E	1pc.
		7EBM-3 , 4 , 6			
		7EBS-3.6 , 4.5 , 6.4			
12ES-A	DTE12	12EA -3.5~13	(1ea.) total 26pcs.	CLP-12E	1pc.
		12EBM-3~12			
		12EBS-3.6~12.3			



■Std. Access.
● Collet driver




Coolant cap



CODE	Holder type	φD	φC	H
CLP- 7E	DTE 7	21	29	14
-12E	DTE12	30	40	18

DETa-1 COLLET




Highest guaranteed accuracies throughout entire chucking range(100% inspection)

Collet	Run-out accuracy(μm)	
	D3	D7 / D12
Precision Collet	3 (6)	5 (10)
Standard Collet	5 (10)	10 (15)

※Accuracy of collet alone,
( ) means collapsibility usable.

D	L
～10	4×D
10～13	40




CODE		ϕD	Holder type	Collapsibility	ϕD1	L	H1	H2
Standard Collet	Precision Collet							
D 3- 0.6	Add "-P" after the standard type item code. 〈 Example 〉 D12 - 6 - P	0.5 ～ 0.6	DTA 3 DTB 3	0.1	7	40	30	6.9
- 0.8		0.6 ～ 0.8		0.2				
- 1		0.8 ～ 1						7
- 1.5		1 ～ 1.5		0.5				7.2
- 2		1.5 ～ 2						7.3
- 2.5		2 ～ 2.5						7.4
- 3		2.5 ～ 3						7.5
- 3.175		2.7 ～ 3.175						7.6
D 7- 1.5		1 ～ 1.5	DTA 7 DTB 7 DTE 7	0.5	17	50	36	7
- 2		1.5 ～ 2						10
- 2.5		2 ～ 2.5						12
- 3		2.5 ～ 3						
- 4		3 ～ 4		1				14
- 5		4 ～ 5						16
- 6		5 ～ 6						
- 7		6 ～ 7						
D12- 4		2.5 ～ 4	DTA12 DTB12 DTE12	1.5	26	70	50	16
- 6		4 ～ 6		2				20
- 8		6 ～ 8						22
-10		8 ～ 10						
-12		10 ～ 12						
-13		11 ～ 13						

Spanner · Wrench

CODE	Holder type	Fig.	B	R	L	Tightening torque (N·m)
F- 22	DTA 3	1	-	22	110	2～ 3
DW-2.5-110	DTB 3	2	2.5	-	103	
F- 38	DTA 7	3	-	19	148.5	20～40
- 45	DTA12			22.5	225	70
TW-4	E32 - DTB 7	4	4	-	77	14
-5	DTB 7		5		153	
-6	DTB12		6		173	34
W-135DR	DTE 7	5	5		110	14
	DTE12					18
	E40 - DTB12					
	E50 - DTB12					
	F63 - DTB 7					14
	F63 - DTB12					18

■Std. Access.
●Collet driver (F-38, F-45, TW-5, TW-6, W135-DR)

Fig. 1 Fig. 2 Fig. 3 Fig. 4 Fig. 5



Adjustable torque wrench

The nut-tightening torque can be adjusted more properly.



Spanner for torque wrench	Adjustable torque wrench	Holder type
F-38AW	AW-1	DTA 7
-45AW		DTA12

Attaching a cutting tool (DTB, DTE)

If a retention knob with a hole is used, direct tightening of cutting tools is possible.


Reguired hole dia of retention knob
DTB 3 : ϕ4～
DTB 7, DTE : ϕ6～
DTB12 : ϕ7～



Collet driver

The DETa-1 collet can be attached/detached with ease.


CODE	Q'ty
DR-1	2pcs.



Cleaning tool felt type

Apply this tool to clean the hard-to-clean inside portion of DTA3 and DTB3 holders.
The initial accuracy of tool holders can be made to last a long time by keeping the internal bore clean.

CODE	Q'ty
PCT01-10	10pcs.
-25	25pcs.



COLLET HOLDER

Taper collet chuck

The optimum holder choices for a variety of applications!!






Coolant-through



Coolant-Through Cutter | "SUKIMA" Coolant Around Tool | Coolant-Through Collet

Precision spring collet

The increased number of slits ensures the uniform tightening and high accuracy of the collet.




Using a high-precision collet will increase the life of your tools. P. 117

Highest guaranteed accuracies throughout entire chucking range

(100% inspection)

Collet	Run-out accuracy(μm)
Precision Collet	5
Standard Collet	10


※Accuracy of collet alone



D	L
~10	4×D
10 ~20	40
20.5~42	60

Ideal taper angle

Since the collet angle is smaller than that of typical collets, the collapsibility is also small. However, because the collet can be inserted deeper into the main body, the gripping area increases, it provides stable run-out accuracy and high gripping force and rigidity for end milling. This collet as a taper angle of 6°, the ideal angle for run-out accuracy, gripping force and rigidity.




Thick and highly rigid body

- Thick body.
- The nut part is compact and has less interference.
- Short holder length.




Nut for high accuracy


- Because steel ball bearings are built into the nut, the collet does not get twisted when tightened.
- The threaded area and the ball bearing grooves for steel bearings are finished using the same process after heat treatment, thus providing high accuracy with no distortion.
- Stable tightening force and smoothly rotation achieve high accuracy.



Five main body types based on cutting tool size




A variety of holder lengths 45L~315L



Pre-balanced by previously designing (CTHtype)

The collet holder (CTH type) is pre-balanced by previously designing the holder to be as axisymmetrical as possible. When used with the precision collet, it enables stable machining during high-speed machining.



Comparison in imbalance value

Holder code	Spring collet used	Cutter used		Imbalance value (g·mm)
		Diameter	Overhang	
BT30-CTH10-75	Precision collet C10-10-P	ϕ10	40	3.3
-CTA10-75	Standard collet C10-10			13.1

Longer cutter life using through-spindle capability
P. 117

Coolant-through system

The spindle-through feature can be used whether the cutting tool has oil holes or not. P. 39

Pressure 7 Mpa

Coolant-Through Cutter



"SUKIMA" Coolant Around Tool



Coolant-Through Collet



COLLET HOLDER for high-speed (CTH)



➔P. 118

BT40-CTH20-90



A63-CTH20-90

Fig. 1




Fig. 2




Fig. 3




Fig. 4





Fig. 5



CODE	Fig.	φD	L	φC	L1	Kg	N
BT30-CTH10- 45	1	2.4～10	45	36	23	0.5	2.6
- 75			75		53	0.6	2.7
-CTH20- 60		5.8～20	60	50	38		4.3
- 90			90		68	0.9	4.7
BT40-CTH10- 60	1	2.4～10	60	36	33	1.1	3.8
- 90			90		63	1.3	4.0
-120			120		93	1.4	4.4
-150			150		123	1.6	4.6
-CTH20- 60		5.8～20	60	50	33	1.2	6.4
- 90			90		63	1.4	7.0
-120			120		93	1.7	7.3
-150			150		123	2.0	7.6
-CTH25- 75		5.8～25	75	62	48	1.5	8.9
-105			105		78	2.0	9.8
BT50-CTH10-105	1	2.4～10	105	36	67	3.8	5.3
-135			135		97	4.0	5.7
-165			165		127	4.1	6.1
-CTH20-105		5.8～20	105	50	67	4.2	8.3
-135			135		97	4.6	9.0
-165			165		127	4.9	9.4
-CTH25- 75		5.8～25	75	62	37	3.8	10.3
-105			105		67	4.4	11.0
-CTH32- 90		24.8～32	90	74	52	4.1	14.4
A40 -CTH10- 55	3	2.4～10	55	32	35	0.4	3.6
- 75			75		55	0.5	3.9
- 90			90		70	0.6	4.0
-CTH20- 75		5.8～20	75	50	55	0.7	7.3
- 90			90		70	0.8	7.0
-CTH25- 95		5.8～25	95	55	75	0.9	10.7
A50 -CTH10- 55	3	2.4～10	55	36	29	0.6	6.6
- 75			75		49	0.7	6.9
A50M-CTH20- 80※		5.8～20	80	50	54	0.9	10.2
-105※			105		79	1.2	11.1
-CTH25-105※		5.8～25		62		1.3	14.7

CODE	Fig.	φD	L	φC	L1	Kg	N
A63 -CTH10- 75	3	2.4～10	75	36	49	0.9	10.2
- 90			90		64	1.0	10.4
-120			120		94	1.2	10.7
-150			150		124	1.4	11.0
-CTH20- 90		5.8～20	90	50	64	1.2	14.1
-120			120		94	1.5	14.0
-150			150		124	1.9	14.9
-CTH25-105		5.8～25	105	62	79	1.6	17.1
A100-CTH10-135	3	2.4～10	135	36	106	2.7	25.1
-165			165		136	2.9	25.4
-225	4		225		175	3.4	26.0
-CTH20-135	3	5.8～20	135	50	106	3.2	28.5
-165			165		136	3.6	29.5
-225			225		196	4.3	31.1
-CTH25-135		5.8～25	135	62	106	3.7	31.4
-165			165		136	4.3	32.7
-195			195		166	4.8	34.1
E32 -CTH10- 55	5	2.4～10	55	32	35	0.2	1.2
-CTS10- 50※	2		50	26	30		0.9
E40 -CTH10- 55	5	2.4～10	55	32	34	0.4	1.4
E50 -CTH10- 60	5	2.4～10	60	36	34	0.7	2.1
- 90			90		64	0.9	2.3
-CTH20- 75		5.8～20	75	50	49		3.8
F63 -CTH10- 60	5	2.4～10	60	36	34	0.9	2.2
- 90			90		64	1.1	2.4
-CTH20- 75		5.8～20	75	50	49		3.9
DN40AD-CTH20- 75	1	5.8～20	75	50	56	1.1	5.4
-135			135		116	1.7	5.9
DIN -CTH25- 75※		5.8～25	75	62	56	1.4	7.2
DN50AD-CTH20-105	1	5.8～20	105	50	70	3.6	9.1
-165			165		130	4.4	9.9
DIN -CTH25-105		5.8～25	105	62	70	3.8	10.9

■**Option**
- Spring collet(Precison collet)→P.38 ●Spanner→P.38 ●Adjust screw→P.37
- Retention knob(BT)→P.64 ●Adjustable torque wrench→P.38
- Coolant screw→P.39 ●Sukima nut→P.39 ●Collet remover→P.38

■**Std. Access.**
- Nut(NUA-CTH)→P.37 ●Coolant duct(Fixed)(HSK-A)→P.104

■**Note**
- Swing type coolant ducts are available upon request (HSK-A). For details, please contact us.
- Applicable for coolant-through methods →P.39
- Be sure to use precision-type spring collet.

■**Caution**
- ※The undercut area of the A50M and DN40AD-CTH25 are different from the standards. Please be careful to check for interference with the ATC arm.
- ※CTS10 = Collapsibility cannot be used. The collet can only chuck a tool of the reference diameter.
- HSK-E and F shank don't come with a coolant duct and cannot be attached.
- For precautions and maintenance, refer to page 116.

COLLET HOLDER(CTA)



BT50-CTA20-135

Fig. 1





Fig. 2





ST32T-CTA20-90

Fig. 3





Fig. 4



CODE	Fig.	ϕD	L	ϕC	L1	L2	ϕC1	Kg
BT30-CTA10- 45	1	2.4～10	45	36	23	—	—	0.5
- 75			75		53			0.7
-105			105		83			0.9
-CTA20- 60		5.8～20	60	50	38			0.6
- 90			90		68			0.9
BT40-CTA10- 60	1	2.4～10	60	36	33	—	—	1.1
- 90			90		63			1.3
-120			120		93			1.5
-150			150		123			1.7
-180			180		153			1.9
-210	2		210		155	28	44	2.1
-CTA20- 60	1	5.8～20	60	50	33	—	—	1.1
- 90			90		63			1.4
-120			120		93			1.7
-150			150		123			2.1
-180			180		153			2.5
-210			210		183			2.9
-CTA25- 75		5.8～25	75	62	48			1.2
-105			105		78			1.6
-135			135		108			2.0
-CTA32-105		24.8～32	105	74	78			1.8
BT50-CTA10-105	1	2.4～10	105	36	67	—	—	3.8
-135			135		97			3.9
-165			165		127			4.0
-195			195		157			4.2
-255	2		255		155	62	55	4.9
-315			315			122		5.8
-CTA20-105	1	5.8～20	105	50	67	—	—	4.0
-135			135		97			4.4
-165			165		127			4.8
-195			195		157			5.2
-255	2		255		180	37	65	6.3
-315			315			97		7.7
-CTA25- 75	1	5.8～25	75	62	37	—	—	3.6
-105			105		67			4.2
-135			135		97			4.8
-165			165		127			5.4
-195			195		157			6.0
-255			255		217			7.2
-315	2		315		225	52	70	8.7
-CTA32- 90	1	24.8～32	90	74	52	—	—	4.0
-120			120		82			4.7
-150			150		112			5.4
-180			180		142			6.1
-CTA40- 90		31.8～42	90	90	52			4.0
-120			120		82			5.0

CODE	Fig.	φD	L	φC	L1	φD1	G	Kg (lbs)
DN40AD-CTA20- 75	1	5.8～20	75	50	56	—	—	1.1
-135			135		116			1.9
DIN -CTA25- 75		5.8～25	75	62	56			1.7
DN50AD-CTA20-105	2	5.8～20	105	50	70	—	—	2.3
-165			165		130			3.0
DIN -CTA25-105		5.8～25	105	62	70			2.9
CT40 -CTA20- 75	1	.23～.79	2.95	1.97	2.20	—	—	2.65
-135			5.31		4.57			3.75
CAT. -CTA25- 75		.23～.98	2.95	2.44	2.20			3.09
CT50 -CTA20-105	1	.23～.79	4.13	1.97	2.68			7.94
-165			6.50		5.12			9.70
CAT. -CTA25-105		.23～.98	4.13	2.44	2.68			8.60
ST20T-CTA10	3	2.4～10	35	36	110	20	—	—
ST25T-CTA10	3	2.4～10	35	36	110	25	—	—
-CTA20		5.8～20	60	50				
ST32T-CTA10- 30	3	2.4～10	30	36	100	32	—	—
- 60			60					
- 90			90					
-120			120					
-CTA20- 60		5.8～20	60	50				
- 90			90					
-120			120					
ST42T-CTA25- 90	3	5.8～25	90	62	110	42	—	—
-120			120					
S 32 -CTA10	4	2.4～10	30	36	70	32	—	—
-CTA20		5.8～20	60	50				
S 42 -CTA10	4	2.4～10	30	36	80	42	—	—
-CTA20		5.8～20	35	50				
-CTA25		5.8～25	80	62				

■**Option**
- Spring collet→P.38 ●Spanner→P.38 ●Retention knob(BT)→P.64
- Adjustable torque wrench→P.38

■**Std. Access.**
- Nut(NUA-CTA)

■**Note**
- Applicable for coolant-through methods. Please contact us for more information.

■**Caution**
- The undercut area of the DN40AD-CTA25 and CT40-CTA25 are different from the standard. Please be careful to check for interference with the ATC arm.
- For precautions and maintenance, refer to page 116.

Nut



Fig. 1




Fig. 2





Fig. 3



CODE	Fig.	φC	H	Holder type
NUA-CTA10	1	36	18	CTA10
-CTA20		50	25	CTA20
-CTA25		62	28.5	CTA25
-CTA32		74	32	CTA32
-CTA40		90	36	CTA40
-CTH10	2	36	18	CTH10
-CTH20		50	25	CTH20
-CTH25		62	28.5	CTH25
-CTH25-55		55		CTH25(A40)
-CTH32		74	32	CTH32
-CTH10-32		32	18	CTH10(A40, E32, E40)
-CTS10	3	26	21	CTS10

Adjust screw

Fig. 1






Fig. 2




The overhang of the cutting tool can be adjusted.




CODE	Fig.	L	φD	L1	J	K	G	Holder type
AJC-M14	1	22	10	8	1.5	3	M14×1.5	CTA10 ST25T-CTA20
-M24		27	20	13	5	4	M24×1.5	CTA20 (※1) BT40-CTA25- 75 BT40-CTA32-105
-M28			25				M28×1.5	CTA25 (※2)
-M18		24	15	8			M18×1.5	BT30-CTA20 , ST32T-CTA20
-M18L	2	43	23					BT50-CTA32 , CTA40

※1:Except BT30, SE30M, ST25T and ST32T
※2:Except BT40-CTA25-75

SPRING COLLET





CODE		ϕD	Holder type	Collapsibility	L	ϕD1	H
Standard Collet	Precision Collet						
C10-D	Add "-P" after the standard type item code. 〈 Example 〉 C10 - 6 - P	2.6 2.8 **3** 3.2 3.4 3.6 3.8 **4** 4.2 4.4 4.6 4.8 5 5.2 5.4 5.6 5.8 **6** 6.2 6.4 6.6 6.8 7 7.2 7.4 7.6 7.8 **8** 8.2 8.4 8.6 8.8 9 9.2 9.4 9.6 9.8 **10**	CTH10 CTA10 CTS10 ※	0.2	26	17.2	2.6 ～ 5.8 → 18 6 ～10 → 20
C20-D		**6** 6.2 6.4 6.6 6.8 7 7.2 7.4 7.6 7.8 **8** 8.2 8.4 8.6 8.8 9 9.2 9.4 9.6 9.8	CTH20 CTA20	0.2	50	29.5	6 ～ 9.8 → 32 10 ～15.8 → 35 16 ～20 → 40
		10 10.2 10.4 10.6 10.8 11 11.2 11.4 11.6 11.8 **12** 12.2 12.4 12.6 12.8 13 13.2 13.4 13.6 13.8 14 14.2 14.4 14.6 14.8 15 15.2 15.4 15.6 15.8					
		16 16.2 16.4 16.6 16.8 17 17.2 17.4 17.6 17.8 18 18.2 18.4 18.6 18.8 19 19.2 19.4 19.6 19.8 **20**					
C25-D		**6 8**	CTH25 CTA25	0.2	68	36.5	6 ～ 8 → 38
		10 10.5 11 11.5 **12** 12.5 13 13.5 14 14.5 15					10 ～15 → 48
		15.5 **16** 16.5 17 17.5 18 18.5 19 19.5 **20**					15.5～20 → 54
		20.5 21 21.5 22 22.5 23 23.5 24 24.5 **25**					20.5～25 → 57
C32-D		25 28	CTH32 CTA32	0.2	80	46	25 ～28 → 66
		30 32					30 ～32 → 68
C40-D		32 40	CTA40	0.2	80	56	32 ～40 → 65
		42					42 → 70

Ex. C10 - 6 - P (ϕD)

CODE		ϕD	Holder type	Collapsibility	L	ϕD1	H
Standard Collet							
C20-D		1/4 5/16 3/8	CTA20	.008	1.97	1.16	1.14
		7/16 1/2					1.30
		5/8 3/4					1.57
C25-D		1/4 5/16 3/8	CTA25	.008	2.67	1.44	1.38
		7/16 1/2					1.81
		5/8 3/4					2.12
		1IN					2.24

■**Option**
- Collet remover


■**Note**
- Please contact us if you need a size that is not mentioned above, and we will manufacture it for you (standard accuracy collets only).

■**Caution**
- ※CTS10 = Collapsibility cannot be used. The collet can only chuck a tool of the reference diameter.

Highest guaranteed accuracies throughout entire chucking range(100% inspection)

Collet	Run-out accuracy (μm)
Precision Collet	5
Standard Collet	10

※Accuracy of collet alone



D	L
～10	4×D
10 ～20	40
20.5～42	60

Spanner · Wrench

Fig. 1



Fig. 2



CODE	Fig.	Holder type	R	L	Tightening torque(N・m)
FC-32	1	CTH10 (A40, E32, E40)	16	120	40～60
-36		CTA10, CTH10	18	208	
-50		CTA20, CTH20	25	281	120
-55		CTH25(A40)	27.5	284	150
-62		CTA25, CTH25	31	312	
-74		CTA32, CTH32	37	364	
-90		CTA40	45		
RC-26	2	CTS10	-	240	-

Adjustable torque wrench

The nut-tightening torque can be adjusted more properly.



Spanner for torque wrench	Adjustable torque wrench	Holder type
FC-36AW	AW-1	CTA10, CTH10
-50AW	-2	CTA20, CTH20

Spring collet standard set



C10-A set


CODE	Collet inner diameter	Q'ty	Holder type
C10-Aset	3, 4, 5, 6, 8, 10	6pcs. (1ea.)	CTA10
C20-Aset	6, 8, 10, 12, 16, 20		CTA20
C25-Aset	6, 8, 10, 12, 16, 20, 25	7pcs. (1ea.)	CTA25

■**Std. Access.**
- Collet remover (C10-A set)

Collet remover

The collet can be attached/detached with ease.

CODE	Holder type
C10-RM	C10
C20-RM	C20
CE-CTS10	CTS10




COOLANT-THROUGH SYSTEM

CODE	Retention knob with hole	Coolant-through cutter Coolant screw	H	SUKIMA through SUKIMA nut
BT30 -CTH10- 45	Model no. of retention knob depends on the machine model.	CSA-M14	22～38	NUB-CTH10
- 75			22～68	
-CTH20- 60		※1	-	-CTH20
- 90				
BT40 -CTH10- 60		CSA-M14	22～54	NUB-CTH10
- 90			22～67	
-120				
-150				
-CTH20- 60		-M24S	44～54	-CTH20
		-M24L	36～46	
- 90		-M24S	44～79	
		-M24L	36～71	
-120		-M24S	44～83	
		-M24L	36～75	
-150		-M24S	44～89	
		-M24L	36～81	
-CTH25- 75		-M24S	61～73	-CTH25
		-M24L	53～65	
-105		-M28	61～80	
BT50 -CTH10-105		CSA-M14	22～49	NUB-CTH10
-135			22～67	
-165				
-CTH20-105		-M24S	44～81	-CTH20
		-M24L	36～73	
-135		-M24S	44～89	
		-M24L	36～81	
-165		-M24S	44～89	
		-M24L	36～81	
-CTH25- 75		-M28	61～79	-CTH25
-105			61～89	
-CTH32- 90		※1	-	-CTH32
DN40AD-CTH20- 75		CSA-M24S	44～ 69	NUB-CTH20
		-M24L	36～ 61	
-135		-M24S	44～ 89	
		-M24L	36～ 81	
-CTH25- 75		-M24S	61～ 73	-CTH25
		-M24L	53～ 65	
DN50AD-CTH20-105		CSA-M24S	44～ 89	NUB-CTH20
		-M24L	36～ 81	
-165		-M24S	44～ 89	-CTH20
		-M24L	36～ 81	
-CTH25-105		-M28	61～ 90	-CTH25


CODE	Coolant duct	Coolant screw	H	SUKIMA nut
A40 -CTH10- 55	CD 40-01	CSR- 14	21.7	NUB-CTH10
- 75		CSA-M14	22～ 24	
- 90			21～ 44	
-CTH20- 75	-03	Unnecessary	53	-CTH20
- 90	-01	CSA-M24S	41.9	
-CTH25- 95	-04	Unnecessary	72	-CTH25
A50 -CTH10- 55	CD 50-01	Unnecessary	-	NUB-CTH10
- 75		CSA-M14	21～ 22	
A50M-CTH20- 80		Unnecessary	-	-CTH20
-105		CSA-M24S	42～ 47	
-CTH25-105	-03	Unnecessary	80	-CTH25
	-04※2		60	
A63 -CTH10- 75	CD 63-02	CP - 14M	21～ 28	NUB-CTH10
- 90	-01	CSA-M14	22～ 31	
-120			22～ 52	
-150				
-CTH20- 90	-03	Unnecessary	65	-CTH20
	-04※2		44	
-120	-01	CSA-M24S	44～ 54	
		-M24L	36～ 46	
-150		-M24S	44～ 77	
		-M24L	36～ 69	
-CTH25-105	-03	Unnecessary	80	-CTH25
	-04※2		59	
A100 -CTH10-135	CD100-01	CSA-M14	22～ 67	NUB-CTH10
-165				
-225				
-CTH20-135		-M24S	44～ 65	-CTH20
		-M24L	36～ 57	
-165		-M24S	44～ 89	
		-M24L	36～ 81	
-225		-M24S	44～ 89	
		-M24L	36～ 81	
-CTH25-135	-02	※1	-	-CTH25
-165	-01	CSA-M28	61～ 75	
-195			61～105	

■Note
- For information on the asterisked (※1) coolant screw for the coolant-through cutter capability, please contact MST.
- A coolant duct is built into every tooling holder. However, the coolant ducts marked with ※2 are optional.
- Applicable for CTA type too. Please contact us for more information.




*SUKIMA through = Coolant Around Tool

Coolant screw



CODE	ϕD	ϕd	L	G	W
CSR-14	3.2	4～10	14	-	-
CP -14M	3	7～10	53	M14×1.5	3
CSA-M14	2.4	4～10	26		2
-M24S	7	10～20	30	M24×1.5	6
-M24L	3.4	6～12	38		3
-M28	6	10～25	40	M28×1.5	5

SUKIMA nut



CODE	ϕC	L	ϕd	ϕd1	S
NUB-CTH10- 3.6	36	23	3	3.6	3.1
- 4.5			4	4.5	3.3
- 5.5			5	5.5	3.7
- 6.4			6	6.4	3.9
- 8.4			8	8.4	4.6
-10.3			10	10.3	4.8
-CTH20- 6.4	50	30	6	6.4	3.9
- 8.4			8	8.4	4.6
-10.3			10	10.3	4.8
-12.3			12	12.3	
-16.2			16	16.2	5.1
-20.2			20	20.2	5.7
-CTH25-20.2	62	34.5			
-25.2			25	25.2	5.9
-CTH32-25.2	74	38			
-32.1			32	32.1	6.0

■Caution
- Only the reference cutter size can be used.

Hi-ART MILLING CHUCK

Needle-roller type chuck


The Hi-ART milling chuck achieves the accuracy, rigidity and torque required of a milling chuck.
Ideal for use as the end-milling base holder!!



Shrinker

Thanks to the shrinker, the cutter shank is chucked evenly from the bottom to the top of the gripping range, ensuring high rigidity and gripping force.

coolant-through




Nozzle-through　Coolant-Through Cutter




The shortest holder length is 85mm (BT40).

The shorter holder length means increased rigidity. The rigidity of the tool holder is inversely proportional to the cube of the length, meaning the deflection of this holder is about half that of a 105mm holder.



Memory line clearly confirms tightness of the nut.


You can check the recommended degree of tightening at a glance.
Also, it only takes about one and half turns for tightening operation.



Keeps chips and coolant out completely


Longer life

Dust-proof cover keeps chips and coolant out completely.




Applicable for coolant-through version

Nozzle-through



Coolant-Through Cutter



Longer cutter life using through-spindle capability P.117

Applicable as a base holder for various applications



Hi-ART MILLING CHUCK (ART)



BT50-ART32-105



A100-ART32-135

Fig. 1




Fig. 2




Fig. 3




Fig. 4





Fig. 5



CODE	Fig.	ϕD	L	ϕC	ϕC1	ϕC2	L1	Cutter insertion length	Kg	MAX. min-1
BT40-ART32- 85	1	32	85	72	—	—	37	66～ 88	1.9	6,000
- 95			95				47		2.1	
-105			105				57		2.3	
-135			135				87		3.0	
BT50-ART32-105	2	32	105	82	—	80	—	66～ 98	5.1	5,000
-135	3		135		86		69		6.4	
-165			165				99		7.7	
-180			180				114		8.4	
-ART42-105	2	42	105	97	—	95	—	76～108	5.4	3,000
-135	3		135		99		67		7.1	
A50M-ART32-100	4	32	100	72	—	—	44	66～ 71	1.7	6,000
A63 -ART32-100	4	32	100	72	—	—	44	66～ 71	2.0	6,000
A100-ART32-135	5	32	135	82	85	80	69	66～ 98	5.3	5,000
-ART42-135		42		97	99	95	67	76～ 98	6.1	3,000

■Option

- Straight collet→P.42 ●Nozzle→P.42 ●Spanner with ejection hook→P.42
- Adjust screw→P.42 ●Retention knob(BT)→P.64

■Std. Access.

- Coolant duct(Fixed)(HSK-A)→P.104

■Note


- To utilize the coolant-through nozzle capability, the retention knob with hole and nozzle are required.
- Swing type coolant ducts are available upon request(HSK-A). For details, please contact us.

■Caution

- For BT40 type, the outer diameter of the nut is larger than that of the V-flange. Therefore, pay close attention to possible interference with the ATC arm.
- When using the straight arbor in BT40, use the S type (ex.S32-CTA10).
- For A50M and A63, the coolant-through system is not available for straight collets.
- Cutter-through coolant is not available for straight collets.
- For precautions and maintenance, refer to page 116.

Increased rigidity with the Face Lock system (BT)

For face milling applications, combining a holder and a face mill arbor, with backup screw (ST32B, ST42B-FMA), will achieve strong gripping (Face Lock) and improve the rigidity during transverse feed milling.



Face Lock


Straight collet

Standard type



F type






CODE		φD	L	φD1	H	Holder type
Standard type	F type					
S32- 6	S32- 6F	6	75	32	30～68	ART32
- 8	- 8F	8				
-10	-10F	10			40～68	
-12	-12F	12				
-16	-16F	16			50～68	
-20	-20F	20				
-25	-25F	25			55～68	
S42- 6	S42- 6F	6	80	42	30～73	ART42
- 8	- 8F	8				
-10	-10F	10			45～73	
-12	-12F	12				
-16	-16F	16			50～73	
-20	-20F	20				
-25	-25F	25			55～73	
-32	-32F	32			60～73	

■**Caution**
- Remove the adjust stopper when using a straight collet with A50M/ A63.
- When a straight collet with nozzles is used, use the F type.

■**Std. Access.**
- Adjust stopper

Spanner with ejection hook

This spanner can be used to both tighten a nut and remove a straight collet.






CODE	R	L	Holder type	Clamping torque(N·m)
FM-72	36	204	ART32 (BT40, A50M, A63)	60
-82	41	234	ART32 (BT50, A100)	70
-97	48.5	239	ART42 (BT50, A100)	

Nozzle






CODE	L	G	W	φD	Holder type	Q'ty
NOZ-M4-12	6.3	M4	4.5	1.2	BT40, A50M, A63	12pcs.
-60						60pcs.
-M6-12	8.5	M6	7	1.8	BT50, A100	12pcs.
-60						60pcs.


■**Std. Access.**
- Wrench for attachment

Adjust screw

The overhang of the cutting tool can be adjusted.








CODE	L	Shank type	Q'ty
AJN-M18L	38	BT40	5pcs.
-M18	63	BT50	

Cutting data



The ace for heavy-duty cutting!!
The set screw holder that doesn't need a whistle notch.

- Accuracy → Less than 20μm / 100L
- Gripping force → 4000N · m (ϕ 42)



SLZ





Whistle notch
end mill


coolant-through



Nozzle-through


Adjustable projection of cutting tool

Our original tightening pad system allows a round shank, as well as a whistle notch shank end mill, to be used. The projection of the cutting tool, which is critical for heavy-duty cutting, can be made as short as possible.



Applicable for coolant-through version (A100)


Nozzle-through






Applicable to high-speed cutting

Pre-balanced design



High accuracy thanks to its eccentric bore design



SUMMIT (SLZ)



BT50-SLZ32-105



A100-SLZ32-135

Fig. 1




Fig. 2





Fig. 3



CODE	Fig.	ϕD	L	L1	ϕC	ϕC1	H	H1	G	Kg
BT50-SLZ25- 90	1	25	90	—	66	—	45	70	4-M12	4.6
-120			120	45		75				5.6
-150			150							6.5
-SLZ32-105		32	105	—	88	—	65	100	6-M16	5.9
-135			135	62		95				7.5
-165			165							9.1
-SLZ42-105		42	105	—	98	—	70	110		6.1
-135			135							7.8
-165			165							9.5
A100-SLZ25-135	2	25	135	66	66	75	45	70	4-M12	4.9
-SLZ32-135	3	32		88	88	—	65	100	6-M16	6.1
-SLZ42-135		42		98	98		70			6.6


■**Option**
- Wrench ●Adjust screw (BT50) ●Nozzle (HSK-A100) ●Retention knob (BT50)→P.64

■**Std. Access.**
- Coolant duct (Fixed) (HSK-A100)→P.104

■**Note**
- Swing type coolant ducts are available upon request (HSK-A). For details, please contact us.


■**Caution**
- If the dedicated wrench is not used, use a wrench with a minimum handle length of 30 cm for the M16 or 20 cm for the M12.
- For precautions and maintenance, refer to page 117.

Wrench



CODE	Holder type	B	L	Tightening torque(N·m)
W-206	SLZ25	6	200	40
-308	SLZ32 SLZ42	8	300	100

Nozzle



CODE	Q'ty
NOZ-M6-12	12pcs.
-60	60pcs.

■**Std. Access.**
- Wrench for attachment




Adjust screw


The overhang of the cutting tool can be adjusted.



CODE	Shank type	Q'ty
AJC-M18L	BT50	5pcs.



The overhang of the cutting tool can be adjusted.




Cutting data

A2017

ϕ38 end mill 4 flutes

n	5000 min-1
Vf	5000 mm/min
Vc	597 m/min
fz	0.25 mm/t




BT50-SLZ32-105

S50C

ϕ40 roughing end mill 6 flutes

n	280 min-1
Vf	168 mm/min
Vc	35 m/min
fz	0.1 mm/t




BT50-SLZ32-105

S50C

ϕ45 roughing end mill 6 flutes

n	190 min-1
Vf	114 mm/min
Vc	25 m/min
fz	0.1 mm/t



BT50-SLZ42-105


The solution for high-efficient machining of deep cavity application.

1 Roughing

With a solid carbide core PAT.

FMH RIGID type →P. 46

Ideal for heavy duty roughing application at shallow and deep machining using a face milling arbor with a large size solid carbide core.







2 Semi-finishing

For screw-in end-mills PAT.

RED SCREW ARBOR →P. 48

Less vibration at a corner and pocket machining thanks to a solid design using a carbide shaft.






3 Finishing

SHRINK-FIT HOLDER PAT.

SLIMLINE MONO CURVE

Superior Accessibility.
Slim tip design of Curve minimizes cutter projection.





If you would like more detailed information, please contact MST and ask for a SLIMLINE catalog.

FMH RIGID type

PAT.
with a solid carbide core

Achieves higher efficiency during long gauge length machining. Achieves stable machining during long, continuous operation.

FMH-H


▷ Machining efficiency **2 times**
(Compared to conventional holders)



coolant-through


Large dia. Carbide core

The large-diameter carbide core is integrated into the thick body by shrink-fitting. Achieves less deflection and higher efficiency during long-gauge machining. Vibration-free machining leads to longer insert life and achieves stable machining during long and continuous operation.



Even greater efficiency!

Effective length of our line up is from 110mm to 360mm and cutter dia of our line up is from ϕ40 to ϕ100.
Shorter and longer gauge length models added to our current line up. Ideal for deep cavity mold applications. Makes more efficient roughing possible.



FMH standard

Available for FMH standard cutting tools that supplies coolant to the cutting edge properly.

Works with these manufacturers' cutting tools


OSG KYOCERA Sumitomo Electric Hardmetal
DIJET INDUSTRIAL Tungaloy MITSUBISHI MATERIALS
MOLDINO

Comparison test

Cutting depth ap (mm)	0.5	1.0	1.5	2.0
FMH RIGID type BT50-FMH22-60-315H	○	○	○	◎
Conventional BT50-FMH22-60-300	○	× Chattering		

Double the Machining efficiency

- Application Shouldering
- Material S50C (Mild steel)
- Cutting speed 220 m/min (S1,112 min^{-1})
- Feed rate 1,112 mm/min



FMH RIGID type with a solid carbide core (FMH-H)





Fig. 1




Fig. 2






Fig. 3





CODE	Fig.	L	M	Kg	Moment kgf·m
BT50-FMH16 -37-125H	1	125	60	5.2	—
-175H		175	110	5.8	
-225H		225	160	6.5	
-275H		275	210	7.1	
-325H		325	260	7.8	
BT50-FMH22 -47-165H	1	165	110	5.7	0.1
-215H		215	160	6.5	0.2
-265H		265	210	7.3	0.3
-315H		315	260	8.2	0.6
-365H		365	310	9.0	0.8
BT50-FMH22 -60-165H	1	165	110	6.9	0.2
-215H		215	160	8.1	0.3
-265H		265	210	9.3	0.6
-315H		315	260	10.7	1.0
-365H		365	310	11.9	1.3
-415H		415	360	13.1	1.7
BT50-FMH31.75-76-215H	1	215	160	10.6	0.6
-265H		265	210	12.7	1.0
-315H		315	260	15.3	1.5
-365H		365	310	17.6	2.3
A100-FMH16 -37-125H	1	125	60	3.9	—
-175H		175	110	4.5	
-225H		225	160	5.2	
-275H		275	210	5.8	
-325H		325	260	6.4	
A100-FMH22 -47-165H	2	165	110	4.2	0.1
-215H		215	160	5.1	0.3
-265H		265	210	5.9	
-315H		315	260	6.8	0.6
-365H		365	310	7.6	0.8
A100-FMH22 -60-165H	2	165	110	5.9	0.2
-215H		215	160	7.2	0.5
-265H		265	210	8.4	0.7
-315H		315	260	9.8	1.1
-365H		365	310	11.1	1.4
-415H		415	360	12.4	1.8
A100-FMH31.75-76-215H	2	215	160	9.7	0.7
-265H		265	210	11.8	1.2
-315H		315	260	14.0	1.7
-365H		365	310	16.3	2.4
A100-FMH31.75-96-250H	3	250	—	13.6	1.3
-300H		300		16.3	2.0
-350H		350		17.4	2.6

■Common dimensions

CODE	Cutter dia.	φD	H	φC	W	K	φd	G	Clamp bolt
FMH16 -37	40	16	17	37	8	5	2	M 8	M 8※
FMH22 -47	50/52	22	18	47	10	5	3	M10	M10※
FMH22 -60	63/66	22	18	60	10	5	3	M10	M10※
FMH31.75-76	80	31.75	30	76	12.7	7	4	M16	MBF-M16
-96	100	31.75	30	96	12.7	7	4	M16	MBF-M16

■Option
- Retention knob (BT50) →P.64

■Std. Access.
- Coolant duct(Fixed) (HSK-A100) →P.104
- Clamp bolt (unless marked with in the list) • Stopper key

■Note
- Swing type coolant ducts are available upon request (HSK-A). For details, please contact us.
- The clamp bolt marked with ※ in the list is a hexagonal socket bolt. Use a market standard bolt.
- Contact us to find out what manufacturers' cutters can be used with this product.

■Caution
- The required clamp bolt design depends on the cutter manufacturer and the type of cutter.


Available for DIN/ CAT.

RED SCREW arbor

PAT.
The arbor for screw-in End Mill

Displaying the highest cutting performance of any screw-in end mill!!

- Highly rigid design makes the best use of carbide properties (high Young's modulus).
- Ideal for deep standing-wall machining.



coolant-through




RSG

Carbide integral type




Works with these manufacturers' tools






Many effective lengths for machining



Heavy cutting ⟷ Deep standing-wall machining


Machining example

RED screw arbor
BT50-RSG12-215-M100




Carbide integral type

Deflection amount **1μm**




A general holder+
A steel shank




Steel

Deflection amount **3μm**



○ Excellent
× Chattering


Cutting condition





2-flutes end-mill
Climb milling
Feed : 0.1mm/tooth
Material : S50C

RED SCREW arbor (RSG)

BT







Dimensions for the screw-in end mill mounting.


Available for DIN/ CAT.

■Option
- Retention knob→P.64

■Caution
- Some of the screw-in end mills cannot be attached to the RED screw arbor. Please check your screw-in end mills for conformance to the dimensions, or please contact MST.
- Because cutting resistance is greater than the tool holder connection force associated with the machine spindle, please reduce the recommended cutting conditions by 50% for the RED screw arbors marked with ※. Otherwise, the tool holder shank may experience fretting corrosion or fall out of the machine spindle.

S The rigidity value

A rigidity value represents the amount of deflection for the entire holder and tool when a bending load of 1 kgf (9.8 N) is applied to the tip of the tool. The smaller the numerical value is, the higher the rigidity and the more accurate the machining.



CODE	L	M	L1	Kg	S
BT40-RSG 8-105-M 25	105	25	80	1.4	0.6
-135-M 25	135		110	1.8	0.7
-165-M 25	165		140	2.1	0.8
-130-M 50	130	50	80	1.4	1.5
-160-M 50	160		110	1.8	1.7
-190-M 50	190		140	2.1	1.8
-155-M 75	155	75	80	1.5	3.1
-185-M 75	185		110	1.9	3.4
-215-M 75	215		140	2.2	3.5
-170-M 90	170	90	80	1.5	4.5
-200-M 90	200		110	1.9	4.8
-230-M 90	230		140	2.2	4.9
-185-M105	185	105	80	1.6	6.2
-215-M105	215		110	2.0	6.7
-245-M105	245		140	2.3	6.8
BT40-RSG10-125-M 25	125	25	100	1.8	0.4
-155-M 25	155		130	2.2	0.5
-185-M 25	185		160	2.4	0.7
-150-M 50	150	50	100	1.9	0.8
-180-M 50	180		130	2.3	1.0
-210-M 50	210		160	2.5	1.2
-175-M 75	175	75	100	2.0	1.6
-205-M 75	205		130	2.4	1.8
-235-M 75	235		160	2.6	2.0
-200-M100	200	100	100	2.0	2.7
-230-M100	230		130	2.4	3.0
-260-M100	260		160	2.6	3.3
-220-M120	220	120	100	2.1	4.0
-250-M120	250		130	2.5	4.3
-280-M120	280		160	2.7	4.6
BT40-RSG12-125-M 25	125	25	100	2.0	0.3
-155-M 25	155		130	2.4	0.4
-185-M 25	185		160	2.7	0.5
-150-M 50	150	50	100	2.1	
-180-M 50	180		130	2.5	0.7
-210-M 50	210		160	2.8	0.9
-175-M 75	175	75	100	2.3	
-205-M 75	205		130	2.7	1.1
-235-M 75	235		160	3.0	1.3

CODE	L	M	L1	Kg	S
BT40-RSG12-200-M100	200	100	100	2.4	1.4
-230-M100	230		130	2.8	1.6
-260-M100	260		160	3.1	1.9
-225-M125	225	125	100	2.6	2.1
-255-M125	255		130	3.0	2.4
-285-M125	285		160	3.3	2.8
BT40-RSG16-125-M 25	125	25	100	2.6	0.2
-150-M 50	150	50		2.8	0.3
-175-M 75	175	75		3.0	0.5
-200-M100	200	100		3.2	0.8
-225-M125※	225	125		3.4	1.2
BT50-RSG 8-120-M 25	120	25	95	4.0	0.6
-150-M 25	150		125	4.3	0.7
-180-M 25	180		155	4.8	
-145-M 50	145	50	95	4.0	1.5
-175-M 50	175		125	4.3	1.7
-205-M 50	205		155	4.8	
-170-M 75	170	75	95	4.1	3.1
-200-M 75	200		125	4.4	3.4
-230-M 75	230		155	4.9	
-185-M 90	185	90	95	4.1	4.4
-215-M 90	215		125	4.4	4.8
-245-M 90	245		155	4.9	
-200-M105	200	105	95	4.2	6.2
-230-M105	230		125	4.5	6.6
-260-M105	260		155	5.0	
BT50-RSG10-140-M 25	140	25	115	4.3	0.4
-170-M 25	170		145	4.6	0.5
-200-M 25	200		175	5.6	
-165-M 50	165	50	115	4.4	0.8
-195-M 50	195		145	4.7	0.9
-225-M 50	225		175	5.7	1.0
-190-M 75	190	75	115	4.5	1.6
-220-M 75	220		145	4.8	1.7
-250-M 75	250		175	5.8	1.8
-215-M100	215	100	115	4.5	2.7
-245-M100	245		145	4.8	2.9
-275-M100	275		175	5.8	

■Common dimensions

CODE	Cutter dia.	G	ϕD	H	H1	ϕC	ϕC1	ϕC2
RSG 8	16	M 8	8.5	18	6.5	15	30	32
RSG10	20	M10	10.5	22	6.5	19	36	38
RSG12	25	M12	12.5	22	6	24	43	45
RSG16	32/40	M16	17	25	6	29	52	54
RSG16-37	40	M16	17	25	6	37	71	73



BT50-RSG16-37-265-M150

CODE	L	M	L1	Kg	S
BT50-RSG10-235-M120	235	120	115	4.6	3.9
-265-M120	265		145	4.9	4.2
-295-M120	295		175	5.9	
-255-M140	255	140	115	4.7	5.5
-285-M140	285		145	5.0	5.8
-315-M140	315		175	6.0	
BT50-RSG12-140-M 25	140	25	115	4.6	0.2
-170-M 25	170		145	5.0	0.3
-200-M 25	200		175	5.8	0.4
-165-M 50	165	50	115	4.7	0.5
-195-M 50	195		145	5.1	0.6
-225-M 50	225		175	5.9	
-190-M 75	190	75	115	4.9	0.8
-220-M 75	220		145	5.3	1.0
-250-M 75	250		175	6.1	
-215-M100	215	100	115	5.0	1.3
-245-M100	245		145	5.4	1.5
-275-M100	275		175	6.2	1.6
-240-M125	240	125	115	5.2	2.1
-270-M125	270		145	5.6	2.3
-300-M125	300		175	6.4	2.4
-265-M150	265	150	115	5.3	3.0
-295-M150	295		145	5.7	3.3
-325-M150	325		175	6.5	3.4
-290-M175	290	175	115	5.5	4.2
-320-M175	320		145	5.9	4.6
-350-M175	350		175	6.7	
BT50-RSG16-140-M 25	140	25	115	4.8	0.2
-170-M 25	170		145	5.4	
-200-M 25	200		175	6.6	
-165-M 50	165	50	115	5.0	0.3
-195-M 50	195		145	5.6	0.4
-225-M 50	225		175	6.8	
-190-M 75	190	75	115	5.3	0.5
-220-M 75	220		145	5.9	0.6
-250-M 75	250		175	7.0	
-215-M100	215	100	115	5.5	0.7
-245-M100	245		145	6.1	0.9
-275-M100	275		175	7.2	
-240-M125	240	125	115	5.7	1.1
-270-M125	270		145	6.3	1.3


CODE	L	M	L1	Kg	S
BT50-RSG16-300-M125	300	125	175	7.4	1.3
-265-M150	265	150	115	5.9	1.6
-295-M150	295		145	6.5	1.8
-325-M150	325		175	7.7	
-290-M175	290	175	115	6.1	2.2
-320-M175	320		145	6.7	2.4
-350-M175	350		175	7.9	2.5
-315-M200	315	200	115	6.3	3.0
-345-M200	345		145	6.9	3.2
-375-M200	375		175	8.1	3.3
-340-M225	340	225	115	6.5	3.9
-370-M225	370		145	7.1	4.1
-400-M225	400		175	8.3	4.2
BT50-RSG16- 37-190-M 75	190	75	115	6.8	0.2
-215-M100	215	100			0.3
NEW -240-M125	240	125		7.6	0.4
-265-M150	265	175			0.6
-290-M175	290	200		8.3	0.9
-315-M200	315	225			1.1
-340-M225	340	250		9.0	1.5
-365-M250	365	250			1.9
-390-M275	390	275		9.7	2.4
-415-M300	415	300			2.9


RED SCREW arbor (RSG)

HSK-A



A63-RSG10-175-M75





Dimensions for the screw-in end mill mounting.


■**Std. Access.**
- Coolant duct(Fixed type)→P.64

■**Note**
- Swing type coolant ducts are available upon request. For details, please contact us.

■**Caution**
- Some of the screw-in end mills cannot be attached to the RED screw arbor. Please check your screw-in end mills for conformance to the dimensions, or please contact MST.
- Because cutting resistance is greater than the tool holder connection force associated with the machine spindle, please reduce the recommended cutting conditions by 50% for the RED screw arbors marked with ※. Otherwise, the tool holder shank may experience fretting corrosion or fall out of the machine spindle.

S The rigidity value

A rigidity value represents the amount of deflection for the entire holder and tool when a bending load of 1 kgf (9.8 N) is applied to the tip of the tool. The smaller the numerical value is, the higher the rigidity and the more accurate the machining.



CODE	L	M	L1	Kg	S
A63-RSG 8-105-M 25	105	25	80	1.3	0.6
-135-M 25	135		110	1.4	0.7
-165-M 25	165		140	1.9	0.8
-130-M 50	130	50	80	1.3	1.5
-160-M 50	160		110	1.4	1.7
-190-M 50	190		140	1.9	
-155-M 75	155	75	80	1.4	3.1
-185-M 75	185		110	1.5	3.4
-215-M 75	215		140	2.0	
-170-M 90	170	90	80	1.4	4.4
-200-M 90	200		110	1.5	4.8
-230-M 90	230		140	2.0	4.9
-185-M105	185	105	80	1.5	6.2
-215-M105	215		110	1.6	6.6
-245-M105	245		140	2.1	6.7
A63-RSG10-125-M 25	125	25	100	1.6	0.4
-155-M 25	155		130	1.9	0.5
-185-M 25	185		160	2.3	0.6
-150-M 50	150	50	100	1.7	0.8
-180-M 50	180		130	2.0	1.0
-210-M 50	210		160	2.4	1.2
-175-M 75	175	75	100	1.8	1.6
-205-M 75	205		130	2.1	1.8
-235-M 75	235		160	2.5	2.0
-200-M100	200	100	100	1.8	2.7
-230-M100	230		130	2.1	2.9
-260-M100	260		160	2.5	3.2
-220-M120	220	120	100	1.9	4.0
-250-M120	250		130	2.2	4.2
-280-M120	280		160	2.6	4.5
-240-M140	240	140	100	2.0	5.6
-270-M140	270		130	2.3	5.9
-300-M140	300		160	2.7	6.2

CODE	L	M	L1	Kg	S
A63 -RSG12-125-M 25	125	25	100	1.9	0.3
-155-M 25	155		130	2.3	0.4
-185-M 25	185		160	2.7	0.5
-150-M 50	150	50	100	2.0	
-180-M 50	180		130	2.4	0.6
-210-M 50	210		160	2.8	0.8
-175-M 75	175	75	100	2.2	0.9
-205-M 75	205		130	2.6	1.0
-235-M 75	235		160	3.0	1.3
-200-M100	200	100	100	2.3	1.4
-230-M100	230		130	2.7	1.6
-260-M100	260		160	3.1	1.9
-225-M125	225	125	100	2.5	2.1
-255-M125	255		130	2.9	2.4
-285-M125	285		160	3.3	2.7
-250-M150	250	150	100	2.6	3.1
-280-M150	280		130	3.0	3.4
-310-M150	310		160	3.4	3.8
A63 -RSG16-140-M 25	140	25	115	2.6	0.2
-165-M 50	165	50		2.8	0.4
-190-M 75	190	75		3.0	0.6
-215-M100	215	100		3.2	0.9
-240-M125※	240	125		3.4	1.3
-265-M150※	265	150		3.7	1.9
-290-M175※	290	175		3.9	2.5
A100-RSG 8-120-M 25	120	25	95	2.6	0.6
-150-M 25	150		125	2.9	0.8
-180-M 25	180		155	3.4	
-145-M 50	145	50	95	2.6	1.5
-175-M 50	175		125	2.9	1.7
-205-M 50	205		155	3.4	
-170-M 75	170	75	95	2.7	3.1
-200-M 75	200		125	3.0	3.4

■Common dimensions

CODE	Cutter dia.	G	ϕD	H	H1	ϕC	ϕC1	ϕC2
RSG 8	16	M 8	8.5	18	6.5	15	30	32
RSG10	20	M10	10.5	22	6.5	19	36	38
RSG12	25	M12	12.5	22	6	24	43	45
RSG16	32/40	M16	17	25	6	29	52	54
RSG16-37	40	M16	17	25	6	37	71	73

CODE	L	M	L1	Kg	S
A100-RSG 8-230-M 75	230	75	155	3.5	3.4
-185-M 90	185	90	95	2.7	4.5
-215-M 90	215		125	3.0	4.9
-245-M 90	245		155	3.5	4.8
-200-M105	200	105	95	2.8	6.3
-230-M105	230		125	3.1	6.7
-260-M105	260		155	3.6	6.6
A100-RSG10-140-M 25	140	25	115	3.1	0.4
-170-M 25	170		145	3.5	0.5
-200-M 25	200		175	4.4	
-165-M 50	165	50	115	3.2	0.8
-195-M 50	195		145	3.6	1.0
-225-M 50	225		175	4.5	
-190-M 75	190	75	115	3.3	1.6
-220-M 75	220		145	3.7	1.8
-250-M 75	250		175	4.6	
-215-M100	215	100	115	3.3	2.7
-245-M100	245		145	3.7	2.9
-275-M100	275		175	4.6	
-235-M120	235	120	115	3.4	4.0
-265-M120	265		145	3.8	4.2
-295-M120	295		175	4.7	
-255-M140	255	140	115	3.5	5.6
-285-M140	285		145	3.9	5.8
-315-M140	315		175	4.8	
A100-RSG12-140-M 25	140	25	115	3.4	0.3
-170-M 25	170		145	3.7	0.4
-200-M 25	200		175	4.7	
-165-M 50	165	50	115	3.5	0.5
-195-M 50	195		145	3.8	0.6
-225-M 50	225		175	4.8	
-190-M 75	190	75	115	3.7	0.8
-220-M 75	220		145	4.0	1.0
-250-M 75	250		175	5.0	
-215-M100	215	100	115	3.8	1.4
-245-M100	245		145	4.1	1.6
-275-M100	275		175	5.1	
-240-M125	240	125	115	4.0	2.1
-270-M125	270		145	4.3	2.4
-300-M125	300		175	5.3	
-265-M150	265	150	115	4.1	3.0
-295-M150	295		145	4.4	3.4
-325-M150	325		175	5.4	
-290-M175	290	175	115	4.3	4.3
-320-M175	320		145	4.6	4.6
-350-M175	350		175	5.6	

CODE	L	M	L1	Kg	S
A100-RSG16-140-M 25	140	25	115	4.0	0.2
-170-M 25	170		145	4.5	
-200-M 25	200		175	5.7	
-165-M 50	165	50	115	4.2	0.3
-195-M 50	195		145	4.7	0.4
-225-M 50	225		175	5.9	
-190-M 75	190	75	115	4.5	0.5
-220-M 75	220		145	5.0	0.6
-250-M 75	250		175	6.1	
-215-M100	215	100	115	4.7	0.8
-245-M100	245		145	5.2	0.9
-275-M100	275		175	6.3	
-240-M125	240	125	115	4.9	1.1
-270-M125	270		145	5.4	1.3
-300-M125	300		175	6.5	
-265-M150	265	150	115	5.1	1.6
-295-M150	295		145	5.6	1.8
-325-M150	325		175	6.7	
-290-M175	290	175	115	5.3	2.2
-320-M175	320		145	5.8	2.4
-350-M175	350		175	7.0	2.5
-315-M200	315	200	115	5.5	3.0
-345-M200	345		145	6.0	3.2
-375-M200	375		175	7.2	3.3
-340-M225	340	225	115	5.7	3.9
-370-M225	370		145	6.3	4.2
-400-M225	400		175	7.4	
A100-RSG16- 37-190-M 75	190	75	115	6.3	0.2
-215-M100	215	100			0.3
NEW -240-M125	240	125		7.1	0.4
-265-M150	265	150			0.6
-290-M175	290	175		7.8	0.9
-315-M200	315	200			1.1
-340-M225	340	225		8.5	1.5
-365-M250	365	250			1.9
-390-M275	390	275		9.2	2.4
-415-M300	415	300			2.9

Cutter arbor with spindle-through coolant (FMH)

- Standard design has through-coolant holes that allow superior chip evacuation, cutting edge cooling and lubrication.
- Achieves amazing high-feed machining
- We also have a variety of ultra-long type arbors.



BT50-FMH31.75-76-300

Fig. 1






Fig. 2



Dimensions
for the cutter mounting
Depth of threaded portion




CODE	Fig.	Cutter dia.	L	φC1	kg
BT40-FMH16 -29- 45	1	32	45	29	1.1
-90			90		1.4
-120			120		1.5
-37- 45		40	45	37	1.2
-90			90		1.6
-120			120		1.9
BT40-FMH22 -47- 45	1	50/52	45	47	1.3
-90			90		1.9
-150			150		2.7
-200			200		3.3
-60- 45		63/66	45	60	1.4
-90			90		2.2
-150			150		3.2
-200			200		4.1
BT40-FMH22.225-47- 45	1	50/52	45	47	1.3
-90			90		1.9
-150			150		2.7
-200			200		3.3
-60- 45		63/66	45	60	1.4
-90			90		2.2
-150			150		3.2
-200			200		4.1
BT40-FMH25.4 -70- 60	1	80	60	70	1.9
-90			90		2.4
-150			150		3.4
BT40-FMH31.75 -76- 60	1	80	60	76	2.1
-90			90		2.6
-150			150		3.6
-200			200		4.4
-96- 60		100	60	96	2.4
-90			90		3.1
-150			150		4.1
-200			200		4.9
BT50-FMH16 -29- 90	1	32	90	29	3.9
-150			150		4.3
-37- 90		40	90	37	4.1
-150			150		4.7
-200			200		5.3

CODE	Fig.	Cutter dia.	L	φC1	kg
BT50-FMH22 -47- 90	1	50/52	90	47	4.4
-150			150		5.4
-200			200		6.2
-250			250		7.2
-300			300		8.3
-60- 90	1	63/66	90	60	4.8
-150			150		6.4
-200			200		7.8
-250			250		9.2
-300			300		10.8
BT50-FMH22.225-47- 90	1	50/52	90	47	4.4
-150			150		5.4
-200			200		6.2
-250			250		7.2
-300			300		8.3
-60- 90		63/66	90	60	4.8
-150			150		6.4
-200			200		7.7
-250			250		9.2
-300			300		10.8
BT50-FMH25.4 -70- 60	1	80	60	70	4.4
-90			90		5.3
-150			150		7.0
BT50-FMH31.75 -76- 60	1	80	60	76	4.5
-90			90		5.6
-150			150		7.6
-200			200		9.3
-250			250		11.0
-300			300		12.8
-96- 60		100	60	96	5.0
-90			90		6.4
-150			150		9.2
-200			200		11.5
-250			250		13.8
-300			300		16.2
BT50-FMH38.1 -100- 60	1	125	60	100	5.2
-90			90		6.6
-150			150		9.4
-200			200		11.7
-250			250		13.9
BT50-FMH50.8 -100- 60	1	160	60	100	5.4
-90			90		6.9
-150			150		9.6
-200			200		11.8
-250			250		14.1

■Common dimensions

CODE	φD	H	W	K	G	Clamp bolt
FMH16	16	17	8	5	M 8	M 8 ※
FMH22	22	18	10	5	M10	M10 ※
FMH22.225	22.225	17	8	3.5	M10	M10 ※
FMH25.4	25.4	22	9.5	5	M12	MBF-M12
FMH31.75	31.75	30	12.7	7	M16	MBF-M16
FMH38.1	38.1	34	15.9	9	M20	MBF-M20
FMH50.8	50.8	36	19.05	10	M24	MBF-M24

Clamp bolt



CODE	L	φC1	φC2	H1	H2	W	G	FMH model
MBF-M12	30	33	23	10	11	10	M12	FMH25.4
-M16	40	40				14	M16	FMH31.75
-M20	50	50	27	14	16	17	M20	FMH38.1
-M24	59	65	37			19	M24	FMH50.8

CODE	Fig.	Cutter dia.	L	φC1	kg
A63 -FMH16 -29- 45	2	32	45	29	0.8
- 90			90		1.1
-120			120		1.3
-37- 45		40	45	37	0.9
- 90			90		1.3
-120			120		1.6
A63 -FMH22 -47- 45	2	50/52	45	47	1.0
- 90			90		1.6
-150			150		2.6
-200			200		3.5
-60- 60		63/66	60	60	1.4
- 90			90		1.9
-150			150		2.9
-200			200		3.8
A63 -FMH22.225-47- 45	2	50/52	45	47	1.0
- 90			90		1.6
-150			150		2.6
-200			200		3.4
-60- 60		63/66	60	60	1.4
- 90			90		1.9
-150			150		2.9
-200			200		3.8
A63 -FMH25.4 -70- 60	2	80	60	70	1.6
- 90			90		2.1
-150			150		3.1
A63 -FMH31.75 -76- 60	2	80	60	76	1.7
- 90			90		2.3
-150			150		3.3
-200			200		4.1
-96- 60		100	60	96	2.1
- 90			90		2.9
-150			150		3.8
-200			200		4.6
A100-FMH16 -29- 90	2	32	90	29	2.4
-150			150		2.8
-37- 90		40	90	37	2.6
-150			150		3.3
-200			200		3.9
A100-FMH22 -47- 90	2	50/52	90	47	2.9
-150			150		3.9
-200			200		4.8
-250			250		5.8
-300			300		6.9

CODE	Fig.	Cutter dia.	L	φC1	kg
A100-FMH22 - 60- 90	2	63/66	90	60	3.5
-150			150		5.1
-200			200		6.4
-250			250		7.9
-300			300		9.5
A100-FMH22.225- 47- 90	2	50/52	90	47	2.9
-150			150		3.9
-200			200		4.8
-250			250		5.8
-300			300		6.9
- 60- 90		63/66	90	60	3.4
-150			150		5.0
-200			200		6.4
-250			250		7.9
-300			300		9.5
A100-FMH25.4 - 70- 60	2	80	60	70	3.1
- 90			90		4.0
-150			150		5.7
A100-FMH31.75 - 76- 60	2	80	60	76	3.3
- 90			90		4.3
-150			150		6.4
-200			200		8.1
-250			250		9.8
-300			300		11.5
- 96- 90		100	90	96	5.3
-150			150		8.1
-200			200		10.4
-250			250		12.7
-300			300		15.1
A100-FMH38.1 -100- 90	2	125	90	100	5.5
-150			150		8.2
-200			200		10.5
-250			250		12.8
A100-FMH50.8 -100- 90	2	160	90	100	5.7
-150			150		8.4
-200			200		10.7
-250			250		12.9

■Option
- Retention knob→P.64

■Std. Access.
- Coolant duct(Fixed) (HSK-A)→P.104
- Clamp bolt(unless marked with ※ in the list) ●Stopper key

■Note
- The clamp bolt marked with ※ in the list is a hexagonal socket bolt. Use a market standard bolt.
- Swing type coolant ducts are available upon request. For details, please contact us.

■Caution
- The required clamp bolt design depends on the cutter manufacturer and the type of cutter.

MICRO HEAD


Applicable for all applications, from finishing to roughing.

MFA

Finishing



coolant-through



ϕ20～102

Super precision finishing boring holder

MBH


Roughing

Semi-finishing

Finishing



coolant-through





ϕ50～380

Finishing and heavy duty boring holder

MBJ

Semi-finishing

Finishing




ϕ5.5～205

Wide range and multi-purpose boring holder


Super precision finishing boring holder MFA P. 57

Rigid design thanks to the square sliding head

The square slide system can achieve greater rigidity against cutting force compared to a round slide system since it has 2-face contact.




MST square slide




Competitors' round slide

Guaranteed fine adjustment

It allows 0.01mm dia. fine adjustment easily and precisely.The setting diameter doesn't change when you clamp the head.



Available for spindle-through coolant as standard.







System

MODEL	Boring dia.
MFA20	ϕ20～ 24.5
MFA24	ϕ24～ 30
MFA29	ϕ29～ 38
MFA36	ϕ36～ 52
MFA50	ϕ50～ 77
MFA75	ϕ75～102

Adjustable effective length

Using the extension allows for increased effective length




MODEL	Length(mm)
MFA20	30・35・40・45
MFA24	
MFA29	30・40・50・60
MFA36	40・50・60・70
MFA50	45・60・75・90
MFA75	

Finishing and heavy duty boring holder MBH P. 59


Sliding rack design ··· Wide adjusting range

The micro head, MBH provides a wide adjusting range and secure clamping by making use of the sliding rack design for fine adjustment in combination with dovetail clamping capability.




Dovetail clamping ··· High rigidity and accuracy

The dovetail clamping capability holds the slide portion firmly without needing to change the setting diameter when clamping the slide.
It is ideal for high-rigidity, high-accuracy boring applications.



System

MODEL	Boring dia.
MBH 50	ϕ 50 ~ 80
MBH 75	ϕ 75 ~ 120
MBH115	ϕ115 ~ 185
MBH180	ϕ180 ~ 250
MBH245	ϕ245 ~ 315
MBH310	ϕ310 ~ 380





coolant-through





Wide range and multi-purpose boring holder MBJ P. 61

The combination of two kinds of boring bars allows for a wide range of boring applications from 5.5mm to 205mm dia.

MBJ45








MBJ70






Cutting data P. 63

Micro Head for engraving

If you would like more detailed information, please contact MST and ask for a catalog.



MICRO HEAD MFA type (MFA)



BT50-MFA36-165

Fig. 1





Fig. 2





A100-MFA29-165

Fig. 3






Fig. 4






S32-MFA24-90

Fig. 5



CODE	Fig.	Boring dia. (φD)	L	M	φC1	φC2	Extension	Kg
BT30-MFA20- 90	1	20～ 24.5	90	63	19	—	—	0.6
-MFA24- 90		24～ 30			22			
-MFA29-105		29～ 38	105	78	27.6			0.7
-MFA36-105		36～ 52			34.4			0.9
BT40-MFA20-120	2	20～ 24.5	120	65	19	46	—	1.4
-150			150	81				1.5
-MFA24-150		24～ 30		62	22			1.7
-180			180	92			30	1.8
-MFA29-150		29～ 38	150	82	27.6		—	1.7
-180			180	112			30	1.8
-MFA36-150		36～ 52	150	97	34.4	62	—	1.9
-195			195	142			45	2.2
-MFA50-150		50～ 77	150	102	46		—	2.4
-195			195	147			45	3.0
-MFA75-150		75～102	150	102	51		—	2.5
-195			195	147			45	3.1
BT50-MFA20-165	2	20～ 24.5	165	54	19	62	—	4.9
-195			195	84			30	5.0
-240			240	64			—	6.3
-MFA24-165		24～ 30	165	52	22			4.9
-195			195	82			30	5.0
-240			240	62			—	6.3
-270			270	92			30	6.4
-MFA29-165		29～ 38	165	82	27.6	70	—	4.7
-195			195	112			30	4.8
-240			240	82			—	6.7
-270			270	112			30	6.9
-MFA36-165		36～ 52	165	97	34.4		—	4.6
-210			210	142			45	4.9
-255			255	97		80	—	7.9
-300			300	142			45	8.2
-MFA50-165	1	50～ 77	165	122	46	—	—	4.9
-210			210	167			45	5.5
-255	2		255	147		86	—	7.6
-300			300	192			45	8.2
-MFA75-165	1	75～102	165	122	51	—	—	5.0
-210			210	167			45	5.6
-255	2		255	147		86	—	7.7
-300			300	192			45	8.3

Extension



CODE	Applicable head	φD	L	Kg
MS0-30	MFA20	19	30	0.1
-35			35	0.1
-40			40	0.1
-45			45	0.1
MS1-30	MFA24	22	30	0.1
-35			35	0.1
-40			40	0.1
-45			45	0.1
MS2-30	MFA29	27.6	30	0.1
-40			40	0.2
-50			50	0.2
-60			60	0.3
MS3-40	MFA36	34.4	40	0.3
-45			45	0.3
-50			50	0.3
-60			60	0.4
-70			70	0.5
MS4-45	MFA50 MFA75	46	45	0.6
-60			60	0.7
-75			75	0.9
-90			90	1.1

■Caution

- Longer projection length causes chattering and reduced rigidity

Insert



CODE	R	Insert material	Q'ty	Work material
TPA082-PA	0.2	Cermet	10pcs.	Steel
TPA084-PA	0.4			
TPA082-MA	0.2	Carbide		Stainless
TPA084-MA	0.4			
TPA082-KA	0.2			Cast iron
TPA084-KA	0.4			
TPA082-NA	0.2			Aluminum
TPA084-NA	0.4			
TPA082-ND	0.2	Polycrystalline diamond	1pc.	
TPA084-ND	0.4			

CODE	Fig.	Boring dia. (φD)	L	M	φC1	φC2	Extension	D1	L1	Kg
A40 -MFA20- 90	3	20～ 24.5	90	65	19	—	—	—	—	0.4
-MFA24- 90		24～ 30			22					
-MFA29-105		29～ 38	105	82	27.6					0.6
-MFA36-105		36～ 52			34.4					0.8
-MFA50-105		50～ 77			46					1.2
A50 -MFA20-120	4	20～ 24.5	120	69	19	41	—	—	—	0.8
-MFA24-120		24～ 30			22					0.9
-MFA29-120		29～ 38		82	27.6					
-MFA36-120	3	36～ 52		91	34.4	—				1.1
-MFA50-120		50～ 77			46					1.6
-MFA75-120		75～102			51					1.7
A63 -MFA20-150	4	20～ 24.5	150	81	19	46	—	—	—	1.3
-MFA24-150		24～ 30		62	22					1.5
-180			180	92			30			1.6
-MFA29-150		29～ 38	150	82	27.6		—			1.5
-180			180	112			30			1.6
-MFA36-150		36～ 52	150	97	34.4	52	—			1.7
-195			195	142			45			2.0
-MFA50-150		50～ 77	150	102	46		—			2.2
-195			195	147			45			2.7
-MFA75-150		75～102	150	102	51		—			2.3
-195			195	147			45			2.8
A100 -MFA20-165	4	20～ 24.5	165	54	19	62	—	—	—	3.8
-195			195	84			30			3.9
-240			240	64			—			5.3
-MFA24-165		24～ 30	165	52	22					3.8
-195			195	82			30			3.9
-240			240	62			—			5.4
-270			270	92			30			5.5
-MFA29-165		29～ 38	165	82	27.6	70	—			3.7
-195			195	112			30			3.8
-240			240	82			—			5.8
-270			270	112			30			6.0
-MFA36-165		36～ 52	165	97	34.4	80	—			3.7
-210			210	142			45			4.0
-255			255	97			—			7.2
-300			300	142			45			7.5
-MFA50-165	3	50～ 77	165	131	46	—	—			3.6
-210			210	176			45			4.2
-255	4		255	147		85	—			6.7
-300			300	192			45			7.3
-MFA75-165	3	75～102	165	131	51	—	—			3.7
-210			210	176			45			4.3
-255	4		255	147		85	—			6.8
-300			300	192			45			7.4
F63 -MFA20-150	4	20～ 24.5	150	81	19	46	—	—	—	1.3
-MFA24-150		24～ 30		62	22					1.5
-180			180	92			30			1.6
-MFA29-150		29～ 38	150	82	27.6		—			1.5
-180			180	112			30			1.6
-MFA36-150		36～ 52	150	97	34.4	52	—			1.7
-195			195	142			45			2.0
-MFA50-150		50～ 77	150	102	46		—			2.2
-195			195	147			45			2.7
ST25T-MFA20- 75	5	20～ 24.5	75	75	19	—	—	25	70	—
-MFA24- 90		24～ 30	90	85	22					
-MFA29-105		29～ 38	105	105	27.6					
S 32 -MFA20- 90	5	20～ 24.5	90	75	19	—	—	32	70	—
-MFA24- 90		24～ 30		80	22					
-MFA29-105		29～ 38	105	95	27.6					
-MFA36-105		36～ 52			34.4					
-MFA50-105		50～ 77			46					

Cutting data
P. 63

■**Option**
- Insert
- Retention knob(BT)→P.64

■**Std. Access.**
- T wrench
- Insert clamping screw
- Coolant duct(Fixed)(HSK-A)→P.104
- Torx wrench

■**Note**
- Swing type coolant ducts are available upon request. For details, please contact us.
- Drive key slot and cutting direction are in alignment.
- The extension mentioned in the list is set between shank and head. The number refers to the extension length.

MICRO HEAD MBH type (MBH)



BT50-MBH180-225



A100-MBH75-165

Fig. 1




Fig. 2




Fig. 3




Fig. 4




Fig. 5





Fig. 6



CODE	Fig.	Boring dia. (ϕD)	L	M	ϕC	L1	Cartridge	Kg
BT40-MBH 50-150	2	50～ 80	150	118	45	—	PTC 10 STGP10	2.1
-210	1		210	155		28		3.0
-MBH 75-165	3	75～120	165	165	70	—	PTC 12 STGP12	4.0
-MBH115-165		115～185			110			5.9
-MBH180-165		180～250			153			6.6
BT50-MBH 50-150	2	50～ 80	150	107	45	—	PTC 10 STGP10	4.5
-180			180	137				5.6
-240	1		240	155		47		6.3
-300			300			107		7.0
-MBH 75-165	3	75～120	165	127	70	—	PTC 12 STGP12	6.7
-225			225	187				8.5
-285			285	247				10.3
-315			315	277				11.2
-MBH115-165		115～185	165	165	110			8.6
-225			225	225				10.4
-285			285	285				12.2
-315			315	315				13.1
-MBH180-165		180～250	165	165	153			9.3
-225			225	225				11.1
-285			285	285				12.9
-MBH245-165		245～315	165	165	200			10.0
-225			225	225				11.8
-285			285	285				13.6
-MBH310-165		310～380	165	165	255			11.0
-225			225	225				12.8
A50M-MBH 50-135	5	50～ 80	135	109	45	—	PTC10/STGP10	1.6
-MBH 75-175		75～120	175	149	70		PTC12/STGP12	3.4
A63 -MBH 50-150	5	50～ 80	150	119	45	—	PTC 10 STGP10	1.9
-210			210	179				2.6
-MBH 75-195	6	75～120	195	195	70		PTC 12 STGP12	4.5
-MBH115-195		115～185			110			6.5
-MBH180-195		180～250			153			7.2
A100-MBH 50-150	5	50～ 80	150	116	45	—	PTC 10 STGP10	3.3
-180			180	146				3.6
-240	4		240	155		56		5.2
-300			300			116		6.8
-MBH 75-165	6	75～120	165	131	70	—	PTC 12 STGP12	5.3
-225			225	191				6.9
-285			285	251				8.6
-315			315	281				9.4

CODE	Fig.	Boring dia. (φD)	L	M	φC	L1	Cartridge	Kg
A100-MBH115-165	4	115～185	165	165	110	—	PTC 12	7.2
-225			225	225			STGP12	8.9
-285			285	285				10.5
-315			315	315				11.4
-MBH180-165		180～250	165	165	153			7.9
-225			225	225				9.6
-285			285	285				11.2
-MBH245-165		245～315	165	165	200			8.7
-225			225	225				10.3
-285			285	285				12.0
-MBH310-165		310～380	165	165	255			9.6
-225			225	225				11.2

Cutting data ➔P. 63

■**Option**
- Insert ● Cartridge ● Coolant-through ● Retention knob(BT)→P.64


■**Std. Access.**
- T wrench ● Coolant duct(Fixed) (HSK-A)→P.104


■**Note**
- Swing type coolant ducts are available upon request. For details, please contact us.
- Drive key slot and cutting direction are in alignment.
- Add "C" after the MBH model no. for through-spindle coolant when you order. (Example: BT50-MBH75C-165)

■**Caution**
- Each slide part is produced to match precisely with its corresponding slide, so such parts are not interchangeable with each other.
- The undercut area of the A50M is different from the standards. Please be careful to check for interference with the ATC arm.



Cartridge






CODE	Work-piece material	Holder type
PTC10	Steel・Cast Iron・Stainless	MBH50
STGP10	Steel・Cast Iron Stainless・Aluminum	
PTC12	Steel・Cast Iron	MBH75 ～310
STGP12	Steel・Cast Iron Stainless・Aluminum	

■**Note**
- PTC : Pin lock type
- STGP: Clamp-on type

Insert





CODE	R	Insert material	Work-piece material	Application	Q'ty	Cartridge
TNB114-PB	0.4	Carbide coating	Steel	Semi-finishing	10pcs.	PTC 10
-MB		Carbide	Stainless			
-KB			Cast iron			
-PMA		Cermet	Steel・stainless	Finishing		
-KA		Carbide	Cast iron			
TPC112-PA	0.2	Cermet	Steel	Finishing	10pcs.	STGP10
TPC114-PA	0.4					
TPC112-MA	0.2	Carbide	Stainless			
TPC114-MA	0.4					
TPC112-KA	0.2		Cast iron			
TPC114-KA	0.4					
TPC112-NA	0.2		Aluminum			
TPC114-NA	0.4					
TPC112-ND	0.2	Polycrystalline diamond			1pc.	
TPC114-ND	0.4					
TNB168-PB	0.8	Carbide coating	Steel	Semi-finishing	10pcs.	PTC 12
-MB			Stainless			
-KB		Carbide	Cast iron			
TNB164-PMA	0.4	Cermet	Steel・stainless	Finishing		
-KA		Carbide	Cast iron			
TPC164-PA	0.4	Cermet	Steel	Finishing	10pcs.	STGP12
-MA		Carbide coating	Stainless			
-KA		Carbide	Cast iron			
-NA			Aluminum			
-ND		Polycrystalline diamond			1pc.	

MICRO HEAD MBJ45 type (MBJ45)



A100-MBJ45-150

Fig. 1






Fig. 2





S32-MBJ45-105

Fig. 3



CODE	Fig.	Boring dia. (ϕD)	L	M	Kg
BT30-MBJ45-120	1	5.5～80	120	98	1.3
BT40-MBJ45-150	1	5.5～80	150	123	2.2
BT50-MBJ45-150	1	5.5～80	150	112	4.6
-180			180	142	5.6
A63 -MBJ45-150	2	5.5～80	150	124	2.0
A100-MBJ45-150	2	5.5～80	150	121	3.3
-180			180	151	3.7
S32 -MBJ45-105	3	5.5～80	—	—	—

■**Option**
- Insert ●Insert holder
- Insert and insert holder set ●Retention knob(BT)→P.64

■**Std. Access.**
- Wrench set
- Coolant duct(Fixed) (HSK-A)→P.104

■**Note**
- Swing type coolant ducts are available upon request. For details, please contact us.
- Drive key slot and cutting direction are in alignment.

Insert holder, Insert

For center hole




STV-C1208 STV1216

Boring diameter ϕ5.5～8

Insert holder


CODE
STV-C12055

Carbide shank



Insert

CODE	R	Insert material	Q'ty	Work material
TPE042-PA	0.2	Cermet	10pcs.	Steel
-MKA		Carbide coating		Stainless Cast iron
-NA		Carbide		Aluminum




Boring diameter ϕ8～10

Insert holder


CODE
STV-C1208

Carbide shank



Insert

CODE	R	Insert material	Q'ty	Work material
TPE032-PA	0.2	Cermet	10pcs.	Steel
TPE034-PA	0.4			
TPE032-MKA	0.2	Carbide coating		Stainless Cast iron
TPE034-MKA	0.4			
TPE032-NA	0.2	Carbide		Aluminum
TPE034-NA	0.4			




Boring diameter ϕ10～12

Insert holder


CODE
STV-C1210

Carbide shank



Insert

CODE	R	Insert material	Q'ty	Work material
TPE082-PA	0.2	Cermet	10pcs.	Steel
TPE084-PA	0.4			
TPE082-MA	0.2	Carbide		Stainless
TPE084-MA	0.4			
TPE082-KNA	0.2			Cast iron Aluminum
TPE084-KNA	0.4			




Boring diameter ϕ12～14

Insert holder


CODE
STV-C1212

Carbide shank



Insert

CODE	R	Insert material	Q'ty	Work material
TPE112-PA	0.2	Cermet	10pcs.	Steel
TPE114-PA	0.4			
TPE112-MA	0.2	Carbide coating		Stainless
TPE114-MA	0.4			
TPE112-KNA	0.2	Carbide		Cast iron Aluminum
TPE114-KNA	0.4			




Boring diameter ϕ14～46

Insert holder


CODE
STV-C1214

Carbide shank



Insert

CODE	R	Insert material	Q'ty	Work material
TPE112-PA	0.2	Cermet	10pcs.	Steel
TPE114-PA	0.4			
TPE112-MA	0.2	Carbide coating		Stainless
TPE114-MA	0.4			
TPE112-KNA	0.2	Carbide		Cast iron Aluminum
TPE114-KNA	0.4			




Boring diameter ϕ16～48

Insert holder


CODE
STV1216

Steel shank



Insert

CODE	R	Insert material	Q'ty	Work material
TPC092-PA	0.2	Cermet	10pcs.	Steel
TPC094-PA	0.4			
TPC092-MA	0.2	Carbide		Stainless
TPC094-MA	0.4			
TPC092-KNA	0.2			Cast iron Aluminum
TPC094-KNA	0.4			
TPC092-ND	0.2	Polycrystalline diamond	1pc.	Aluminum
TPC094-ND	0.4			



For inclined hole


S-STA12

Boring diameter ϕ48～80

Insert holder

CODE
S-STA12

Steel shank



Insert

CODE	R	Insert material	Q'ty	Work material
TPC112-PA	0.2	Cermet	10pcs.	Steel
TPC114-PA	0.4			
TPC112-MA	0.2	Carbide		Stainless
TPC114-MA	0.4			
TPC112-KA	0.2			Cast iron
TPC114-KA	0.4			
TPC112-NA	0.2			Aluminum
TPC114-NA	0.4			
TPC112-ND	0.2	Polycrystalline diamond	1pc.	
TPC114-ND	0.4			

Insert and insert holder set

CODE	Insert holder	Q'ty	Insert	Q'ty	Work material
PJ-45	STV1216	1pc.	TPC094-PA	10pcs.	Steel
	S-STA12		TPC114-PA		
KJ-45	STV1216	1pc.	TPC094-KNA	10pcs.	Cast iron
	S-STA12		TPC114-KA		Aluminum


STV1216 S-STA12


TPC094


TPC114

MICRO HEAD MBJ70 type (MBJ70)


BT50-MBJ70-165

Fig. 1





Fig. 2



CODE	Fig.	Chucking range(ϕD)	L	Kg
BT40-MBJ70-165	1	22～205	165	4.2
BT50-MBJ70-165	1	22～205	165	6.5
A63 -MBJ70-195	2	22～205	195	4.6
A100-MBJ70-165	2	22～205	165	5.4

■**Option**
- Insert ●Insert holder ●Insert and insert holder set
- Clamping sleeve ●Retention knob (BT)→P.64

■**Std. Access.**
- Wrench set ●Coolant duct (Fixed) (HSK-A)→P.104

■**Note**
- Swing type coolant ducts are available upon request. For details, please contact us.
- Drive key slot and insertion direction are in alignment.
- The throw-away insert for aluminum is a diamond insert. Sales unit is per 1 piece.

Insert holder, Insert

For center hole · inclined hole


S-STV1822


Boring diameter ϕ22 ～ 107

Insert holder


CODE
S-STV1822

Steel shank

Center hole




Offset hole



Insert

CODE	R	Insert material	Q'ty	Work material
TPC112-PA	0.2	Cermet	10pcs.	Steel
TPC114-PA	0.4			
TPC112-MA	0.2	Carbide		Stainless
TPC114-MA	0.4			
TPC112-KA	0.2			Cast iron
TPC114-KA	0.4			
TPC112-NA	0.2			Aluminum
TPC114-NA	0.4			
TPC112-ND	0.2	Polycrystalline diamond	1pc.	
TPC114-ND	0.4			





For side hole


Boring diameter ϕ100～205


STH18

Insert holder

CODE
STH18

Steel shank




A	ϕD
15	100～145
35	140～185
45	160～205

Insert

CODE	R	Insert material	Q'ty	Work material
CCD094-PA	0.4	Carbide coating	10pcs.	Steel
CCD094-MA				Stainless
CCD094-KA		Carbide		Cast iron
CCD094-NA				Aluminum
CCD094-ND		Polycrystalline diamond	1pc.	





Insert and insert holder set

CODE	Insert holder	Q'ty	Insert	Q'ty	Work material
PJ-70	S-STV1822	1pc.	TPC114-PA	10pcs.	Steel
	STH18		CCD094-PA		
KJ-70	S-STV1822	1pc.	TPC114-KA	10pcs.	Cast iron
	STH18		CCD094-KA		


S-STV1822


STH18



TPC114


CCD094

Cutting data

MFA type


S45C – Finishing –
Insert : TPA084-PA (Nose R0.4)



n 3317 min-1
Vf 331 mm/min
Vc 250 m/min
f 0.1 mm/rev

BT50-MFA24-270


SUS304 – Finishing –
Insert : TPA084-MA (Nose R0.4)



n 1326 min-1
Vf 132 mm/min
Vc 100 m/min
f 0.1 mm/rev

BT50-MFA24-240


FC250 – Finishing –
Insert : TPA084-KA (Nose R0.4)



n 636 min-1
Vf 63 mm/min
Vc 100 m/min
f 0.1 mm/rev

BT50-MFA50-300

A5056 – Finishing –
Insert : TPA084-NA (Nose R0.4)




n 3538 min-1
Vf 353 mm/min
Vc 400 m/min
f 0.1 mm/rev

BT50-MFA36-300

MBH type


S45C – Semi-finishing –
Insert : TNB168-PB (Nose R0.8)
Cartridge : PTC12



n 575 min-1
Vf 86 mm/min
Vc 150 m/min
f 0.15 mm/rev

BT50-MBH75-315


SUS304 – Semi-finishing –
Insert : TNB168-MB (Nose R0.8)
Cartridge : PTC12



n 383 min-1
Vf 57 mm/min
Vc 100 m/min
f 0.15 mm/rev

BT50-MBH75-315


FC250 – Semi-finishing –
Insert : TNB168-KB (Nose R0.8)
Cartridge : PTC12



n 383 min-1
Vf 57 mm/min
Vc 100 m/min
f 0.15 mm/rev

BT50-MBH75-315


A5056 – Semi-finishing –
Insert : TPC164-NA (Nose R0.4)
Cartridge : STGP12



n 806 min-1
Vf 120 mm/min
Vc 200 m/min
f 0.15 mm/rev

BT50-MBH75-315


S45C – Finishing –
Insert : TPC164-PA (Nose R0.4)
Cartridge : STGP12



n 1057 min-1
Vf 105 mm/min
Vc 250 m/min
f 0.1 mm/rev

BT50-MBH75-315


SUS304 – Finishing –
Insert : TPC164-MA (Nose R0.4)
Cartridge : STGP12



n 507 min-1
Vf 50 mm/min
Vc 120 m/min
f 0.1 mm/rev

BT50-MBH75-315


FC250 – Finishing –
Insert : TPC164-KA (Nose R0.4)
Cartridge : STGP12



n 507 min-1
Vf 50 mm/min
Vc 120 m/min
f 0.1 mm/rev

BT50-MBH75-315

A5056 – Finishing –
Insert : TPC164-NA (Nose R0.4)
Cartridge : STGP12




n 1693 min-1
Vf 169 mm/min
Vc 400 m/min
f 0.1 mm/rev

BT50-MBH75-315

MBJ type


S45C – Finishing –
Insert : TPE032-PA (Nose R0.2)
Insert holder : STV-C1208



n 3107 min-1
Vf 186 mm/min
Vc 80 m/min
f 0.06 mm/rev

BT40-MBJ45-150


SUS304 – Finishing –
Insert : TPE032-MKA (Nose R0.2)
Insert holder : STV-C1208



n 1165 min-1
Vf 69 mm/min
Vc 30 m/min
f 0.06 mm/rev

BT40-MBJ45-150


FC250 – Finishing –
Insert : TPE032-MKA (Nose R0.2)
Insert holder : STV-C1208



n 3107 min-1
Vf 186 mm/min
Vc 80 m/min
f 0.06 mm/rev

BT40-MBJ45-150

A5056 – Finishing –
Insert : TPE032-NA (Nose R0.2)
Insert holder : STV-C1208



n 6602 min-1
Vf 396 mm/min
Vc 170 m/min
f 0.06 mm/rev

BT40-MBJ45-150

Retention knob




Caution


- Retention knobs in this catalog are typical models for various machine tool companies. Confirm the correct retention knob design refer to the machine specification sheet.
- We manufacture other kinds of retention knobs. Please contact us for the details.

Machine manufacturers	Standard type						For through spindle coolant type		
	BT30		BT40		BT50		BT30	BT40	BT50
	Standard	Standard type with a through hole	Standard	Standard type with a through hole	Standard	Standard type with a through hole			
OKUMA	–		P40T-2 (MB series)	P-339 (MB series)	P50T-2	P-419	–	P-499	P-419
			P40T-1 (MILLAC series)	P-297 (MILLAC series)					
OKK	–		P40T-1	–	P-143	–	–	–	–
OHTORI	–		P40T-1	P-297	P50T-1	P-299	–	–	–
KITAMURA	P30T-1	P-445	P-348	P-323-1	P-400		–	P-323-1	P-400
	P-399 (Mycenter-1Xi)								
KIRA	P30T-1	P-445	P40T-1	P-297	–		–	P-323-1	–
KIWA	P30T-1	P-445	P-348	P-323-1	P-400		–	P-323-1	P-400
KURASHIKI	–		P40T-1	P-297	P50T-1	P-299	–	–	–
KOMATSU NTC	P30T-1	P-445	P40T-1	P-297	P50T-1	P-299	P-522	P-505	P-384
JTEKT	–		P40T-1	P-297	P50T-1	P-299	–	P-297	P-299
SHIZUOKA	P30T-1	P-445	P-141	P-498	P-143	P-402	–	–	–
SNK	–		P40T-2	P-339	P50T-2	P-419	–	–	–
SUGINO	P30T-2	P-497	–		–		–	–	–
DMG MORI	P30T-1	P-445	P-141	–	P-143	–	–	P-435	P-513
TOSHIBA MACHINE	–		–		P50T-1	P-299	–	–	–
NIIGATA MACHINE TECHNO	–		–		P50T-2	P-419	–	–	–
FANUC	P30T-1	P-522	–		–		P-522	–	–
BROTHER	P30T-2	P-511	–		–		P-511	–	–
HOWA	P30T-1	P-445	P40T-1	P-297	P50T-1	P-299	–	–	–
MAKINO	–		P40T-1 (V-series)	P-297 (V-series)	P50T-1 (A, MCC, V-series)	P-299 (A, MCC, V-series)	–	P-323-1	P-299
			P-348 (a-series, D-series)	P-323−1 (a-series, D-series)	P-400 (A-series, a-series)				
MATSUURA	P30T-2	P-511	P-348	P-323-1	P50T-2	P-419	–	P-323-1	–
	P-399				P-400				
MITSUI SEIKI	–		P-007	–	P-008	P-250	–	–	–
MITSUBISHI	–		P40T-1	–	P50T-2	–	–	–	–
YASDA	–		P-348	P-438	P50T-1	P-299	–	P-509	P-459
					P-400 (YBM1218V)			–	P-288-1 (YBM1218V)
YAMAZAKI GIKEN	–		P40T-1	P-297	P50T-2	P-419	–	–	–
MAZAK	–		P-227		P-514		–	P-227	P-514

BT30




CODE	ϕD	ϕd	θ	Note
P30T-1	7	-	45	MAS-1
P-445		3		P30T-1 through hole
P30T-2		-	60	MAS-2
P-497		2		P30T-2 through hole
-522	8	4	45	FANUC center-through
-511	7.5	2.5	60	BROTHER center-through




CODE	Note
P-399	JIS30P


BT40




CODE	ϕd	θ	Note
P40T-1	-	45	MAS-1
P-297	4		P40T-1 through hole
P40T-2	-	60	MAS-2
P-339	4		P40T-2 through hole
-141	-	90	-
-498	4		P-141 through hole
-505	3	45	KOMATSU NTCcenter-through




CODE	ϕd	Note
P-348	-	JIS40P
-323-1	7	P-348 through hole
-499	4	OKUMA center-through
-438	7	YASDA through hole
-509		YASDA center-through



CODE	Note
P-007	MITSUI SEIKI




CODE	Note
P-227	MAZAK




CODE	Note
P-435	DMG MORI center-through


BT50




CODE	ϕd	θ	Note
P50T-1	-	45	MAS-1
P-299	6		P50T-1 through hole
P50T-2	-	60	MAS-2
P-419	6		P50T-2 through hole
-143	-	90	-
-402	7		P-143 through hole
-459		45	YASDA center-through
-513	8	90	DMG MORI center-through
-384	5.5	45	KOMATSU NTC center-through



CODE	ϕd	Note
P-400	10	JIS50P
-288-1	6	P-400 through hole



CODE	ϕd	Note
P-008	-	MITSUI SEIKI
-250	8	P-008 through hole



CODE	Note
P-514	MAZAK

HSK-T Tooling Systems for Turning Mill

Set screw holders for Round shank

For through-spindle coolant
CC type



For nozzle-coolant
CN type



P. 69

World standard ISO

for Turning Mill

HSK TOOLING SYSTEM

Insert holders for Square-shank

For external turning and cutting off
SV type



For external / face turning
SA type



For external / face turning
SB type



For external / face turning
SC type



For external / face turning
SN type



For face turning
SH type



P. 70

BLANK TOOL



P. 72

CHECKING ARBOR




P. 72



HSK-T TOOLING SYSTEMS for TURNING MILL

The obvious choice for ISO standard, HSK-T specs turning mill spindles!!



- A full range of milling tool holders, covering 70% of multi-tasking machine applications!
- Compatible with machining center holders!
- Supplied by tool holder manufacturer world wide!
- Extensive line-up and reasonable price!


Standardized by many machine tool manufacturers!


OKUMA · MULTUS SERIES · MACTURN SERIES etc	DMG MORI · NT(NTX) Series · CTX Series	Nakamura-tome Precision Industry · Super NTJX Series · Super NTMX Series etc	YAMAZAKI MAZAK · INTEGREX i Series J Series e Series etc
MATSUURA MACHINERY CORPORATION · CUBLEX Series	HERMLE · MT Series	HORKOS · NS70 Version	

Turning tools (HSK-T standard)

Maintains high precision during turning operation


By using an ICTM tool holder, which minimizes the gap between the machine spindle drive key and tool holder drive key way, the height of the cutting edge is maintained precisely and variation in workpiece diameter is minimized.





High bending rigidity


During turning, the cutting force of a spindle axis becomes very large. Therefore, a rigid, two-face-contact clamping system performs very well.



Designed to shorten undercut area

We made an undercut area thicker and as short as possible in order to increase the holder rigidity.

Improved rigidity !




Undercut area


Width	4 mm
Depth	0.5 mm

Rotating tools (HSK-A standard)

Compatible with machining center

Needless to say, the holder of a machining center and a turning mill machine can be shared.






Sharable



Pre-balanced design


The HSK-A-type shank is unbalanced in its standard form, but at MST we have applied our original pre-balancing to make the tool holders applicable for high-speed machining. According to DIN standards, only the area marked with ※ in the hollow shank needs to be finished. However, MST provides perfect finishing for all areas after heat treatment in order to improve balance.




Set screw holders for Round shank

CC type for through-spindle coolant


T63-CC32-90





CODE	L	ϕD	ϕC	H1	M	Kg
T40 -CC32- 90	90	32	58	62	M12	1.2
T50 -CC32- 85	85	32	62	62	M12	1.4
T63 -CC32- 90	90	32	62	62	M12	1.6
-CC40-100	100	40	68	72		2
T100-CC40-105	105	40	82	72	M12	4.5
-CC50-115	115	50	92	82	M14	5.3


■**Option**
- Sleeve for set screw holder (SS)


■**Std. Access.**
- Coolant duct→P.104

■**Note**
- Available for both boring bar and indexable drill.

CN type for nozzle-coolant


T63-CN32-95





CODE	L	ϕD	ϕC	H1	M	Kg
T40 -CN32- 95	95	32	70	62	M12	2
T50 -CN32-100	100	32	70	62	M12	2.1
T63 -CN32- 95	95	32	70	62	M12	2.2
-CN40-105	105	40	78	71		2.7
T100-CN40-115	115	40	82	72	M12	4.9
-CN50-125	125	50	92	82	M14	5.8


■**Option**
- Sleeve for set screw holder (SS)

■**Std. Access.**
- Coolant duct→P.104
- Detent plug for a nozzle A =Set screw (M5-12L)
- Detent plug for Center through B =Set screw (M5-5L)

■**Note**
- The coolant nozzle direction is adjustable.
- Nozzle-coolant type is available for through-spindle coolant.
- Available for both boring bar and indexable drill.

Sleeve for set screw holders





CODE	L	ϕD	ϕC1	ϕC2	H1	G
SS32- 8	55	8	38	32	35	M 6
-10		10			40	M 8
-12		12			45	
-16		16			50	
-20		20				
-25		25			58	※
SS40- 8	60	8	46	40	35	M 6
-10		10			40	M 8
-12		12			45	
-16		16			50	
-20		20				M10
-25		25			58	
-32		32			62	※


■**Note**
- Items marked with ※ in the G section of the list means they are screw-tightening type.
- Available for both boring bar and indexable drill.


Insert holders for Square-shank


SV type for external turning and cutting off



T63-SV2525R-105







CODE	L	L1	L2	(LA)	(LB)	A1	A2	A3	B1	B2	B3	M	Q	Kg
T40 -SV2020R- 90	90	15	60	120	90	24.5	39	20	25	22	20	M10	78	1.5
-SV2020L- 90														
T50 -SV2020R- 95	95	15	60	125	90	25	43.5	20	25	25	20	M10	87	1.9
-SV2020L- 95														
T63 -SV2020R-105	105	20	70	135	100	32	45	20	33	32	20	M12	90	2.7
-SV2020L-105														
-SV2525R-105※							53.5	25	38		25		108	3.1
-SV2525L-105※														
-SV2525R-105D	105			135			45		28				90	2.7
-SV2525L-105D														
-SV2525R-115	115			145			53.5		38				108	3.3
-SV2525L-115														
T100-SV2525R-150	150	20	70	190	150	37	59	25	48	43	25	M12	118	9.1
-SV2525L-150														
-SV3232R-150		25	100	195	145	40	68.5	32	47		32	M14	137	9.3
-SV3232L-150														

■ **Std. Access.**
- Coolant duct→P.104

■ **Note**
- The coolant nozzle direction is adjustable.


■ **Caution**
- The maximum coolant pressure for the nozzle on the holder is 1.5MPA.
- The holder marked with ※ in the chart cannot be installed on the Mazak INTEGREX I and J series.


SA type for external / face turning


The multi-inserts type holder reduces using holders quantity, it saves A.T.C. magazine pot.



T63-SA2525-105







CODE	L	L1	(LA)	(LB)	A1	A2	B1	B2	Q	Kg
T63 -SA2525-105※	105	70	135	100	32	54	38	38	108	3.7
-115	115		145							
T100-SA2525-150	150	70	185	105	37	59	48	48	118	9.3

■ **Std. Access.**
- Coolant duct→P.104
- Detent plug for a nozzle＝Set screw (M5-12L) (Ex.) When using only right-hand, plug the nozzle on the left-hand side.

■ **Note**
- The coolant nozzle direction is adjustable.


■ **Caution**
- The maximum coolant pressure for the nozzle on the holder is 1.5MPa.
- The holder marked with ※ in the chart cannot be installed on the Mazak INTEGREX I and J series.


SB type for external / face turning


The multi-inserts type holder reduces using holders quantity, it saves A.T.C. magazine pot.



T63-SB2525-95







CODE	L	Kg
T63-SB2525- 95※	95	3.2
-105	105	

■ **Std. Access.**
- Coolant duct→P.104
- Detent plug for a nozzle=Set screw(M5-12L)
  (Ex.) When using only right-hand, plug the nozzle on the left-hand side.

■ **Note**
- The coolant nozzle direction is adjustable.


■ **Caution**
- The maximum coolant pressure for the nozzle on the holder is 1.5MPa.
- The holder marked with ※ in the chart cannot be installed on the Mazak INTEGREX I and J series.


SC type for external / face turning


The multi-inserts type holder reduces using holders quantity, it saves A.T.C. magazine pot.



T63-SC2020R-105







CODE	L	L1	(LA)	(LB)	(A1)	(A2)	A3	B1	B2	B3	M	Q	Kg
T40 -SC1616R- 90	90	60	110	80	38	38	16	30	38.5	16	M10	77	1.7
T50 -SC2020R- 95	95	60	125	90	44.5	44.5	20	35	45	20	M10	90	2.4
T63 -SC2020R-105	105	70	140	105	44.5	44.5	20	35	45	20	M12	90	3.0
T100-SC2525R-150	150	70	185	105	59	59	25	48	59	25	M12	108	9.7

■ **Std. Access.**
- Coolant duct→P.104
- Detent plug for a nozzle=Set screw(M5-12L)


■ **Note**
- The coolant nozzle direction is adjustable.


■ **Caution**
- The maximum coolant pressure for the nozzle on the holder is 1.5MPa.


SN type for external / face turning



T63-SN2525R-110







CODE	L	(LA)	(LB)	A1	A2	A3	B1	B2	B3	M	Q	Kg
T40 -SN2020R-100	100	125	80	25	40	20	32	32	20	M10	80	1.7
T50 -SN2020R-110	110	135	85	25	45	20	35	35	20	M10	90	2.2
T63 -SN2020R-110	110	135	85	25	45	20	35	35	20	M10	90	2.5
-SN2020L-110												
-SN2525R-110		140	105	32	53	25	39	39	25	M12	106	3.2
-SN2525L-110												
T100-SN2525R-135	135	165	105	32	54	25	43	43	25	M12	108	6.1
-SN2525L-135												
-SN3232R-135		175	120	37	68.5	32	48		32	M14	137	7.2
-SN3232L-135												


■ **Std. Access.**
- Coolant duct→P.104


■ **Note**
- The coolant nozzle direction is adjustable.


■ **Caution**
- The maximum coolant pressure for the nozzle on the holder is 1.5MPa.

SH type for face turning









CODE	L	(LA)	(LB)	A1	A2	B1	B2	B3	M	Q	Kg
T40 -SH2020- 75	75	79	70	25	20	25	25	20	M12	80	1.2
-120	120	124									1.6
T50 -SH2020- 90	90	94	75	25	20	27.5	27.5	20	M12	90	1.8
-120	120	124									2.3
T63 -SH2020- 90	90	94	80	32	20	30	30	20	M12	90	2.5
-SH2525- 90		97	100		25	40.5	40.5	25		108	2.9
-120	120	127									3.6
T100-SH2525-105	105	112	120	32	25	48	48	25	M12	118	6.1
-150	150	157									8.8
-SH3232-105	105	113	145	40	32	57	57	32	M14	148	7.7


■ **Std. Access.**
- Coolant duct→P.104 • Detent plug for a nozzle=Set screw(M5-12L)
(Ex.) When using only right-hand, plug the nozzle on the left-hand side.

■ **Note**
- The coolant nozzle direction is adjustable.

■ **Caution**
- The maximum coolant pressure for the nozzle on the holder is 1.5MPa.

BLANK TOOL (For additional machining)





CODE	L	L1	ϕC	A°	Kg
T40 -BL 32- 35	35	15	32	0	0.3
-BL 48-120	120	97	48	15	1.6
-BL 95- 75	75	52	95		2.9
T50 -BL 40- 42	42	16	40	0	0.6
-BL 62-150	150	120	62	15	3.3
-BL105- 90	90	60	105		4.3
T63 -BL 52- 45	45	19	52	0	1.0
-BL 75-200	200	168	75	15	6.6
-BL115- 90	90	58	115		5.5
T100-BL 87- 45	45	16	87	0	2.8
-BL100-200	200	166	100		12.6
-BL118-120	120	86	118	15	9.7


■ **Std. Access.**
- Coolant duct→P.104

■ **Note**
- Material: SNCM439, Heat treatment hardness : 43HRC±2
- Hardening depth indicates depth to the center.

■ **Caution**
- If heat treatment is applied again to a holder produced from a blank tool, the original taper area may be deformed. Therefore, please do not apply heat treatment.

CHECKING ARBOR





CODE	L	L1	ϕD	A	Kg
T40 -CAAX32-150	150	10	32	60	1.1
T50 -CAAX40-150	150	10	40	70	1.7
T63 -CAAX52-150	150	10	52	90	2.9
T100-CAAX60-250	250	12	60	110	7.2


■ **Std. Access.**
- Coolant duct→P.104
- Special case

■ **Usage**
1. Measure the concentricity of the spindle using cylinder area.
2. When using a flat surface, adjustment of the insert position can be verified.
3. Confirm and adjust the absolute dimension in the X direction.
4. Measure the bending of the spindle using flange surface area.
5. Can be used with tool presetter.


■ **Note**
- ATC repeatability can be observed.
- Flatness of square test bar for the datum A is within ±0.01mm.

Universal Facing Boring Head

Universal Boring Head allows any applications just using this holder.



Automatic feeding using the machine spindle rotation.



Max. Boring diameter : ϕ920

High accuracy and Long life

Hand scraping surface leads to higher accuracy and longer life.





Specification

We guarantee a slide traverse accuracy of 5μm squareness at 50L, and we provide thorough overhaul and repair after-service.

TYPE	Max. Boring diameter	Max. slide movement	Automatic feed speed	Fine adjustment (one graduation)	Fast return screw	Max. rotation min⁻¹	Kg
MU	ϕ260	48	0.05 / Rotation	0.005 Vernier scale 0.001	—	600	2.1
MU-S4	ϕ400	52	0.02 ≀ 0.24 / Rotation 12 speeds	0.005	3.0 / Rotation	400	7
MU-S5	ϕ620	112					8.7
MU-S6H	ϕ800	140				250	21
MU-S6	ϕ920	210					23.3


Parts name





Combination of shank and head

Shank




※Please inform us when the cotter slot is needed.
(please inform us the machine brand and model).

CODE	Fig.	L	g
BT40 -MU	1	49	—
H 40 -MU	2	34	
NT40U-MU	3	15	
MT3 -MU(Tang type)	4	18	
MT4 -MU(Tang type)		19.5	
MT3 -MU(Screw type)	5	18	M12
MT4 -MU(Screw type)		19.5	M16
S32 -MU-20	6	20	—
S42 -MU-20			

CODE	Fig.	L	g
BT50 -MU-S4/S5	1	73.5	—
H 50 -MU-S4/S5	2	44.5	
NT40U-MU-S4/S5	3	17.1	
NT50U-MU-S4/S5		18.7	
MT4 -MU-S4/S5(Tang type)	4	28	
MT5 -MU-S4/S5(Tang type)			
MT6 -MU-S4/S5(Tang type)		29.5	
MT4 -MU-S4/S5 (Screw type)	5	27	M16


CODE	Fig.	L
BT50 -MU-S6H/S6	1	77
NT50U-MU-S6H/S6	2	28.2
MT6 -MU-S6H/S6(Tang type)	3	35

Mounting flange



CODE
Mounting flange

Boring head




Set content

Accessories \ Boring head (set)	MU	MU-S4	MU-S5	MU-S6H	MU-S6
Boring head	MU-H	MU-S4-H	MU-S5-H	MU-S6H-H	MU-S6-H
Boring bar	Diameter×length / Effective length / Q'ty	Diameter×length / Effective length / Q'ty	Diameter×length / Effective length / Q'ty	Diameter×length / Effective length / Q'ty	Diameter×length / Effective length / Q'ty
	18× 60 / 30 / 1	22× 85 / 45 / 1	22× 85 / 45 / 1	30×120 / 70 / 1	30×120 / 70 / 1
	18× 90 / 60 / 1	22×125 / 85 / 1	22×125 / 85 / 1	30×200 / 150 / 1	30×200 / 150 / 1
	18×120 / 90 / 1	22×165 / 125 / 1	22×165 / 125 / 1	30×260 / 210 / 1	30×260 / 210 / 1
Boring bar holder	Diameter×Shank length / Q'ty	Diameter×Shank length / Q'ty	Diameter×Shank length / Q'ty	Diameter×Shank length / Q'ty	Diameter×Shank length / Q'ty
	18× 82 / 1	22× 98 / 3	22× 98 / 2	30×120 / 2	30×120 / 2
	18×120 / 1	22×180 / 1	22×130 / 1	30×220 / 1	30×220 / 1
	—	—	22×229 / 1	30×360 / 1	30×360 / 1
Adjustment collar for boring bar holder	—	Inner diameter×Thickness / Q'ty	Inner diameter×Thickness / Q'ty	Inner diameter×Thickness / Q'ty	Inner diameter×Thickness / Q'ty
		22×10 / 1	22×10 / 1	30×10 / 1	30×10 / 1
		22×20 / 1	22×20 / 1	30×20 / 1	30×20 / 1
		22×60 / 1	22×45 / 1	30×40 / 1	30×40 / 1
		—	22×60 / 1	30×70 / 1	30×70 / 1
		—	—	30×80 / 1	30×80 / 1
Draw bolt for boring bar holder	—	Diameter×length / Q'ty	Diameter×length / Q'ty	Diameter×length / Q'ty	Diameter×length / Q'ty
		M12×40 / 1	M12×89 / 1	M16×80 / 1	M16×120 / 1
Clamping sleeve	Outer dia.× Inner dia. / Q'ty	Outer dia.× Inner dia. / Q'ty	Outer dia.× Inner dia. / Q'ty	Outer dia.× Inner dia. / Q'ty	Outer dia.× Inner dia. / Q'ty
	18× 8 / 1	22× 8 / 1	22× 8 / 1	22×12 / 1	22×12 / 1
	18×10 / 1	22×10 / 1	22×10 / 1	22×14 / 1	22×14 / 1
	18×12 / 1	22×12 / 1	22×12 / 1	22×18 / 1	22×18 / 1
	18×14 / 1	22×14 / 1	22×14 / 1	30×22-A / 1	30×22-A / 1
	—	22×18 / 1	22×18 / 1	30×22-B / 1	30×22-B / 1
Insert Material	□ × length / Q'ty	□ × length / Q'ty	□ × length / Q'ty	□ × length / Q'ty	□ × length / Q'ty
HSS	□ 6×30L-H / 3	□ 6×40L-H / 3	□ 6×40L-H / 3	□ 10×60L-H / 3	□10×60L-H / 3
Carbide	□ 6×30L-C / 1	□ 6×30L-C / 1	□ 6×30L-C / 1	□ 10×60L-C / 1	□10×60L-C / 1
Other accessories	●Stop rod ●Spanner ●Knocking rod ●L wrench	●Stop rod ●T handle wrench ●Connection for wrench ●L wrench ●Spanner	●Stop rod ●T handle wrench ●Connection for wrench ●L wrench ●Spanner	●Stop rod ●T handle wrench ●Connection for wrench ●Auxiliary bar ●L wrench ●Spanner	●Stop rod ●T handle wrench ●Connection for wrench ●Auxiliary bar ●L wrench ●Spanner

■Note
●We can provide only the head without accessories.

The fixture creates the new machining process.

▷ A highly rigid work-clamping fixture developed for both 5-axis machining centers and multi-surface machining with 3-axis machining centers (with a rotary table)





29th Award

Small- and Medium-size Enterprises Award for Excellence in New Innovative Technologies and Products

The Resona Foundation for Small and Medium Enterprise Promotion and The Daily Industrial News

5-axis machine

Clamping force







Automated robotic work-piece changing system


3-axis + rotary table

Multi-surface machining


Process integration on a 3-axis machining center with a rotary table and 5-axis machining center

















Clamping force

HSK (2-face clamping interface) and dovetail clamping






Maximum cutting force




Avoids interference

The fixture(work-holders and heads) design has much smaller than the work-piece.



- The fixture has less interference with a tool holder and a cutting tool and it endures large machining force in a different direction.




Quick change

Clamping 5-sec. Unclamping 5-sec.




- Easy operation – just mount the work holder on the head and tighten with a wrench.




Off-line set-up

Minimizing machine downtime.


- You can start machining the next work-piece quickly when it is mounted in a work holder in advance.
- The machine runs continuously, so you can maximize the machine utilization ratio.






Repeatability

No alignment by experienced workers required.






L=3×D	D	L
A40	40	120
A63	63	190
A100	100	300

If necessary, please off-set the rotational direction using a touch probe.

BLUM high-accuracy touch probe





Supports various work-piece shapes



HEAD

The Manual Clamping Head (Manual exchange)





CODE	Interface	L	ϕD1	L1	G	P.C.D.	Clamping force(kN)	Kg
F100H21-A40 - 50	HSK-A40	50	100	25	M 6×30	55～ 85	10	1.7
F125H34-A63 - 70	HSK-A63	70	125	30	M 8×35	80～100	20	3.8
F200H53-A100-110	HSK-A100	110	200	50	M12×50	125～160	30	14


■**Option**
- Mounting plate

■**Std access.**
- T-handle wrench ● Mounting bolt × 4pcs.

■**Note**
- A manual clamping hole on the work holder is required for mounting.

Please use a mounting plate if the fixing hole of the head doesn't match with a T-groove on the machine table. Also, we can make a custom-designed mounting plate for you if necessary.

CODE	Interface	T	ϕD	ϕH	G1	G2	G3	P.C.D	Kg
F160H32-A40	HSK-A40	20	160	32	M 5×20	M 6×20	M 6	80～125	2.6
F200H32-A40		25	200		M 8×25	M10×25		100～160	5
F160H50-A63	HSK-A63	20	160	50	M 5×20	M 6×20	M 6	80～125	2.4
F200H50-A63		25	200		M 8×25	M10×25		100～160	4.7
F250H50-A63		30	250	50	M10×30	M12×30	M12	140～200	9.4
F250H80-A100	HSK-A100	30	250	80	M10×30	M12×30	M12	140～200	8.7






Automatic Clamping Head P.81

WORK HOLDER

Dovetail clamping work holder



A63-DOC25-65




CODE	L	L1	ϕC	W	H1	G	SW	Kg
A40 -DOC 17.5-55	55	25	30	17.5	2	M 5	4	0.4
-DOC 25 -55		28	40	25	3	M 6	5	0.6
-DOC 35 -55		25	50	35				0.7
-DOC 50 -60	60	30	70	50	5	M 8	6	1.2
A63 -DOC 25 -65	65	27	40	25	3	M 6	5	1.2
-DOC 35 -65			50	35				1.3
-DOC 50 -70	70	30	70	50	5	M 8	6	1.8
-DOC 70 -75	75	35	100	70		M10	8	3
A100-DOC 35 -70	70	27	50	35	3	M 6	5	3.3
-DOC 50 -75	75	32	70	50	5	M 8	6	3.8
-DOC 70 -75		35	100	70		M10	8	5
-DOC100 -85	85	40	140	100	10	M12	10	7.7


Dovetail grooving a work-piece

Dovetail grooving of the work-piece clamping area using an angular cutter is required prior to machining.
After machining, cut off the dovetail of the work-piece.

Angular cutter
For more information, please contact us.

Details of dovetail dimensions





Holder type	W	H	P	SW	SD
DOC 17.5	17.5	2.5	2.5	4	2
DOC 25	25	3.5		6	2.5
DOC 35	35		5.5	8	
DOC 50	50	5.5	9	10	4
DOC 70	70		18	12	
DOC100	100	10.5	26	15	

Flange clamping work holder



A63-FP85-50




Fig. 1




Fig. 2






Fig. 3



3 Ways to Mount Work-pieces

① Center bolt
② Flange bolt from the head
③ Flange bolt from the work-piece



CODE	Fig.	L	φD	φD1	φD2	φD3	φd	h1	h2	T1	T2	T3	φd2	φd3	G1	G2	Kg
A40 -FP 40-35	3	35	40	32	—	—	25 +0.053 +0.020	12	4	M4× 6	—	—	—	—	M 6×15	M4× 8	0.3
-FP 63-40	2	40	63		50						M5		5.5		M 6×20		0.5
A63 -FP 63-45	3	45	63	50	—	—	40 +0.064 +0.025	13	5	M5× 8	—	—	—	—	M10×20	M6×10	0.9
-FP 85-50	2	50	85		73						M6		6.6		M10×25		1.2
-FP110-55	1	55	110			95					M6×9	M 8		9	M10×30		1.7
A100-FP100-55	3	55	100	85	—	—	70 +0.076 +0.030	17	7	M8×12	—	—	—	—	M12×25	M8×16	3.0
-FP130-65	2	65	130		115						M8		9		M12×35		4.2
-FP160-70	1	70	160			140					M8×12	M10		11	M12×40		5.3


■**Std access.**
- Center bolt (G1)×1pc. ● Set screw (G2)×6pcs.
- M6 special small-head bolt (the head diameter size is the same as the M5 bolt)×6pcs. (A63FP-85-50 / A63-FP110-55)
※Regular M6 cap screw doesn't fit.

■**Option**
- Positioner boss ● Adapter

■**Note**
- Use the G1 set screw when you use the center bolt to clamp the work-piece. When you need whirl-stop machining of a work-piece, make a flat surface on the work-piece and clamp it using a set screw (G2).


Positioner boss (Flange clamping)

Use it when you need centering.



CODE	Holder type	φD4	φD5	h	Kg
IR15-A40 FP	HSK-A40	15 0 -0.027	25	15	0.05
IR25-A63 FP	HSK-A63	25 0 -0.033	40	16	0.1
IR40-A100FP	HSK-A100	40 0 -0.039	70	20	0.5

■**Note**
- When you do not want the work-piece to rotate, make a flat surface on the O.D. (B1) of the boss, and attach it using a set screw (G2).



IR25-A63FP

Please use an adapter for small size work-pieces.

Minimizing clamping area for a small-size work-pieces reduces the interference area.



RS-A63-A40




Fig. 1





Fig. 2



CODE	Work holder	Fig.	φD	φD1	φd	H1	H2	H	T1	G1	G2	G3	Kg
RS-A63 -A40	**A63 -FP 63-45**	1	40 +0.064 +0.025	32	25	12	4	50	M4×6	M 6×20	M4× 8	M5×16	0.5
	-FP 85-50												
	-FP110-55												
RS-A100-A40	**A100-FP100-55**	2	40 +0.053 +0.020	32	25	12	4	60	M4×6	M 6×20	M4× 8	M8×25	1.5
	-FP130-65												
	-FP160-70												
RS-A100-A63	**A100-FP100-55**	1	63 +0.053 +0.020	50	40	13	5	55	M5×8	M10×20	M6×10	M8×25	1.7
	-FP130-65												
	-FP160-70												

■**Std access.**
- Center bolt (G1)× 1pc. ● Set screw (G2)× 3pcs.
- Fixing bolt (G3)× 3pcs.


■**Note**
- Attach the work-piece with the center bolt (G1). When you do not want the work-piece to rotate, secure the chamfering surface using a set screw.

Dovetail Vise clamping work holder



A63-DOV90


Fig. 1





A63-DOV110I

Fig. 2



CODE	Fig.	□S	Number of grooves	B	W	G (Depth)	L	L1	Kg
A63 -DOV 90	1	—	3	90	12～ 73	20-M4(6)	85	35	3.8
110I	2	110	—	—	36～ 80	24-M8(10)	90		5.7
A100-DOV140	1	—	5	140	12～ 73	30-M4(6)	100	35	7.7
140I	2	140	—	—	36～110	52-M8(10)			9.9

■**Std access.**
- 8mm hexagonal wrench

Angular cutter
For more information, please contact MST.


■**Note**
- **Dovetail grooving of the work-piece clamping area using an angular cutter is required prior to machining. After machining, cut off the dovetail of the work-piece.**
- Work-piece clamping jaws move individually.
- Please use the screw hole on the top face as necessary.

Side screw clamping work holder



A63-SCS10-55


Fig. 1






A63-SCD30-70

Fig. 2





■Std access.
- Large screw(G1)×2pcs.


CODE	Fig.	□W	W1	W2	B	L	L1	φC	H	H1	H2	G1 (Bolt)	G2	G3	Kg
A40 -SCS10-40	1	5 ~ 10	13	18.6	30	40	11	39	4.5	—	—	M 6×10	—	M 6	0.5
-SCD20-55	2	15 ~ 20	—	—	—	55	30	49	25	11	—	M 8×16	M4	M10	0.5
A63 -SCS10-55	1	5 ~ 10	20	23.5	50	55	21	62	7.5	17	—	M10×15	M5	M10	1.1
-SCS20-55		15 ~ 20	25	28.5											
-SCD20-65	2	15 ~ 20	—	—	—	65	30	49	25	11	—	M 8×16	M4	M10	1.2
-SCD25-70		20 ~ 25				70	35	56	30	8	20				1.3
-SCD30-70		25 ~ 30					44	62	35	9	24	M10×20	M5		1.4
-SCD40-85		35 ~ 40				85	52	76	45	12	30	M12×20	M6		1.9
A100 -SCS20-70	1	12 ~ 20	29.5	34	80	70	26	99	9	20	—	M12×20	M5	M12	3.6
-SCS30-70		22 ~ 30	34.5	39											
-SCD20-70	2	15 ~ 20	—	—	—	70	30	49	25	11	—	M 8×16	M4	M10	3
-SCD25-75		20 ~ 25				75	35	56	30	8	20				3.4
-SCD30-80		25 ~ 30				80		62	35	9	24	M10×20	M5		3.5
-SCD40-90		35 ~ 40				90	45	76	45	12	30	M12×20	M6		3.9

Direct-mounting (Direct-mounting type on the machine table)

Dovetail clamping type



F140S80-DOC50-55



Angular cutter
For more information, please contact MST.

■Option
- Mounting plate

■Std access.
- Mounting bolt×4pcs. (DOC100)

■Note
- Dovetail grooving of the work-piece clamping area using an angular cutter is required prior to machining. After machining, cut off the dovetail of the work-piece.

CODE	H	H1	H2	φC	W	Kg
F140S80-DOC17.5-60	60	45	2	30	17.5	2.5
-DOC25 -60			3	40	25	2.6
-DOC35 -55	55	40		50	35	2.8

CODE	H	H1	H2	φC	W	Kg
F140S80-DOC 50-55	55	40	5	70	50	3.4
-DOC 70-55				100	70	4.7
-DOC100-55			10	140	100	5.5

Flange clamping type



F140S80-FP85-50




Fig. 1





Fig. 2




CODE	Fig.	L	L1	H1	φD	φD1	T1	φD2	T2	φd2	φD3	T3	φd3	φd	G2	Kg
F140S80-FP 63-50	2	50	35	12	63	32	M4× 6	50	M5 thru	5.5 thru	—	—	—	$25^{+0.053}_{+0.020}$	M4	2.6
-FP 85-50				13	85	50	M5× 8	73	M6 thru	6.6 thru				$40^{+0.064}_{+0.025}$	M6	3.1
-FP110-70	1	70	55		110				M6×9		95	M8 thru	9 thru			3.7
-FP130-75	2	75	60	17	130	85	M8×12	115	M8 thru	9 thru	—	—	—	$70^{+0.076}_{+0.030}$	M8	5.5

■Option
- Mounting plate ●Positioner boss→P.79 ●Adapter→P.79

The mounting plate is required.
Also, we can make a custom design mounting plate.


CODE	Kg
F200H80-MP140-25	4.3


■Std access. ●Mounting bolt×4pcs.



The Automatic Clamping Head (Automatic exchange)


The hydraulic clamping design allows you to interchange work-pieces automatically, and makes it possible for you to combine your machining centers with robots to create a fully-automated system.





CODE	Interface	L	φD1	L1	Clamping force (kN)	Max. loading weight (kg)	Kg
F70S45 -A40 - 64	HSK-A40	64	70	35	6	50	1.1
F100S65 -A63 - 89	HSK-A63	89	100	50	24	140	3.1
F140S100-A100-139	HSK-A100	139	140	80	55	640	9.7


■Note
- Hydraulic pressure : 3.5MPa



The mounting plate is required.


- The mounting plate is an adapter for installation on the machine table and for connecting the hydraulic and pneumatic lines.
- Please provide us with a detailed drawing of your machine table and the plumbing drawing of your hydraulic and pneumatic lines. We can design and produce an exclusive mounting block, so please contact us for more information.





Fully-automated system

We can provide the following items to automate your system:
- **Control unit** - **Work-piece shelf** - **Robot finger**



Goo Checker

Set up the original point on the Z axis / measuring tool for reference position

Easy and accurate Z-axis origin setting!


▷ It is easy to accurately set the Z-axis origin of the machining center, the reference surface of work-piece, and the jig fixture.

ZPM




Available for using 5-axis machine.

ZPB




Measuring steps are easy.

Accurate measuring of the distance from the Z-axis origin to the reference surface of the work-piece and jig fixture is easy.




Sharable Z-axis origin for several machining centers

After measuring the distance from the Z-axis origin to the table surface of each machining center and correcting any variations, multiple machining centers can share the tool holders and programming.




Flatness check

Precise measurement for flatness.



Step measurement

Measurement for steps on the work-piece.



Goo Checker ZPM type (ZPM)

▷ **Thanks to its compact design, interference is reduced , making it the optimum holder for compact machining centers.**



CODE	Fig.	L	L1	Kg
BT30-ZPM-130	1	130	100	1.0
-165		165	135	1.2
BT40-ZPM-150	2	150	120	1.3
-210		210	180	1.5
BT50-ZPM-180	2	180	150	2.9
-240		240	210	4.1
A63 -ZPM-150	3	150	120	1.2
-210		210	180	1.5
A100-ZPM-180	3	180	150	2.5
-240		240	210	3.8
E32 -ZPM-120	3	120	90	0.7
-165		165	135	1.0
E40 -ZPM-120	3	120	90	0.8
-180		180	150	1.1
E50 -ZPM-150	3	150	120	1.0
-195		195	165	1.3
F63 -ZPM-150	3	150	120	1.1
-210		210	180	1.3
DN40-ZPM-150	2	150	120	1.3
DN50-ZPM-180	2	180	150	2.9
CT40-ZPM-150	2	150	120	1.3
CT50-ZPM-240	2	240	210	4.1

■**Option**
- Retention knob (BT/DIN/CAT.) → P.64

■**Std. Access.**
- Master block
- Indicator, 1/ 1000 reading

■**Caution**
- A.T.C is not available. (except for BT30)

Easy confirmation of actual value (self-check function)

1. Attach the master block to the holder, and tighten the screw until it stops.
2. Adjust the dial gauge to "0".




Fig. 1




Fig. 2







Fig. 3




Goo Checker ZPB type (ZPB)

▷ **High reliability due to its machined solid structure.**






Usage example for test indicator



Actual measurement



CODE	Kg
BT40-ZPB-200	3.3
BT50-ZPB-200	5.2


■**Option**
- Retention knob → P.64

■**Std. Access.**
- Indicator, 1/ 1000 reading
- Test Indicator, 2/ 1000 reading
- Centering arm
- Master cap
- Wooden box

Centering bar


To identify workpiece datum position

CODE
ST6-CEB102



Usage


①Rotate a spindle in low-speed rotation (450~600min-1)



②Contact the stylus carefully with a work-piece by micro feeding until it doesn't have a swing.



③You can find the alignment between the machine spindle center and the work-piece edge face after the stylus moves another 1mm(the radius of dia. 2mm stylus).



Measuring instrument tool holder (HSK-E25)

Use when centering a workpiece.
The spring collet (C10-6-P) and the centering bar (ST6-CEB102) are required and sold separately. Tighten nuts by hand.



CODE
E25-CEH10-37

■**Option**
- Centering bar
- Spring collet(C10-6-P)→P.38


■**Caution**
- Not usable for machining.

MAINTENANCE TOOL


■ TOOL CLINIC

Our engineers are here to improve your productivity by demonstrating the correct usage and maintenance of tool holders.









P. 114

TOOL SET UP STATION

Work table
6S DESK **6SD**




P. 86

Tool washing machine
CLEAN BOX **CBX**



P. 88

For machine spindle maintenance
TEST BAR CHECKMATE **CMA CMB**




P. 90

TOOL CAP **TCA TCB TCC**




P. 91

TOOL SET UP STAND **Petit-Ball MY CUBE HF series**




P. 94

Collet stand
PALETTE **PA**



P. 96

ENDMILL HOUSE **EMO**



P. 97

TOOL HOLDER STORING CABINET **HBX**




P. 98

Ensures safe tool settings ! Improves the work environment in the factory !

CODE
6SD-01

- Helps in the rapid implementation of the five S's in your factory.
- Compact and space saving.
- Do-it-yourself style allows you to do the assembly.



※This image includes the options.
Tool is not included.


White board and Punched board

Useful as a bulletin board or message board, and for attaching drawings.
Freely mounting position on the left or right side.



Shelf Board

Shelf is deep enough for a laptop computer, and the shelf can be attached at whatever height you desire.



Two-position angle adjustment



Hook base panel



Arbitrary attachment and recombination



Effective utilization of a rear space

Tool insert stand (Option)

Insert and store frequently used hand tools, stationery, etc.




Tool insert stand 5
Movable model (5 pockets)



Tool insert stand 16
Fixed model (16 pockets)

Dust Shooter (Option)

Easy trash separation.



Container box



Storage



Can be removed and carried.



Organizing



The see-through box allows easy storage and organizing.

Optional dividers allow you to easily organize and systematize items.

Upper lighting

Safety light cover.

Lighting switch and socket

Upper lighting (32W) and under shelf lighting (20W) (max. capacity 1,500W)



Air gun

Can be mounted on either the right or left.


Lower lighting

Brightly lit, safe work space



Safety stopper


Prevents dropping of cutting tools and tool holders.



Tabletop

The tool setup stand (sold separately) can be installed anywhere using the tabletop holes. No need to put your own holes in the tabletop.





Tool set up stand

P.94




MY CUBE



Petit Ball

Dimensions



Uniformity with stand load 100kg

Std. Access.

CODE	Description	Q'ty
6SD-FBP	Hook base panel	12pcs.
-FS	Short hook	3pcs.
-FL	Long hook	2pcs.
-UFS	U-type short hook	3pcs.
-UFL	U-type long hook	1pc.
-FSP	Hook for spanner	1pc.
-FDR	Hook for driver	1pc.
CN -103	Container box	3pcs.
-150		6pcs.
6SD-AIR	Air gun set	1set

Description	Q'ty
Shelf Board	1pc.
Upper lighting / Lower lighting ※Select 50Hz or 60Hz	1ea.
Power code set (Socket / Lighting / switch / Power code)	1set
White board. Marker pen for whiteboard. Whiteboard eraser. Magnet pocket. Punched board. Name seal set. Magnets(3pcs.). Memo book.	1set

■Caution
- Assembly by buyer.
- Customers pay the shipping cost.
- 100V electric power supply (transformer is required)

Option

Side table

CODE
6SD-STB

Uniformity with stand load : 40kg



Side Table for the 6S DESK

■Std. Access.
- Container box (CN-103) (1pc.)
- Container box (CN-150) (2pcs.)
- Lid for Container Box (3pcs.)

Dust Shooter

CODE
6SD-DST

Comes with two kinds of sign seals.

※Trash cans are not provided. Please prepare it by yourself.






Tool insert stand 5

CODE	Attachment q'ty
6SD-IS5	5pcs.


5-pocket movable model



Tool insert stand 16

CODE	Attachment q'ty
6SD-IS16	16pcs.


16-pocket fixed model



Consumables / Replacement parts

Container box

CODE	h	Capacity	Q'ty
CN-103-3	103 (88)	8ℓ	3pcs.
-150-3	150 (135)	12ℓ	



※( ):Inside dimension

Lid for container box

CODE	Q'ty
CN-FT-3	3pcs.




※Lockable

Dividers for storage cabinet


CODE	Required box	Q'ty
CN-S 84-3	CN-103	9 pcs. (for 6 rooms)
-S135-3	-150	(Container box 3 pcs. / set)





Hook base panel

CODE	Q'ty
6SD-FBP	2pcs.



Air gun set

CODE
6SD-AIR



Hook


Short hook

CODE	Q'ty
6SD-FS	5pcs.




U-type short hook

CODE	Q'ty
6SD-UFS	5pcs.




Hook for spanner

CODE	Q'ty
6SD-FSP	1pc.




Long hook

CODE	Q'ty
6SD-FL	5pcs.




U-type long hook

CODE	Q'ty
6SD-UFL	5pcs.



Hook for driver

CODE	Q'ty
6SD-FDR	1pc.



TOOL SET UP STATION


CLEAN BOX

Tool washing machine

CODE
CBX-01

Wash the tooling holders, collets, nuts, cutting tools, and small work-pieces thoroughly to maintain their accuracy!

- Wash tool holders, cutting tools and jig fixtures.
- No plumbing required.
- Safe cleaning system using water.
- Built-in water heater improves washing capability.



※This image includes the options.

Compact built-in sink





Automatic washing space

Shoots cleaning fluid from 18 location nozzles.




Hand washing space

Heavy dirt can be washed off using the hand nozzle brush and hot water (40°C / 104°F)



Built-in sink with an overflow drain allows pre-soaked washing.



Top cover

Top cover of washing unit can be opened and closed with one hand.

Comes with an automatic shutoff function for the washing cycle.

Automatic washing stops automatically when the top cover is lifted during operation.



Washing Unit

18 nozzles shoot hot water from every angle to wash off all the dirt.



Timer operating mode

Operation can be stopped automatically using the clock timer. (The time can be set arbitrarily, up to 12 min.)



Tank

The use of heated cleaning fluid (40°C) increases the cleaning power and makes cleaning easy even in the winter.



65 liter tank.

Tank can be removed for washing.



Comes with built-in heater (3kW) standard.

For more information!

Outer sink cover

Prevents splashing of the washing cleaner.

Hand nozzle

Easy to attach and detach.



Attach



Remove

Filter

Can be changed easily when it becomes dirty.



Main filter




Sub-filter

⚠ Be sure to use water-soluble cleaning fluid.


The sink, washing unit and tank are made of stainless steel, resulting in easy maintenance and less staining.

Dimensions



100kg

Maximum load 165kg (including washing fluid)



Specification

Material	SU304 (Sink、Tank、Cleaning unit) SS400 (Base frame)
Tank	Approx. 65L (Level gauge with thermometer is standard accessory.)
Pump	0.3～0.51kW (50/60Hz) (Produced by Grundfos)
Heater	3kW (with temperature control)
Weight	Approx. 100kg (165kg, including cleaning fluid)
Voltage	3-phase 200V (Rated 15A)

Std. Access.

CODE	Description	Q'ty
CBX-HNZ	Hand nozzle	1pc.
-MFIL	Main filter	2pcs.
-SFIL	Sub-filter	2pcs.
-TRP	Drain trap	1pc.
-GSTP	Rubber drain plug	1pc.
-WBSK	Washing basket	1pc.
-WTBL	Washing table	1pc.
Sink outer cover		1set
Hook		2pcs.
Bamboo brush		1pc.
Primary power code (plug attached 15m)		1pc.

■**Caution**

- ●Be sure to use water-soluble cleaning fluid.
- ●Customers pay the shipping cost.
- ●200V electric power supply (transformer is required)

Option

Draining basket


CODE
CBX-SBX

Uniformity with stand load 40kg

■**Std. Access.**

●Triple hook





※( )Inside dimension

Used for draining, air blowing, rust-proofing, etc.
Can be attached to either the right or left side of the unit.

Consumables / Replacement parts

Washing basket

CODE
CBX-WBSK

Collet and small parts can be washed.







Washing table

CODE
CBX-WTBL

Used in a sink as an auxiliary table when washing by hand.





Main filter

CODE	Q'ty
CBX-MFIL	5pcs.



Sub-filter

CODE	Q'ty
CBX-SFIL	3pcs.



Hand nozzle

CODE
CBX-HNZ



Rubber drain plug

CODE
CBX-GSTP



Drain trap

CODE
CBX-TRP



Cleaning fluid

CODE
CBX-EKI




- ●Capacity 18ℓ
- ●Product name: "Clean Super 285" weak alkaline cleaner

TEST BAR CHECKMATE


For machine spindle maintenance

The maintaining machine spindle run-out accuracy allows superior machining quality. Maximizes tool holder performance!

Periodically checking the run-out accuracy will result in superior machining.




- Light-weight (20% lighter), hollow design makes it easy to use.
- The actual measurement values are marked on the body.
  Length | Diameter | Runout accuracy | Phase of run-out
- Ideal for setting Z axis datum.
- Reasonable price.




You can recognize the exact run-out accuracy and the highest run-out of the spindle.

You can check the spindle condition more precisely using the run-out value and position marked on the body.



It can be installed into the spindle in every phase.

There is no drive-key groove, so measurements can be made without worrying about the phase.




Handy CMA type

Allows you to check the dynamic accuracy thanks to optional balance adjustment.

The name ring and scale ring protect it from scratches and dents.

The taper area and straight area do not touch the table surface even if they are placed horizontally.



Full-fledged CMB type

Z-axis deflection and spindle travel accuracy can be measured.

	CODE	Fig.	φD	φD1	L	L1	L2	L3	Kg
BT / DIN / CAT.	NT30 -CMA20-125	1	20	32	125	45	65	15	0.7
	NT40 -CMA25-175	2	25	42	175	50	110		1.3
	NT50 -CMA30-225		30	53	225	65	145		3.5
	NT30 -CMB30-175	1	30	32	175	45	115	15	1.0
	NT40 -CMB40-325	2	40	42	325		265		2.8
	NT50 -CMB50-325		50	53		60	250		5.7
HSK-A / -E	HSK32 -CMA20-125	3	20	26	125	35	75	15	0.4
	HSK40 -CMA20-125			32		45	65		0.5
	HSK50 -CMA25-175		25	42	175	50	110		1.0
	HSK63 -CMA25-175								1.2
	HSK80 -CMA30-225		30	53	225	65	145		2.2
	HSK100-CMA30-225								3.0
	HSK125-CMA30-225								4.1
	HSK32 -CMB25-175	3	25	26	175	35	125	15	0.7
	HSK40 -CMB30-175		30	32		40	120		0.9
	HSK50 -CMB40-225		40	42	225	45	165		1.8
	HSK63 -CMB40-325				325		265		2.7
	HSK80 -CMB50-325		50	53		60	250		4.4
	HSK100-CMB50-325								5.2
	HSK125-CMB50-325								6.3
HSK-F	HSK63F-CMA25-175	3	25	42	175	50	110	15	1.2
	HSK80F-CMA30-225		30	53	225	65	145		2.3
	HSK63F-CMB40-325	3	40	42	325	45	265	15	2.7
	HSK80F-CMB50-325		50	53		60	250		4.5

Fig. 1




Fig. 2





Fig. 3



Exclusive retention knob

CODE	Shank
P-576	CAT.40
-575	CAT.50
-578	DIN40
-577	DIN50

■Option
- Coolant duct(HSK-A) ●Retention knob(BT)
- Exclusive retention knob(CAT. / DIN)
- Balance adjustment (only for CMA type) less than G2.5 /30000min^{-1}
  ※Please order by adding "BL" to the end of the code.
  (Ex. : HSK63-CMA25-175 **BL**)

■Std. Access.
- Accuracy inspection sheet

■Note
- NT type is available for BT/CAT. and DIN spindle by changing the retention knob.
- HSK type is available for both HSK-A and HSK-E spindles. ●HSK-F type is available only for HSK-F spindle.
- A special design retention knob is required for CAT./DIN spindle. A market standard retention knob for ANSI/DIN/ISO is not available. Contact us for the details.
- Use a market standard retention knob for the BT spindle.
- NT30 type can be installed into a spindle at 0°and 180°.

■Caution
- A.T.C is not available. (except for NT30)

The sub-zero treatment prevents secular change.

MST

TOOL CAP


See-through tool cover.
You can take care of your tools safely and simply.

- Prevent cutting tools from coming into contact with each other and being damaged or chipped.
- Prevent getting injured when taking the tool holder in and out or when carrying.
- Minimize grinding costs for reconditioning and lead to reduced operating costs.
- Applicable for various shapes or brands.

TCC type
Attached by deforming its cap.

TCB type
Attaches directly to the tip of the cutting tool.

TCA type
Attaches to the tip of a tool holder.



The tool is visible

The cutting tools can be stored with the caps on. By placing the cap on the tip of the tool holder, the cutter doesn't receive any stress, alleviating any worries over the cutters breaking.



Prevents chipping and damage to cutting tools

Storing cutters with caps will prevent them from hitting each other and being chipped. This will minimize grinding costs for reconditioning and lead to reduced operating costs.



ENDMILL HOUSE
P. 97



Will not slip off

Can be put on with one touch, and won't fall off when turned upside down.





Conventional

It can be used with every configuration and brand.






TCA type

Attaches to the tip of a tool holder.





Code system

TCA	2030 (Min.~MAX.)	—	50 (pc)
	D dimension		Q'ty

CODE	ϕD	ϕC	ϕd	H	h	h1	h2	Type
TCA2022	20～22	29	8	100	70	30	70	DTA7/DTB7
TCA2830	28～30	34	14	130	90	40	90	DTA12/DTB12/DTE7
TCA3436	34～36	41		135		45		CTA10/CTH10
TCA4043	40～43	47	20	152	105	47	105	DTE12
TCA4650	46～50	54		167	120		120	CTA20/CTH20


Note

10pcs. 50pcs. 100pcs.300pcs. 500pcs.
Please order by adding Q'ty to the end of the code.
Ex. TCA2022-10

Cap dispenser

Tool caps can be easily removed from the dispenser.

Dispenser exclusively for storing TCA-type tool caps.
Made of transparent acrylic resin, allowing you to confirm which caps are still in the dispenser.



Cap dispenser

Five models available for different sizes.

CODE	Type	Q'ty
CAP2022	TCA2022	31pcs.
CAP2830	TCA2830	20pcs.
CAP3436	TCA3436	
CAP4043	TCA4043	22pcs.
CAP4650	TCA4650	

Dedicated bracket


Five cap servers can be attached.
Attach the bracket to a wall using bolts.

CODE
SRV-01

TCB type

Attaches directly to the tip of the cutting tool.
Handles a broad range of sizes.





Code system

TCB	2042 (Min.~MAX.)	—	300 (pc)
	D dimension		Q'ty

CODE	ϕD	ϕC	H	h1	h2
TCB0820	8～20	33	82	52	30
TCB2042	20～42	54	102	62	40

Note

10pcs. 50pcs. 100pcs. 300pcs. 500pcs.
Please order by adding Q'ty to the end of the code.
Ex. TCB0820-10


■**Note**

●The bristles of the brush may become deformed during use. If such deformation occurs, remove the brush and immerse it in hot water (60°C to 80°C). This should restore the deformed bristles to their original state.

TCC type

Attached by deforming its cap.
Simple and reasonably priced.
For small size tool holders and cutting tools.





Code system

TCC	2228 (Min.~MAX.)	—	100 (pc)
	D dimension		Q'ty

CODE	φD	h1	H	Q'ty
TCD03-50	3	—	25	50 pcs.
TCD04-50	4	—	32	50 pcs.
TCC0607- 50	5.4～ 6.7	35	40	50 pcs.
-100				100 pcs.
-500				500 pcs.
TCC0709- 50	6.8～ 8.9	35	40	50 pcs.
-100				100 pcs.
-500				500 pcs.
TCC0911- 50	8.9～10.9	65	70	50 pcs.
-100				100 pcs.
-500				500 pcs.
TCC1113- 50	10.9～13.4	65	70	50 pcs.
-100				100 pcs.
-500				500 pcs.
TCC1418- 25	13.8～17.8	100	110	25 pcs.
- 50				50 pcs.
-250				250 pcs.
TCC1822- 25	17.8～22.4	100	110	25 pcs.
- 50				50 pcs.
-250				250 pcs.
TCC2228- 25	22.3～28	135	150	25 pcs.
- 50				50 pcs.
-250				250 pcs.
TCC2836- 10	28 ～36	130	150	10 pcs.
- 20				20 pcs.
- 50				50 pcs.
-200				200 pcs.
TCC3646- 10	36.2～47	165	190	10 pcs.
- 20				20 pcs.
- 50				50 pcs.
-200				200 pcs.
TCC4760- 10	46 ～60	160	190	10 pcs.
- 20				20 pcs.
- 50				50 pcs.
-200				200 pcs.

Variety set

CODE	Q'ty
TCC-F	2 pieces per cutting tool cover size for TCC0607 to 4760 (Total of 20 pieces / set)

Usage

1. Hold the mouth of the tool cap vertically, and then press it so that its oval shape becomes round.
2. Once the mouth of the tool cap becomes round, push it into the cutting tool or tool holder.



You can cut it to any desired length.





Tool set up stand

Tool tightening stand

The setup time can be shortened! Not only can you mount cutting tools simply and quickly without using other tools, but also clamping collets and retention knobs!

プチボール Petit Ball 40
BT40/DIN40/CAT.40



Freely set vertically or horizontally

マイキューブ MY CUBE 50
BT50/DIN50/CAT.50

マイキューブ MY CUBE 100
HSK-A100/T100



Vise clamping type
HF SERIES
BT30/BT40/BT50
HSK A40/A50/A63/A100
E32/E40/E50/F63
T40/T50/T63/T100


Affordable





Usable either vertically or horizontally (Petit Ball, MY CUBE)

The tool can be placed either vertically or horizontally, whatever angle is most convenient for you.



Nut tightening



Clamping DETa-1 Collet(DTB)




Retention knob tightening



Clamping SLIMLINE collet

Multi-purpose usage

By using adapters, various tool holder shank types, including straight arbor DTB holders, can be used.



Accuracy assured


The taper is the most crucial part for maintaining the accuracy of a tool holder. A special resin is applied to the taper contact area to prevent scratches on the tool holder.




Petit Ball

CODE	Shank type	Kg
Petit Ball40	BT40/DIN40/CAT.40	6.1

■Option
●Adapter
■Std. Access.
●Name plate
■Caution
●No mounting bolts are provided.
Use two M8 bolts for mounting.





Name plate

A specially finished name plate is provided, on which your company name is inscribed. Up to 12 characters (upper-case alphabetic characters, numeric characters, and/or hyphens).



Adapter (Petit Ball)



Adapter for pot

CODE	Shank type
AP40-T30V	BT30


Adapter for hanger


CODE	Shank type
AP40-T30H	BT30
-S25H	ST25T-DTB7
-S32H	ST32T-DTB7, 12

My Cube

CODE	Shank type	Kg
MY CUBE 50	BT50 / DIN50 / CAT.50	9.7
MY CUBE100	HSK-A100, T100	9.6

■Option
●Adapter
■Std. Access.
●Name plate
■Caution
●No mounting bolts are provided.
Use two M12 bolts for mounting.





Name plate

A specially finished name plate is provided, on which your company name is inscribed. Up to 12 characters (upper-case alphabetic characters, numeric characters, and/or hyphens).



Adapter (My Cube50)



Adapter for pot

CODE	Shank type
AP50-T30V	BT30
-T40V	BT40/DIN40/CAT.40
-A63V	HSK-A63, T63
-F63V	HSK-F63

Adapter for hanger

CODE	Shank type
AP50-T30H	BT30
-T40H	BT40
-A63H	HSK-A63, T63
-F63H	HSK-F63
-S25H	ST25T-DTB7
-S32H	ST32T-DTB7, 12

HF series

CODE	Fig.	Shank type	H	W	t	Kg
HF-BT30	1	BT30	77	70	30	0.8
-BT40		BT40	90	90	37	1.2
-BT50	2	BT50	—	—	—	2.2
HF-A40	1	HSK-A40, T40	72	60	30	0.8
-A50		-A50, T50	77	70	37	1.0
-A63		-A63, T63	87	90		1.2
-A100	2	-A100, T100	—	—	—	2.1
HF-E32	3	HSK-E32	98	64	—	1.0
-E40		-E40	100	70		1.1
-E50		-E50	106	80		1.3
-F63		-F63	120	90		1.6

Fig. 1




Fig. 2






Fig. 3



This pallet neatly houses collets.

- Uniquely designed by an industrial designer.
- Protects the collets from damage to maintain their accuracy.
- Both top side and back side are usable.
- Affixing labels allows easy storage by size.
- Has standard outer dimensions ensuring applicability to various types of drawers and shelves.
- Applicable regardless of manufacturer.







A stand for the SLIMLINE 2PIECE type collets is also available.



PA-R




Storage side of Spring collet (C10)




Storage side of Deta-1 collet (D7)

CODE	Q'ty
PA-R- 1	1pc.
- 5	5pcs.
-10	10pcs.

PA-B



Storage side of Spring collet (C20)




Storage side of Deta-1 collet (D12)

CODE	Q'ty
PA-B- 1	1pc.
- 5	5pcs.
-10	10pcs.

ENDMILL HOUSE

Cutter protection box エンドミルのおうち

Are you having trouble storing your cutting tools?



Cutting tool expenses increase due to cutting edge chipping.




The required cutting tool cannot be found easily.

Save cutting tool expenses and time with the optimum working environment!

- Cutting tool life is extended because the cutting edge is not dulled from striking other cutters.
- You can find the required cutting tool immediately.





Value set

This is a convenient value set that can be immediately used and handles tool shank diameters of 3 mm to 12 mm. (Stores 156 cutting tools)


CODE
EMO-SET-01

Stand

Cutter dia	Q'ty
ϕ 3	1pc.
ϕ 4	2pcs.
ϕ 6	3pcs.
ϕ 8	2pcs.
ϕ10	2pcs.
ϕ12	2pcs.

Base

Q'ty
1pc.



\+

TOOL CAP

Cutter dia	Q'ty
ϕ 3	50pcs.
ϕ 4	50pcs.
ϕ 6	50pcs.
ϕ 8	50pcs.
ϕ10	50pcs.
ϕ12	50pcs.



\+

TOOL CAP storage box


Q'ty
1pc.




ϕ3…13pcs. ϕ4…26pcs. ϕ6…39pcs.
ϕ8…26pcs. ϕ10…26pcs. ϕ12…26pcs.

Stand

Parts for storing and securing cutting tools. It is possible to identify the cutting tool size by color, and the cutting tool you need can be found at a glance. Use this stand inserting it into the base.






CODE	ϕd	W	max. Q'ty	Color	Q'ty
EMO-STD 3-2	3	15mm (1W)	13 pcs./cutting tools/stand	Black	2pcs.
-5					5pcs.
-STD 4-2	4			Brown	2pcs.
-5					5pcs.
-STD 6-2	6			Gray	2pcs.
-5					5pcs.
-STD 8-2	8			Yellow	2pcs.
-5					5pcs.
-STD10-2	10			Orange	2pcs.
-5					5pcs.
-STD12-2	12			Black	2pcs.
-5					5pcs.
-STD16-2	16	30mm (2W)	7 pcs./cutting tools/stand	Blue	2pcs.
-5					5pcs.
-STD20-2	20			Orange	2pcs.
-5					5pcs.
-STD25-2	25			Gray	2pcs.
-5					5pcs.

Base


Container for holding the stands.
Stands can be arranged by changing the combination of stands freely.

CODE	Q'ty
EMO-BAS-1	1pc.
-3	3pcs.

■ Note
- 12 rows for the stands of 3mm to 12mm diameter or 6 rows for the stands of 16mm to 25mm diameter.
- The left-right orientation of the stands can be set.



Example of stand arrangment




TOOL HOLDER STORING CABINET

Compact Storage Box with Anti-Rust Treatment for tool holders.




Orderly storing with name plate!




Freely arrangeable

Can be used with a variety of holders by changing the pins and combining as you wish.



Three types of container boxes.



Standard Set

CODE	max. Q'ty	Container box	Pin	Q'ty	Shank type
HBX-A40	24	CN-150	HBX-PNE40	18pcs.	HSK-A40
-A50	15	-245	-PNE50	15pcs.	-A50
-E25	40	-150	-PNE25	32pcs.	-E25
-E32			-PNE32		-E32
-E40	24		-PNE40	18pcs.	-E40
-E50	15	-245	-PNE50	15pcs.	-E50
-F63	10				-F63
-15T	40	-150	-PN15T	16pcs.	15T(BROTHER)
-20T			-PN20T		RS20/20T(SUGINO)

■**Contents of set**
●Base plate ●Container box ●Pin


■**Option**
●Rail ●Name plate
●Lid for container box ●Eyenut

■**Note**
●Knock-down type. A wrench (5mm) is required.

Base plate

A multi-hole base plate is employed. Supports a variety of holder specifications using pins that can be freely changed and relocated.


CODE
HBX-BP01



Container box


CODE	H		Shank type
	Outside diameter	Inside diameter	
CN-103	103	88	—
-150	150	135	E25, 32, 40/15T/20T
-245	245	230	A50, E50, F63

※( ) : Inside diameter



Pin

CODE	Q'ty	Size
HBX-PNE25	10 pcs.	φ13.5 × H20
-PNE32		φ16.5 × H25
-PNE40	5 pcs.	φ20.5 × H29
-PNE50		φ25.5 × H36
-PN15T		φ26.5 × H54
-PN20T		φ30.5 × H62




■**Std. Access.**
●Mounting bolt (M6)

Eyenut

CODE	Q'ty
HBX-ENM6	2pcs.

■**Std. Access.**
●Mounting bolt (M6)




Rail (for name plate)

CODE	Q'ty	L	Note
HBX-R210	6pcs.	210	Vertical type
-R330	4pcs.	330	Horizontal type

■**Std. Access.**
●Mounting bolt (M5)


Required for attaching name plate.




Name plate

CODE	Q'ty
HBX-NP01	40pcs.

Useful for organizing tools.
Attaches easily to the rail.





Freely cut to required overall length

Lid for container box

CODE
CN-FT




MIDDLE VISE

A work-piece fixture with high-accuracy positioning and short setup time.


MIDDLE VISE

- Ideal for small work-pieces.
- High flexibility in choosing installation place compact design.
- After the work-piece is clamped, horizontal and parallel adjustments are possible due to the independent fine adjustment functionality.
- Two sliders makes it easy use to use.




Compact design

This product does not use a table corner, allowing it to be installed in any place.Multiple pieces may be installed.



Height adjusting mechanism

The clearance between the zero level of the table and the level of the workpiece can be set to 0 or 1 mm.




Standard set

CODE
MDV-501

Description


1. A complete set of main body (Including 2 sliders and 1 jaw)
2. Allen wrench (1 each: 2.5, 4, and 6 mm)
3. 10 mm spanner (1pc.)
4. M8 mounting bolts and washers (25 ea.)
















Specification

This unit uses stainless steel that is highly resistant to corrosion and wear.

Maximum dimensions of work-piece	130×100
Maximum weight of work-piece	3kg
Weight of main body	5kg
Material	SUS420J2
Hardness	50HRC



Optional accessories


Name	Model No.		Dimensions	work-piece size
Extension Jaw For large work-pieces	**JAE-501**			
L Slider For small work-pieces	**SRL-501**			
V Slider For round work-pieces	**SRV-501**			
Sandwich Slider For small and thin work-pieces	**SRS-501**			
Clamp on Slider The work-piece can be clamped to the jaw using the clamper. The extension plate can also be used.	**SRC-501**			

Wire Cut Unit

A work-piece fixture with high-accuracy positioning and short setup time.

WIRE CUT UNIT

- A work-piece having a datum surface can be accurately attached by merely affixing it to the wire cut unit body.
- You can clamp a work-piece quickly.
- After the work-piece is clamped, horizontal and parallel adjustments are possible due to the independent fine adjustment functionality.



Wire Cut Unit set


WCU - A set





WCU - B set





WCU - C set






※The right side is the state where set contents are stored in the case.


Extension Plate (Optional accessories)

Case is not included.


PTE-001




PTE-002



Examples of use






Large work-piece - Clamp on



Square work-piece - Side Clamp



Small round work-piece – Side Clamp with the extension plate




Set Contents

Name	Model No.	A set	B set	C set	Extension plate (Option)	
		WCU-A	WCU-B	WCU-C	PTE-001	PTE-002
Base plate	—	1 pc.	1 pc.	1 pc.	—	—
Extension plate (Only plate)	PTE-001	1 pc.	1 pc.	2 pcs.	1 pc.	—
	-002	—	1 pc.	2 pcs.	—	1 pc.
Clamper	CLP-101	4 pcs.	6 pcs.	10 pcs.	2 pcs.	2 pcs.
	-102	4 pcs.	6 pcs.	10 pcs.	2 pcs.	2 pcs.
	-201	1 pc.	2 pcs.	3 pcs.	—	1 pc.
Grip	GRP-002	2 pcs.	2 pcs.	2 pcs.	—	—
Adjusting bolt	AJB-M6-L (L= 30, 50, 80)	1 ea.	2 ea.	3 ea.	—	1 ea.
Stud bolt	STB-M6-L (L= 40, 50, 70, 90)	1 ea.	2 ea.	3 ea.	—	1 ea.
Cap bolt M6 × L	—	L=16, 20, 25, 30, 35 4 ea. L=40, 50 2 ea.	L=16, 20, 25, 30, 35 6 ea. L=40, 50 4 ea.	L=16, 20, 25, 30, 35 10 ea. L=40, 50 6 ea.	L=16, 20, 25, 30, 35 2 ea.	L=16, 20, 25, 30, 35, 40, 50 2 ea.
Set screw (Kultopp) M6×30	—	1 ea.	2 ea.	3 ea.	—	1 pc.
Nut, Washer M6	—	2 ea.	4 ea.	6 ea.	—	2 ea.
Hexagonal wrench, spanner	—	1 set	1 set	1 set	—	—

Specification

This unit uses stainless steel that is highly resistant to corrosion and wear.

Max. work-piece dimensions	160mm(6.30")×160mm(6.30")
Max. work-piece weight	15kg(33lbs)
Main body weight	4.3kg(9.5lbs)
Material	SUS420J2(Stainless steel)
Hardness	50HRC
Datum surface squareness M ⊥ A•B / A ⊥ B	5μm(.0002")/100mm(3.94")



PARTS

Wrench · Spanner

Fig. 1




Fig. 2



Fig. 3




Fig. 4





Fig. 5




CODE	Fig.	L	R	B	L_1	Holder type
DW-2.5-110	5	110	—	2.5	—	DTB 3
F - 22	1	110	22	—	—	DTA 3
- 38		148.5	19			DTA 7
- 45		225	22.5			DTA12
FC- 32	1	120	16	—	—	CTH10(A40, E32, E40), HUD, HUA10, AHU10, HUT4
- 36		208	18			CTA10, CTH10
- 50		281	25			CTA20, CTH20
- 55		284	27.5			CTH25(A40)
- 62		312	31			CTA25, CTH25
- 74		364	37			CTA32, CTH32
- 90			45			CTA40
FF- 50	1	165	22.5	—	—	ST32B-FMA25.4
- 60		195	26			ST32B-FMA31.75, ST42B-FMA
FM- 72	1	204	36	—	—	ART32(BT40, A50M, A63, NT40, H50)
- 82		234	41			ART32(BT50, A100, NT50)
- 97		239	48.5			ART42(BT50, A100, NT50)
RC- 26	4	240	—	24	—	CTS10(E32)
TW- 4	2	77	—	4	—	DTB 7(E32)
- 5		153		5		DTB 7
- 6		173		6		DTB12
W -135	3	132.5	—	5	110	SLK12 (SLIMLINE 2PIECE TYPE)
-135 DR						DTB 7 (F63M), DTB12(E40, E50, F63M), DTE7, DTE12
-206		200		6	30	SLZ25
-308		300		8		SLZ32, SLZ42

Adjustable torque wrench



Spanner for torque wrench	Adjustable torque wrench	R	Holder type	Recommended tightening torque
F -38AW	AW-1	19	DTA 7	D7-1.5 : 20N·m D7-2.0～7.0 : 40N·m
-45AW		22.5	DTA12	D12(All sizes) : 70N·m
FC-36AW	AW-1	18	CTA10 / CTH10	C10-2.6～5.0 : 40N·m C10-5.2～5.8 : 50N·m C10-6～10 : 60N·m
-50AW	AW-2	25	CTA20 / CTH20	C20(All sizes) : 120N·m

Nozzle



CODE	L	G	W	ϕD	Holder type	Q'ty
NOZ-M4-12	6.3	M4	4.5	1.2	BT40-ART A63 -ART -SLK	12pcs.
-60						60pcs.
-M6-12	8.5	M6	7	1.8	BT50-ART A100-ART -SLZ	12pcs.
-60						60pcs.

■**Std. Access.**
- Wrench for attachment

■**Caution**
- Four nozzles are necessary for one tool holder.

Nut (For collet holder)



Fig. 1




Fig. 2






Fig. 3



CODE	Fig.	ϕC	H	Holder type
NUA-CTA10	1	36	18	CTA10, AHB10
-CTA20		50	25	CTA20, AHA20, AHU20
-CTA25		62	28.5	CTA25, AHA25
-CTA32		74	32	CTA32
-CTA40		90	36	CTA40
-CTH10	2	36	18	CTH10
-CTH20		50	25	CTH20
-CTH25		62	28.5	CTH25
-CTH25-55		55		CTH25 (A40)
-CTH32		74	32	CTH32
-CTH10-32		32	18	CTH10 (A40, E32, E40), AHU10
-CTS10	3	26	21	CTS10

Sukima nut (For collet holder)





CODE	ϕC	H	ϕd	ϕd1	S	Holder type
NUB-CTH10- 3.6	36	23	3	3.6	3.1	CTH10
- 4.5			4	4.5	3.3	
- 5.5			5	5.5	3.7	
- 6.4			6	6.4	3.9	
- 8.4			8	8.4	4.6	
-10.3			10	10.3	4.8	
-CTH20- 6.4	50	30	6	6.4	3.9	CTH20
- 8.4			8	8.4	4.6	
-10.3			10	10.3	4.8	
-12.3			12	12.3		
-16.2			16	16.2	5.1	
-20.2			20	20.2	5.7	
-CTH25-20.2	62	34.5				CTH25
-25.2			25	25.2	5.9	
-CTH32-25.2	74	38				CTH32
-32.1			32	32.1	6.0	

Adjust screw



Fig. 1





Fig. 2



Use this to adjust the cutter projection length.
※1 BT30 , SE30M, ST25T and ST32T are excluded.
※2 BT40-CTA25-75 is excluded.

CODE	Fig.	L	ϕD	ϕd	L1	J	K	G	Holder type
AJC-M14	1	22	10	-	8	1.5	3	M14×1.5	CTA10 ST25T-CTA20 SE30M -CTA20
-M24		27	20		13	5	4	M24×1.5	CTA20(※1) BT40-CTA25- 75 BT40-CTA32-105
-M28			25					M28×1.5	CTA25(※2)
-M18		24	15		8			M18×1.5	BT30-CTA20, ST32T-CTA20
-M18L	2	43	23						BT50-CTA32, CTA40 BT50-SLZ25, SLZ32, SLZ42
AJN-M18L	2	38	23	10	8	-	-	M18×1.5	BT40-ART32
-M18		63							BT50-ART32, ART42

Coolant duct

Coolant duct (Fixed)



Fig. 1




Fig. 2





Fig. 3



CODE	Fig.	ϕC	ϕD	L	G	W	Shank type
CD40 -01	1	8	4	29.5	M12×1	4	A40, T40
-03	3			35.5			A40-CTH10-75 A40-CTH25-95
-04				36.5			
CD50 -01	1	10	5	33	M16×1	5	A50, T50
-03	3			39			A50-CTH25-105
-04				59			
CD63 -01	1	12	6	36.5	M18×1	6	A63, T63
-02	2						A63-CTH10-75
-03	3			39.5		5	A63-CTH20-90
-04				60.5			A63-CTH25-105
CD100-01	1	16	8	44	M24×1.5	8	A100, T100
-02	2		10.3				A100-CTH25-135

■Note
- Comes as a standard feature with our holders. However, for the CD50-03 and the CD63-03, CD50-04 and CD63-04 come as options, respectively.

Coolant duct (Adjustable)

Fig. 1






Fig. 2



CODE	Fig.	ϕC	L	ϕD	G	Replaceable coolant duct
CD63 -01F	1	12	36.5	7	M18×1	CD 63-01
-03F	2		45.5	6.5		CD 63-03
CD100-01F	1	16	44	10	M24×1.5	CD100-01

■Note
- For some machines, the use of a coolant duct (Adjustable) is recommended. The existing coolant duct is replaced with an adjustable one at your request only when you have placed an order for the holder.
- If the replacement of the coolant duct is needed after the purchase, use the wrench CD63-01F-RNT.

Dummy duct



CODE	ϕC	L	G	W	Replaceable coolant duct
CD40 -A1	8	29.5	M12×1	4	CD 40-01
CD50 -A1	10	33	M16×1	5	CD 50-01
CD63 -A1	12	36.5	M18×1	6	CD 63-01
CD100-A1	16	44	M24×1.5	8	CD100-01

ANGLE HEAD HALF PARTS LIST

HFD7 / HFT4 (BT30/40/50, A63, DN40/50, CT40/50)

CODE (Master holder)	1 Shank	2 Orientation Ring	8 Washer for intermediate bearing B	9 Intermediate bearing	19 Head
BT30 -HFD7-122	BT30 -FSA-7S	ORR-30	-	-	FBA-7S
-HFT4-122					
-HFD7-182	BT30 -FSA-7L		FZ-7	6804ZZ	FBA-7L
-HFT4-182					
BT40 -HFD7-120	BT40 -FSA-7S	ORR-40	-	-	FBA-7S
-HFT4-120					
-HFD7-180	BT40 -FSA-7L		FZ-7	6804ZZ	FBA-7L
-HFT4-180					
BT50 -HFD7-195	BT50 -FSA-7L	ORR-40			
-HFT4-195					
-HFD7-255	BT50 -FSA-7XL				FBA-7XL
-HFT4-255					
A63 -HFD7-183	A63 -FSA-7L	ORR-40	FZ-7	6804ZZ	FBA-7L
-HFT4-183					
-HFD7-243	A63 -FSA-7XL				FBA-7XL
-HFT4-243					
DN40A-HFD7-135	DN40A-FSA-7S	ORR-40	-	-	FBA-7S
-HFT4-135					
-HFD7-195	DN40A-FSA-7L		FZ-7	6804ZZ	FBA-7L
-HFT4-195					
DN50A-HFD7-195	DN50A-FSA-7L				
-HFT4-195					
-HFD7-255	DN50A-FSA-7XL				FBA-7XL
-HFT4-255					
CT40 -HFD7-135	CT40 -FSA-7S	ORR-40	-	-	FBA-7S
-HFT4-135					
-HFD7-195	CT40 -FSA-7L		FZ-7	6804ZZ	FBA-7L
-HFT4-195					
CT50 -HFD7-195	CT50 -FSA-7L				
-HFT4-195					
-HFD7-255	CT50 -FSA-7XL				FBA-7XL
-HFT4-255					

■**Std. Access.**
- Fixing spanner(KS-23) ● Hexagonal wrench set(W-1550S)
- Single-ended wrench 13mm(SN-13)

※3, 9, 11, 14 and 22 are able to use standard commercial items.

The tools for assembly

Wrench (for shank)

To be used for tightening 11.

CODE
FC-32




Wrench (for head)

To be used for tightening 12 and 13.

CODE
TSH-HF7






1 Shank



2 Orientation ring



3 Angular bearing CODE 7005ADB



4 Housing CODE FHA-S



5 Dovetail nut CODE FDN-M6



6 Collar A CODE FHC-S



3



10 Collar F CODE FHC-7F

11 Nut and washer for bearing CODE AN04/AW04




8 Washer for intermediate bearing B



9 Intermediate bearing



7 Drive gear CODE GRI-7



27 Positioning pin

28 Bracket

27 Positioning pin

BT30/40, A63

CODE	Fig.	Pin type	φD	L
HP-50S	1	Straight pin	18	50
-50W		Expansion pin		
-50T	3	Taper pin	20	


DN40, CT40

HP-62S	1	Straight pin	18	62
-62W		Expansion pin		
-50TL	3	Taper pin	20	65

BT50, DN50, CT50

HP-62S	1	Straight pin	18	62
-62S-20	2		20	
-62W	1	Expansion pin	18	
-62W-20	2		20	
-62T	3	Taper pin	28	

Fig.1 Fig.2 Fig.3



28 Bracket

BT30/40, A63


CODE	S
FKA-60	60
-65	65

DN40, CT40

FKA-60-L	60
-65-L	65

BT50, DN50, CT50

FKA- 80	80
- 85	85
-110	110



HFD7

Drill (φ1~7)

23 Angle shaft(for drilling) CODE FR-D7L

26 Draw bolt CODE FR-7BL

DETa-1 Collet (D7)→P.8

HFT4

25 Draw nut and spring CODE FR-T4NS

Tap sleeve (TA4)→P.8

Tap (M2~8)

24 Angle shaft(for tapping) CODE FR-T4

21 Collar C CODE FBC-7C

22 Bearing for angle shaft CODE 71804

19 Head

20 Collar B CODE FBC-7B

※It is already installed in head

18 Passive gear CODE GRO-7

16 Collar E CODE FBC-7E

17 Collar D CODE FBC-7D

15 Wave washer CODE FWW-7

14 Bearing for angle shaft CODE 7903A5

12 Fixation nut for angle shaft CODE FBN-7

13 Cover CODE FBK-7

HFD7L / HFA10 / HFT4L (BT30)


CODE (Master Holder)
BT30-HFD7L-120
-HFA10-120
-HFT4L-120

■**Std. Access.**
- Fixing spanner (KS-23) (HFD7L)
- Hexagonal wrench set (W-1550S)
- Single-ended wrench (SN-13) (HFD7L/HFA10)
- Fook spanner (FC-32) (HFA10)

※3, 4, 9, 15 and 16 are able to use standard commercial items.


28 Positioning pin

CODE	Pin type	ϕD	L
HP-45S	Straight pin	12	45
HP-E50S	Straight pin	18	50




29 Bracket

CODE	S
FKC-50	50
FKC-65	65



■**Note**
- Be sure to use positioning pin (HP-45S) and the bracket (FKC-50) in a combination, and the positioning pin (HP-E50S) and the bracket (FKC-65) in combination.



The tools for assembly

Wrench (for shank)

To be used for tightening 9. It can also be used as a wrench for head of HFD12.

CODE
TSS-HF7L



Wrench (for head)

To be used for tightening 23 and 24.

CODE
TSH-HF7



HFD12 / HFT6 (BT30/40/50, A63, DN40/50, CT40/50)

CODE (Master Holder)	1 Shank	2 Orientation Ring	3 Angular bearing	4 Housing	6 Collar A	7 Collar AXL	8 Intermediate bearing
BT30 -HFD12-122	BT30 -FSA-12S	ORR-30	7005ADB	FHA-S	FHC-S	-	-
-HFT 6-122							
BT40 -HFD12-120	BT40 -FSA-12S	ORR-40					
-HFT 6-120							
-HFD12-180	BT40 -FSA-12L			FHA-L	FHC-L		
-HFT 6-180							
BT50 -HFD12-135	BT50 -FSA-12S			FHA-S	FHC-S		
-HFT 6-135							
-HFD12-195	BT50 -FSA-12L			FHA-L	FHC-L		
-HFT 6-195							
-HFD12-255	BT50 -FSA-12XL		7906A5DB	FHA-XL	FHC-XL1 (※)	FHC-XL2 (※)	6005VV
-HFT 6-255							
A63 -HFD12-123	A63 -FSA-12S	ORR-40	7005ADB	FHA-S	FHC-S	-	-
-HFT 6-123							
-HFD12-183	A63 -FSA-12L			FHA-L	FHC-L		
-HFT 6-183							
-HFD12-243	A63 -FSA-12XL		7906A5DB	FHA-XL	FHC-XL1 (※)	FHC-XL2 (※)	6005VV
-HFT 6-243							
DN40A-HFD12-135	DN40A-FSA-12S	ORR-40	7005ADB	FHA-S	FHC-S	-	-
-HFT 6-135							
-HFD12-195	DN40A-FSA-12L			FHA-L	FHC-L		
-HFT 6-195							
DN50A-HFD12-135	DN50A-FSA-12S			FHA-S	FHC-S		
-HFT 6-135							
-HFD12-195	DN50A-FSA-12L			FHA-L	FHC-L		
-HFT 6-195							
-HFD12-255	DN50A-FSA-12XL		7906A5DB	FHA-XL	FHC-XL1 (※)	FHC-XL2 (※)	6005VV
-HFT 6-255							
CT40 -HFD12-135	CT40 -FSA-12S	ORR-40	7005ADB	FHA-S	FHC-S	-	-
-HFT 6-135							
-HFD12-195	CT40 -FSA-12L			FHA-L	FHC-L		
-HFT 6-195							
CT50 -HFD12-135	CT50 -FSA-12S			FHA-S	FHC-S		
-HFT 6-135							
-HFD12-195	CT50 -FSA-12L			FHA-L	FHC-L		
-HFT 6-195							
-HFD12-255	CT50 -FSA-12XL		7906A5DB	FHA-XL	FHC-XL1 (※)	FHC-XL2 (※)	6005VV
-HFT 6-255							

(※) FHC-XL1/XL2FHC-XL1/XL2 Set 2pcs-each

■**Std. Access.**
- Fixing spanner (KS-30) ● Hexagonal wrench set (W-1550S)
- Single-ended wrench 17mm (SN-17)

※3, 8, 10, 13 and 16 are able to use standard commercial items.

25 Positioning pin

BT30/40, A63

CODE	Fig.	Pin type	φD	L
HP-50S	1	Straight pin	18	50
-50W		Expansion pin		
-50T	3	Taper pin	20	

DN40, CT40

CODE	Fig.	Pin type	φD	L
HP-62S	1	Straight pin	18	62
-62W		Expansion pin		
-50TL	3	Taper pin	20	65

BT50, DN50, CT50

CODE	Fig.	Pin type	φD	L
HP-62S	1	Straight pin	18	62
-62S-20	2		20	
-62W	1	Expansion pin	18	
-62W-20	2		20	
-62T	3	Taper pin	28	

26 Bracket

BT30/40, A63


CODE	S
FKA-60	60
-65	65

DN40, CT40

CODE	
FKA-60-L	60
-65-L	65

BT50, DN50, CT50

CODE	
FKA- 80	80
- 85	85
-110	110



The tools for assembly

Wrench (for shank)

To be used for tightening 10.

CODE
TSS-HF12




Wrench (for head)

To be used for tightening 11 and 12.

CODE
TSH-HF12





HFA20 / HFT12 (BT40/50, A63, DN40/50, CT40/50)

CODE (Master Holder)	① Shank	③ Needle bearing	⑤ Angular bearing	⑥ Collar A	⑦ Housing	⑧ Angular bearing
BT40 -HFA20-135	BT40 -FSA-20S	—	7906A5	FHC-20S	FHA-20S	7905A5
-HFT12-135						
-HFA20-195	BT40 -FSA-20L			FHC-20L	FHA-20L	
-HFT12-195						
BT50 -HFA20-150	BT50 -FSA-20S			FHC-20S	FHA-20S	
-HFT12-150						
-HFA20-210	BT50 -FSA-20L			FHC-20L	FHA-20L	
-HFT12-210						
-HFA20-270	BT50 -FSA-20XL	TAF374720	7905A5DB	FHC-20XL	FHA-20XL	—
-HFT12-270						
A63 -HFA20-198	A63 -FSA-20L	—	7906A5	FHC-20L	FHA-20L	7905A5
-HFT12-198						
-HFA20-258	A63 -FSA-20XL	TAF374720	7905A5DB	FHC-20XL	FHA-20XL	—
-HFT12-258						
DN40A-HFA20-150	DN40A-FSA-20S	-	7906A5	FHC-20S	FHA-20S	7905A5
-HFT12-150						
-HFA20-210	DN40A-FSA-20L			FHC-20L	FHA-20L	
-HFT12-210						
DN50A-HFA20-150	DN50A-FSA-20S			FHC-20S	FHA-20S	
-HFT12-150						
-HFA20-210	DN50A-FSA-20L			FHC-20L	FHA-20L	
-HFT12-210						
-HFA20-270	DN50A-FSA-20XL	TAF374720	7905A5DB	FHC-20XL	FHA-20XL	—
-HFT12-270						
CT40 -HFA20-150	CT40 -FSA-20S	-	7906A5	FHC-20S	FHA-20S	7905A5
-HFT12-150						
-HFA20-210	CT40 -FSA-20L			FHC-20L	FHA-20L	
-HFT12-210						
CT50 -HFA20-150	CT50 -FSA-20S			FHC-20S	FHA-20S	
-HFT12-150						
-HFA20-210	CT50 -FSA-20L			FHC-20L	FHA-20L	
-HFT12-210						
-HFA20-270	CT50 -FSA-20XL	TAF374720	7905A5DB	FHC-20XL	FHA-20XL	—
-HFT12-270						

■**Std. Access.**
- Fixing spanner(KS-41) • Hexagonal wrench set (W-1550S)
- Fook spanner(FC-50) (HFA20)

※③, ⑤, ⑧, ⑯, ⑱ and ㉑ are able to use standard commercial items.

The tools for assembly

Wrench (for shank and head)

To be used for tightening ⑪ and ⑰.

CODE
TS-HA20




Assembling tool for needle bearings

To be used for tightening ㉑.

CODE
TPN-HA20





① Shank

② Orientation ring CODE ORR-40

③ Needle bearing(XL)

④ Ring A(XL) CODE FHR-A

⑤ Angular bearing

⑥ Collar A

⑦ Housing

⑧ Angular bearing

⑨ Ring B CODE FHR-B

⑩ Drive gear CODE GR1-20

⑪ Shank lock nut CODE FHN-20

⑫ Dovetail nut CODE FDN-20

㉗ Positioning pin

BT40, A63

CODE	Fig.	Pin type	ϕD	L
HP-50S	1	Straight pin	18	50
-50W		Expansion pin		
-50T	3	Taper pin	20	


DN40, CT40

HP-62S	1	Straight pin	18	62
-62W		Expansion pin		
-50TL	3	Taper pin	20	65

BT50, DN50, CT50

HP-62S	1	Straight pin	18	62
-62S-20	2		20	
-62W	1	Expansion pin	18	
-62W-20	2		20	
-62T	3	Taper pin	28	

Fig.1 Fig.2 Fig.3




㉘ Bracket


BT40, A63, DN40, CT40

CODE	S
FKB-60	60
-65	65

BT50, DN50, CT50

FKB- 80	80
- 85	85
-110	110





㉗ Positioning pin

㉘ Bracket

HFA20

㉔ Nut CODE NUA-CTA20

㉓ Angle shaft(for drilling) CODE FR-A20

Drill (ϕ5.8~20)

Endmill (ϕ5.8~20)

Spring collet (C20)→P.8

HFT12

Tap (M14, 16) Tap sleeve (TA12)→P.8

Tap (M3~12) Tap sleeve (TA6)→P.8

㉕ Angle shaft (for tapping) CODE FR-T12

㉖ Draw nut and spring CODE FR-T12NS

⑳ Collar B CODE FBC-20B

㉒ Collar C CODE FBC-20C

㉑ Needle bearing CODE TAF324230P6

⑬ Head CODE FBA-20

⑭ Passive gear CODE GRO-20

⑯ Deep-groove bearing CODE 6905

⑱ Thrust bearing CODE CRT10-20 ※Only for HFA20

⑰ Fixation nut for angle shaft CODE FBN-20

⑮ Bearing supporter CODE FBK2-20

⑲ Cover (for drilling) CODE FBK-A20

Cover (for tapping) CODE FBK-T12

HFCS6 (BT30)

CODE(Master Holder)
BT30-HFCS6-155

■Std. Access.
- Fixing spanner(PS-21)
- Hexagonal wrench set (W-1550S)

※3,7,9,14,15 and 20 are able to use standard commercial items.

The tools for assembly

Wrench (for shank)

To be used for tightening 9.
It can also be used as a wrench for head of HFD12.

CODE
TSH-HF12




Pliers for Retaining ring

To be used for tightening 28.

CODE
TSH-G6





1 Shank
CODE BT30-FSA-G6-30



2 Orientation ring
CODE ORR-30L




3 Angular bearing
CODE 7904C




29 Positioning pin



4 Collar A
CODE FHC-7L



30 Bracket



5 Housing
CODE FHA-7L



6 Dovetail nut
CODE FDN-E7



7 Angular bearing
CODE 7903C



8 Collar F
CODE FHC-7LF




9 Nut and washer for bearing
CODE AN03/AW03




10 Collar 1
CODE CA1-G6



11 Drive gear
CODE GR1-G6




12 Head
CODE FBA-G6-30



Drill (φ3,4,6)
Shrink-fit collet (FCS)→P.10
Endmill (φ3,4,6)
14 Bearing
CODE 6803ZZ
15 Bearing
CODE MR126ZZ
16 Collar 2
CODE CA2-G6
17 Passive gear1
CODE GR2-G6
18 Gear 1
CODE GR3-G6
19 Idler shaft 1
CODE ES1-G6
20 Bearing
CODE 688AZZ1
26 Back plate
CODE FBP-G6-30
28 Retaining ring
CODE SW17
Tap (M4,5,6)
Tap collet (FCS-M)→P.10
13 Angle shaft
CODE FR-CS6
21 Collar 3
CODE CA3-G6
23 Collar 4
CODE CA4-G6
24 Gear 2
CODE GR4-G6
22 Idler shaft 2
CODE ES2-G6
25 Collar 5
CODE CA5-G6
27 Cover
CODE KA-G6


29 Positioning pin

CODE	Pin type	φD	L
HP-45S	Straight pin	12	45
HP-E50S	Straight pin	18	50



30 Bracket

CODE	S
FKC-50	50
FKC-65	65



■Note
- Be sure to use positioning pin (HP-45S) and the bracket (FKC-50) in a combination, and the positioning pin (HP-E50S) and the bracket (FKC-65) in combination.

HFCS6 (BT40/50, DN40/50, CT40/50)

CODE (Master Holder)	1 Shank	11 Head	17 Gear 1	Q'ty	18 Gear 3	20 Bearing	Q'ty	21 Collar 3	Q'ty	22 Idler shaft 2	Q'ty	26 Back plate
BT40 -HFCS6-160	BT40 -FSA-G6	FBA-G6	GR3-G6	2	—	688AZZ1	3	CA3-G6	1	ES2-G6	1	FBP-G6
-205		FBA-G6L		3	GR5-G6		7		3		3	FBP-G6L
BT50 -HFCS6-175	BT50 -FSA-G6	FBA-G6		2	—		3		1		1	FBP-G6
-220		FBA-G6L		3	GR5-G6		7		3		3	FBP-G6L
DN40A-HFCS6-175	DN40A-FSA-G6	FBA-G6	GR3-G6	2	—	688AZZ1	3	CA3-G6	1	ES2-G6	1	FBP-G6
-220		FBA-G6L		3	GR5-G6		7		3		3	FBP-G6L
DN50A-HFCS6-175	DN50A-FSA-G6	FBA-G6		2	—		3		1		1	FBP-G6
-220		FBA-G6L		3	GR5-G6		7		3		3	FBP-G6L
CT40 -HFCS6-175	CT40 -FSA-G6	FBA-G6	GR3-G6	2	—	688AZZ1	3	CA3-G6	1	ES2-G6	1	FBP-G6
-220		FBA-G6L		3	GR5-G6		7		3		3	FBP-G6L
CT50 -HFCS6-175	CT50 -FSA-G6	FBA-G6		2	—		3		1		1	FBP-G6
-220		FBA-G6L		3	GR5-G6		7		3		3	FBP-G6L

■**Std. Access.**
- Fixing spanner (PS-21)
- Hexagonal wrench set (W-1550S)

※3, 8, 13, 14 and 20 are able to use standard commercial items.

29 Positioning pin

BT40

CODE	Fig.	Pin type	ϕD	L
HP-50S	1	Straight pin	18	50
-50W		Expansion pin		
-50T	3	Taper pin	20	

DN40, CT40

HP-62S	1	Straight pin	18	62
-62W		Expansion pin		
-50TL	3	Taper pin	20	65

BT50, DN50, CT50

HP-62S	1	Straight pin	18	62
-62S -20	2		20	
-62W	1	Expansion pin	18	
-62W-20	2		20	
-62T	3	Taper pin	28	

Fig.1




Fig.2





Fig.3



30 Bracket

BT40


CODE	S
FKA-60	60
-65	65


DN40, CT40

FKA-60-L	60
-65-L	65

BT50, DN50, CT50

FKA- 80	80
- 85	85
-110	110





The tools for assembly

Wrench (for shank)


To be used for tightening 8.
It can also be used as a wrench for head of HFD12.

CODE
FC-32

Pliers for Retaining ring

To be used for tightening 28.

CODE
TSH-G6



HUD7 / HUT4 (BT30)

CODE (Master Holder)
BT30-HUD7-102
-HUT4-102

■Std. Access.
- Fixing spanner (KS-23) (HUD7)
- Hexagonal wrench set (W-1550S)

※3, 4, 17, 23 and 30 are able to use standard commercial items.


32 Positioning pin

CODE	Pin type	ϕD	L
HP-45S	Straight pin	12	45
HP-E50S	Straight pin	18	50

33 Bracket

CODE	S
FKC-50	50
FKC-65	65

■Note
- Be sure to use positioning pin (HP-45S) and the bracket (FKC-50) in a combination, and the positioning pin (HP-E50S) and the bracket (FKC-65) in combination.



The tools for assembly

Wrench (for shank and head)

To be used for tightening 10, 20 and 22.

CODE
TS-E7

Wrench (for head) · Assembling tool for needle bearings

To be used for tightening 30.

CODE
TP-U7

HUD7 / HUA10 / HUT4 (BT40/50, DN40/50, CT40/50)

CODE (Master Holder)	① Shank
BT40 -HUD 7-135	BT40-FSA-U7
-HUA10-135	
-HUT 4-135	
BT50 -HUD 7-150	BT50-FSA-U7
-HUA10-150	
-HUT 4-150	
DN40A-HUD 7-150	DN40A-FSA-U7
-HUA10-150	
-HUT 4-150	
DN50A-HUD 7-150	DN50A-FSA-U7
-HUA10-150	
-HUT 4-150	
CT40 -HUD 7-150	CT40-FSA-U7
-HUA10-150	
-HUT 4-150	
CT50 -HUD 7-150	CT50-FSA-U7
-HUA10-150	
-HUT 4-150	

■**Std. Access.**
- Fixing spanner(KS-21)
- Hexagonal wrench set (W-1550S)
- Fook spanner(FC-32)(HUA10)

※3, 8, 13, 16, 21 and 27 are able to use standard commercial items.

The tools for assembly

Wrench (for shank)

CODE
FC-32

To be used for tightening 8.




Wrench (for head) · Assembling tool for needle bearings

To be used for tightening 16, 22 and 27.

CODE
TP-U7






① Shank



② Orientation ring CODE ORR-40



③ Angular bearing CODE 7005ADB



④ Housing CODE FHA-S



⑤ Dovetail nut CODE FDN-M6



⑥ Collar A CODE FHC-S



③



⑦ Collar F CODE FHC-7F



⑧ Nut and washer for bearing CODE AN04/AW04



⑨ Gear 1A CODE GR1A-U7




㉓ Cover 2 CODE FBK-U7



㉒ Fixation nut for angle shaft CODE FBN-U7



㉑ Angular bearing CODE 7901A5DB



⑩ Casing CODE FCA-U7
⑪ Collar C CODE FCC-U7C
⑫ Wave washer CODE FWW-U7
⑬ Angular bearing CODE 7900A5DB
⑭ Collar B CODE FCC-U7B
⑮ Gear 1B CODE GR1B-U7
⑯ Nut and washer for bearing CODE AN00/AW00
⑰ Cover 1 CODE FCK-U7
⑱ Gear 2A CODE GR2A-U7
⑲ T nut CODE FCT-U7
⑳ Head CODE FBA-U7
㉔ Collar D CODE FBC-U7D
㉕ Gear 2B CODE GR2B-U7
㉖ Collar E CODE FBC-U7E
㉗ Shell-type needle bearing CODE TLA1812Z

HUD7

㉘ D7 type angle shaft CODE UR-D7
㉛ Collet draw nut CODE UR-ND7
Drill (φ1~7)
DETa-1 Collet (D7)→P.8

HUA10

Drill (φ2.4~10)
㉚ CTA10 type angle shaft CODE UR-A10
Endmill (φ2.4~10)
Spring collet (C10)→P.8
㉝ Nut CODE NUA-CTH10-32

HUT4

㉜ Draw nut and washer CODE UR-T4NS
Tap (M2~8)
㉙ T4 type angle shaft CODE UR-T4
Tap sleeve (TA4)→P.8

㉞ Positioning pin

BT40

CODE	Fig.	Pin type	φD	L
HP-50S	1	Straight pin	18	50
-50W		Expansion pin		
-50T	3	Taper pin	20	


DN40, CT40

CODE	Fig.	Pin type	φD	L
HP-62S	1	Straight pin	18	62
-62W		Expansion pin		
-50TL	3	Taper pin	20	65

BT50, DN50, CT50

CODE	Fig.	Pin type	φD	L
HP-62S	1	Straight pin	18	62
-62S-20	2		20	
-62W	1	Expansion pin	18	
-62W-20	2		20	
-62T	3	Taper pin	28	

Fig.1 Fig.2 Fig.3



㉟ Bracket

BT40


CODE	S
FKA-60	60
-65	65


DN40, CT40

CODE	
FKA-60-L	60
-65-L	65

BT50, DN50, CT50

CODE	
FKA- 80	80
- 85	85
-110	110





㉞ Positioning pin
㉟ Bracket

HUA20 / HUT6 (BT40/50, DN40/50, CT40/50)

CODE (Master Holder)	① Shank
BT40 -HUA20-135	BT40 -FSA-U20
-HUT 6-135	
BT50 -HUA20-150	BT50 -FSA-U20
-HUT 6-150	
DN40A-HUA20-150	DN40A-FSA-U20
-HUT 6-150	
DN50A-HUA20-150	DN50A-FSA-U20
-HUT 6-150	
CT40 -HUA20-150	CT40 -FSA-U20
-HUT 6-150	
CT50 -HUA20-150	CT50 -FSA-U20
-HUT 6-150	

■**Std. Access.**
- Fixing spanner (KS-33)
- Hexagonal wrench set (W-1560S)
- Fook spanner (FC-50) (HUA20)

※③, ⑦, ⑩, ⑭, ⑰, ㉕, ㉗ and ㉙ are able to use standard commercial items.

㉟ Positioning pin

BT40

CODE	Fig.	Pin type	ϕD	L
HP-50S	1	Straight pin	18	50
-50W		Expansion pin		
-50T	3	Taper pin	20	

DN40, CT40

HP-62S	1	Straight pin	18	62
-62W		Expansion pin		
-50TL	3	Taper pin	20	65

BT50, DN50, CT50

HP-62S	1	Straight pin	18	62
-62S-20	2		20	
-62W	1	Expansion pin	18	
-62W-20	2		20	
-62T	3	Taper pin	28	

Fig.1 Fig.2 Fig.3


㊱ Bracket

BT40, DN40, CT40

CODE	S
FKB-60	60
-65	65

BT50, DN50, CT50

FKB- 80	80
- 85	85
-110	110



The tools for assembly

Wrench (for shank)

To be used for tightening ⑩ and ⑰.

CODE
TSS-HU20

Wrench (for head)

To be used for tightening ㉖.

CODE
TSH-HF12

Assembling tool for needle bearings

To be used for tightening ㉙.

CODE
TPN-HU20

Technical support


At MST, we provide the long-term support that allows you to use our products safely and to maintain the high accuracy of our products for your machining.

1. Pre-sales


Provide wide-ranging technical support.



Tool selection




Interference check with 3D drawings



Designing manufacturing jig fixtures

2. On delivery

You will receive instructions.



Instructions for a heater






Maintenance instruction

3. Post-sales

Our Tool Clinic experts can visit your factory to demonstrate the correct usage, maintenance and give seminars.



Seminar



Evaluation



Consulting

Substantial peripheral equipment



Work table
6S DESK
P. 86



Holder,
Tool washing machine
CLEAN BOX
P. 88



TOOL CAP
P. 91



Tool set up stand
P. 94



Test bar
CHECKMATE
P. 90



Tool holder
storage cabinet
P. 98



Cutter protection box
ENDMILL HOUSE
P. 97



Cleaning tool
P. 31

Instructions for use

To ensure optimum, trouble-free performance, please read this operation manual carefully before using the unit. Please contact us if your holder is damaged. We are ready to help you.

Instructions for using tool holder

Pay attention to scratches and rust.

Before using, be sure to remove anti-rust oil on the holder. Scratches and dust can reduce performance and accuracy.Please keep your holders clean with rags.Our CLEAN BOX is available for your cleaning needs.





CLEAN BOX
➔ P. 88

Tool holder shank.

If you insert holder shanks with scratches and dust into machine spindles, the accuracy of the spindle is reduced and the spindle can be damaged. For shank maintenance, use an oil grinding stone or sandpaper to remove scratches and rust. We cannot re-grind shank since it changes the position of gauge line, so we recommend you to purchase new holders.



Storage.

Please use tool protection covers if you store holders with cutters. Cutting edges may be damaged by coming in contact with each other, and you may get injured by sharp cutting edges.



TOOL CAP
➔ P. 91



Retention knob is comsumable.

Exchange the retention knob regularly.(Usage period is depend on the frequency and cutting condition. Approximately 6 months for heavy duty cutting. 18 months for standard cutting.



ANGLE HEAD

- The gear and bearing in the angle head are consumables. Periodic maintenance is required. The inside of the head can be checked by taking off the aluminum cover and the name plate.
- Be careful about the spindle rotating direction. If used in a wrong rotating direction, it will damage the gears.





DETa-1 Collet Holder

Tighten with the proper torque.

- Excessive tightening will reduce the accuracy and damage the internal components.
- An adjustable torque wrench, which can tighten the nut with the appropriate torque, is available for DTA type holders.




Adjustable torque wrench




The nut-tightening torque can be adjusted more properly.

➔ P. 31


- For the DTB3, the torque is adequate when the wrench starts to bend. Do not use T-type or L-type wrenches for tightening. If a ommercially-available torque wrench is used, use a screwdriver type.





Firmly attach the DETa-1 collet to a rod.


Use a collet driver when screwing in the collet all the way until it stops. If the collet is not screwed in enough, the rod might break. The rod is replaceable.



COLLET HOLDER


Do not use a collet that has a notch or nick (flaw) on its tapered surface.

In order to maintain the accuracy of the main unit, the hardness of the collet is less than that of the main unit.
If the collet is used with its tapered surface having a notch or nick (flaw) in it, poor accuracy or insufficient tightening can cause an accident.
Replacing the collet will allow you to restore the holder to more or less its initial precision level.



Precautions for collet tightening.

First set the collet into the nut. Do not first put the collet into the tool holder. The collet might get stuck in the tool holder when tightened by the nut.



Tighten with the proper torque.

Excessive tightening will damage the holder. Clean the tool holder thoroughly inside and out when setting it up.
When coolant or chips remain on the thread of the tool holder or the nut, the frictional resistance decreases. This will cause the torque to be similar to the torque experienced when over-tightening. Therefore, even if the tightening torque is correct, it might lead to breakage.



Adjustable torque wrench



The nut-tightening torque can be adjusted more properly. P.38

Be sure to keep the clamping length of the cutter insertion to a minimum.

Not clamping the cutter with the entire clamping length will cause degradation of accuracy, slipping out of the cutter, and breakage of the tool holder and the nut.

Collet inner diameter	Min. holding length	HOLDER CODE
φ 2.6～10	20	CTA10, CTH10
φ 6 ～20	40	CTA20, CTH20
φ 6 ～ 9.5	38	CTA25, CTH25
φ10 ～15	48	
φ15.5～25	57	
φ25, 28, 30, 32	68	CTA32, CTH32
φ32, 40, 42	70	CTA40

Hi-ART MILLING CHUCK

Do not tighten the collet without inserting a cutting tool.

Tightening the nut without inserting a cutter will cause the clamping portion of the holder to change shape and make it difficult to insert a cutter.



Use the holder within the allowable spindle speed.

HOLDER	MAX.min-1
BT40, A 63-ART32	6000
BT50, A100-ART32	5000
BT50, A100-ART42	3000

Be sure to insert the cutter shank deeper than the minimum clamping depth.

If the internal bore gets damaged, accuracy degradation, gripping torque degradation and unable insertion of the cutter might occur. Refer to "Cutter insertion length" on the chart.

Cutter shank dia.	Min. holding length	
	ART32	ART42
φ 6, 8	30	35
φ10, 12	40	45
φ16, 20	50	
φ25		55
φ32	66	60
φ42	-	76

After removing the tool, loosen the nut by another one turn or more.


Otherwise, the next time the tool is clamped, the component of the nut might be damaged. This will also prevent you from being able to grip the tool with sufficient strength, causing the tool to slip during machining.



RED screw arbor

Confirm if an screw-in tool can be used.


Some of the screw-in end mills cannot be attached to the RED screw arbor.
Please check your screw-in end mills for conformance to the dimensions,or please contact MST.



Holder type	M	φd1	A	B
RSG8	M 8	8.5	10	18
RSG10	M10	10.5	10	22
RSG12	M12	12.5	10	22
RSG16	M16	17	10	25

Tighten the all bolts at least twice.

Tighten the bolts in the order of the numbers marked on them.




SLZ25 SLZ32, 42

Precautions for tightening the bolts.

If you are unable to loosen the last one or two bolts, tighten all the bolts again and then try to loosen all the bolts again little by little.
(This occurs when the bolts are not loosened equally and little by little from the first step.)
When loosened slowly, the wrench might bend, so loosen the bolts with instantaneous torque.


Cutter life comparison depending on different run-out accuracy

When the cutter run-out accuracy is 10μm, cutter life is 2.2 times longer than with 40μm run-out accuracy.




Cutting condition

Cutting tool	:	φ0.1mm drill
Material	:	NAK80(40HRC)
Coolant	:	Water solubility coolant
Revolution	:	20,000min^{-1}
Feed	:	60mm/min
Step feed	:	Non-step
Depth	:	0.4mm



Cutter life comparison when using cutter-through coolant and external coolant

Applying the cutter-through coolant improves the tool life 3.7 times higher than when external coolant is used.





For high-speed spindle rotation


Imbalance value of a machine tool spindle and a tool holder

A tool holder imbalance value (G grade) focuses at high-speed spindle rotation of a machining center. However, it is important to consider the entire rotation body, including the spindle, holder and cutter to determine the high-speed spindle rotation. This is because the holder and cutter weight is much lighter than the spindle weight (less than approx. 1/20th), and thus the effect of a tool holder on the spindle rotating equipment (spindle, tool holder and cutter) becomes significantly smaller.

Spending time and money on balance corrections to the holder alone will not result in significant improvement.







Achieving high-speed, high-efficiency machining requires more than just good balance.

- What is the run-out accuracy of the machine spindle, tool holder and cutting tool?
- Is there taper contact between the machine spindle and tool holder?
- What is the diameter of the cutting tool?
- What is the cutting speed? Spindle rotation?


Points to keep in mind at high-speed rotation.

- Minimize the length of a tool holder and cutting tool as short as possible.
- Use high accuracy and compact design tool holders.
- Optimize the cutting condition(rpm, feed and depth of cut).

MST considers these points carefully and produces a tool holder according to our own pre-balanced design concept.


Pre-balanced design

MST has applied our original pre-balancing to make the tool holders applicable for high-speed spindle rotation. Balancing corrections for our products is not required.




- Counter-balancing at imbalanced design areas.
- O.D finish grinding after heat treatment.

Relationship between a cutter diameter and spindle rotation



■Unbalancing in terms of tolerable residual ration against the balancing grade(G grade value)



<<Reference >>

■Recommend various of G grade of a rotating body

G grade	G	Rotating body
G40	~40	The car wheel
G16	~16	The parts of agricultural machines The parts of truck
G 6.3	~ 6.3	Machine tools and aviation gas- turbine rotors after assembling general mechanical parts
G 2.5	~ 2.5	**The spindle of machine tool** Gas turbine Steam turbine
G 1	~ 1	The grinding wheel spindle of grinding machine
G 0.4	~ 0.4	The grinding wheel spindle of precise grinding machine Gyroscope

■Determining tool holder G grade

$$G = \frac{\text{Imbalance value(g·mm)}}{\text{Weight (kg)}} \times \frac{\text{Spindle rotation speed}}{9{,}550}$$

Holders for high-speed operation include "Imbalance value" and "holder weight" columns in the dimensions table.

■Determining G grade of rotating equipment

(spindle · tool holder · cutting tool)

$$G = \frac{\text{(Spindle + Holder + Cutter) Imbalance value(g·mm)}}{\text{(Spindle + Holder + Cutter) Weight (kg)}} \times \frac{\text{Spindle rotation speed}}{9{,}550}$$

HSK SHANK

MST uses DIN-HSK standard shanks, which are widely used in Japan and other countries as “2-face contact tooling” for high-speed, high-efficiency machining.

▷ The close contact of the end faces (2-face contact) of the HSK shank results in high rigidity for transverse feed, which minimizes vibrations during machining and improves the operating life of the cutting tool and the finished surface.

▷ Even if the spindle expands during high-speed rotations, the tapered hollow portion comes up with that expansion, thereby maintaining high precision.



A type
The most common type in use today.



E type
This type has no drive keyway and is suitable for high-speed machining.



F type
This type uses a combination of different sizes of tapers and flanges.




T type
This type is for turning with multiple machining

Pre-Balanced design

The HSK-A-type shank is unbalanced in its standard form, but at MST we have applied our original pre-balancing to make the tool holders applicable for high-speed machining. According to DIN standards, only the area marked with ※ in the hollow shank needs to be finished. However, MST provides perfect finishing for all areas after heat treatment in order to improve balance.

	MST	DIN standard
A63	15 g·mm	75g·mm
A100	28 g·mm	170g·mm




Three times stronger clamping force

HSK uses a clamping mechanism, which utilizes the wedge effect,to provide a tool gripping power 2.5 to 3.0 times greater than in the retention knob system (BT40 and BT50), thereby increasing rigidity.


	Tensile strength of draw bar	Tool clamping force
BT40	10~15kN	10~15kN
A63	5.8kN	18.4kN
BT50	20~25kN	20~25kN
A100	14.5kN	45.9kN

Unclamping ⇄ Clamping



Rigidity comparison with BT shank

The HSK shank is effective when longer overhang or higher transverse feed rigidity is required. The higher rigidity greatly contributes to improve the operating life of the cutting tool and the smoothness of the finished surface.



Taper gauge

MST establishes the optimal value within the tolerance in accordance with the DIN standard and manufacturers master gauges for tool shanks and those for spindle tapers accordingly.



1/10 taper ring gauge




1/10 taper plug gauge



Detection gauge for end face position

Coolant duct

This is a coolant feed part exclusively for the HSK-A type.
MST's HSK-A type holder comes standard with each coolant duct.



For some machines, the use of a coolant duct (Adjustable) is recommended. The existing coolant duct is replaced with an adjustable one at your request only when you have placed an order for the holder.
→P. 104


TOOLING SYSTEMS for HSK-T

Collaborative development with 17 Japanese manufacturers has resulted in an interface for mill-turning machines based on the HSK-A type.
With its 2008 ISO accreditation, it has become popular standard around the world.



HSK-A Rotating tools

HSK-T Turning tools




Turning mill machine

Technical data

The shank dimensions

HSK-A (Extracts from DIN 69893-1;1993-07)


Shank	A40	A50	A63	A100	A125
b_1 (H10)	8	10.5	12.5	20	25
b_2 (H10)	9	12	16	20	25
b_3 (H10)	11	14	18	22	28
d_1 (h10)	40	50	63	100	125
d_2	30	38	48	75	95
	+0.007 +0.005	+0.009 +0.006	+0.011 +0.007	+0.015 +0.009	+0.018 +0.011
d_3	29.05	36.9	46.53	72.6	91.95
	+0.005 +0.003	+0.006 +0.003	+0.007 +0.003	+0.009 +0.003	+0.011 +0.004
d_4 (Max.)	34	42	53	85	105
d_8 (H10)	21	26	34	53	67
d_9 (H11)	25.5	32	40	63	80
d_{10}	23	29	37	58	73
d_{11}	M12 × 1	M16 × 1	M18 × 1	M24 × 1.5	M30 × 1.5
d_{14} (Max.)	5	6.8	8.4	12	14
e_1	10.88	13.797	17.862	27.329	35.324
f_1 ($^{0}_{-0.1}$)	20	26	26	29	29
f_2 (min.)	35	42	42	45	45
f_3 (± 0.1)	16	18	18	20	20
f_4 ($^{+0.15}_{0}$)	2	3.75	3.75	3.75	3.75
h_1 ($^{0}_{-0.2}$)	17	21	26.5	44	55.5
h_2 ($^{0}_{-0.3}$)	12	15.5	20	31.5	39.5
ℓ_1 ($^{0}_{-0.2}$)	20	25	32	50	63
ℓ_2	4	5	6.3	10	12.5
ℓ_3	9.5	11	14.7	24	30.5
ℓ_4 ($^{+0.2}_{0}$)	6	7.5	10	15	19
ℓ_5 ($^{+0.2}_{0}$)	3.5	4.5	6	10	12
ℓ_6 (JS10)	11.42	14.13	18.13	28.56	36.27
ℓ_7 ($^{0}_{-0.1}$)	8	10	10	12.5	16
ℓ_8 ($^{0}_{-0.3}$)	8	10	12	16	18
ℓ_{12}	12	19	21	24	24
r_3 ($^{\pm 0.05}_{-0.05}$)	1.88	2.38	2.88	4.88	5.88
r_8	4.5	6	8	10	5






HSK-E (Extracts from DIN V 69893-5;1996-01)

Shank	E25	E32	E40	E50
d_1 (h10)	25	32	40	50
d_2	19	24	30	38
	+0.006 +0.004	+0.007 +0.005	+0.007 +0.005	+0.009 +0.006
d_3	18.15	23.27	29.05	36.90
	+0.004 +0.002	+0.005 +0.003	+0.005 +0.003	+0.006 +0.003
d_4 (Max.)	20	26	34	42
d_8 (H10)	14	17	21	26
d_9 (H11)	16.4	21	25.5	32
d_{10}	15	19	23	29
d_{11} (Max.)	3	4.2	5	6.8
ℓ_1 ($^{0}_{-0.2}$)	13	16	20	25
ℓ_2	2.5	3.2	4	5
ℓ_3	8.5	7.3	9.5	11
ℓ_4 (JS10)	7.21	8.92	11.42	14.13
ℓ_5 ($^{0}_{-0.1}$)	6	8	8	10
f_1 ($^{0}_{-0.1}$)	10	20	20	26
f_2 (min.)	20	35	35	42
f_3 (± 0.1)	4.5	16	16	18
f_4 ($^{+0.15}_{0}$)	2	2	2	3.75



HSK-F (Extracts from DIN 69893-1;1993-07)


Shank	F63	F80
d_1 (h10)	63	80
d_2	38	48
	+0.009 +0.006	+0.011 +0.007
d_3	36.9	46.53
	+0.006 +0.003	+0.007 +0.003
d_4 (Max.)	53	67
d_8 (H10)	26	34
d_9 (H11)	32	40
d_{10}	29	37
f_1 ($-^{0}_{0.1}$)	26	26
f_2 (min.)	42	42
f_3 (± 0.1)	18	18
f_4 ($^{+0.15}_{0}$)	3.75	3.75
ℓ_1 ($-^{0}_{0.2}$)	25	32
ℓ_2	5	6.3
ℓ_3	11	14.7
ℓ_4 (Js10)	14.13	18.13
ℓ_5 ($-^{0}_{0.1}$)	10	10
f_1 ($-^{0}_{0.1}$)	26	26
f_2 (min.)	42	42
f_3 (± 0.1)	18	18
f_4 ($^{+0.15}_{0}$)	3.75	3.75





HSK-T (Extracts from DIN 69893-1;1993-07) For turning with turning mill machines


Shank	T40	T50	T63	T100	T125
b_1 ($^{+0.04}_{-0.04}$)	8.05	10.54	12.54	20.02	25.02
b_2 (H10)	9	12	16	20	25
b_3 (H10)	11	14	18	22	28
b_5	7.932	10.425	12.425	19.91	24.915
	+0.03 0	+0.035 0			+0.04 0
d_1 (h10)	40	50	63	100	125
d_2	30.007	38.009	48.010	75.013	95.016
d_3 (H10)	21	26	34	53	67
d_4 (H11)	25.5	32	40	63	80
d_5	23	29	37	58	73
d_6 (Max.)	5	6.8	8.4	12	14
d_9 (Max.)	39	49	62	99	124
d_{15}	M12 × 1	M16 × 1	M18 × 1	M24 × 1.5	M30 × 1.5
e_1	11	13.88	17.99	27.37	35.37
f_1 ($-^{0}_{0.1}$)	20	26	26	29	29
f_2 (min.)	23	30	30	34	34
f_3 (± 0.1)	16	18	18	20	20
f_4 ($^{+0.15}_{0}$)	2	3.75	3.75	3.75	3.75
h_1 ($-^{0}_{0.2}$)	17	21	26.5	44	55.5
h_2 ($-^{0}_{0.3}$)	12	15.5	20	31.5	39.5
ℓ_1 ($-^{0}_{0.2}$)	20	25	32	50	63
ℓ_2	4	5	6.3	10	12.5
ℓ_3 ($^{+0.2}_{0}$)	6	7.5	10	15	19
ℓ_4 ($^{+0.2}_{0}$)	3.5	4.5	6	10	12
ℓ_5 (JS10)	11.42	14.13	18.13	28.56	36.27
ℓ_6 ($-^{0}_{0.1}$)	8	10	10	12.5	16
ℓ_9 ($-^{0}_{0.2}$)	8	10	12	16	18
ℓ_{12}	12	19	21	24	24
r_3 ($^{+0.05}_{-0.05}$)	1.88	2.38	2.88	4.88	5.88
r_9	4.5	6	8	10	5






BT (Extracts from MAS 403)


Shank	BT30	BT40	BT50
D_1	31.75	44.45	69.85
ℓ_1 (±0.15)	48.4	65.4	101.8
d_2 (H8)	12.5	17	25
g (6H)	M12	M16	M24
ℓ_2 (min.)	24	30	45
ℓ_3 (min.)	34	43	62
ℓ_4	7	9	13
b (H12)	16.1	16.1	25.7
ℓ_5 (min.)	17	21	31
t ($^{0}_{-0.2}$)	16.3	22.6	35.4
D_5 (h8)	46	63	100
f	20	25	35
v (±0.1)	13.6	16.6	23.2
y (±0.4)	2	2	3






DIN (DIN69871-1)


Shank	DN40	DN50
D_1	44.45	69.85
D_2	63.55	97.5
D_3	56.25	91.25
D_4	50	80
L_1	68.4	101.75
L_3	3.75	6.495
b_1	16.1	25.7
d_1	17	25
t_1	22.8	35.5
t_2	25	37.7
t_3	18.5	30







CAT.

Shank	CT40	CT50
D_1	1.75	2.75
D_2	2.5	3.88
D_3	2.22	3.59
D_4	1.75	2.75
L_1	2.69	4
b_1	.65	1.06
d_1	.64	1.03
t_1	.99	1.49
t_2	.84	1.39





HSK-A125/ F80PD are also available as standard products.





If you would like more detailed information, please contact MST and ask for a catalog.

Drill hole size in metric coarse screw thread

Nominal size x pitch	Drill hole dia.
M 1 ×0.25	0.75
M 1.2×0.25	0.95
M 1.6×0.35	1.25
M 2 ×0.4	1.6
M 2.5×0.45	2.1
M 3 ×0.5	2.5
M 4 ×0.7	3.3
M 5 ×0.8	4.2
M 6 ×1	5
M 8 ×1.25	6.8
M10 ×1.5	8.5
M12 ×1.75	10.3
M16 ×2	14
M20 ×2.5	17.5
M24 ×3	21
M30 ×3.5	26.5
M33 ×3.5	29.5
M36 ×4	32
M39 ×4	35
M42 ×4.5	37.5
M45 ×4.5	40.5
M48 ×5	43

Drill hole size in unified screw threads

Nominal size x pitch	Drill hole dia.
NO. 1 - 64UNC	1.55
NO. 2 - 56UNC	1.8
NO. 3 - 48UNC	2.1
NO. 4 - 40UNC	2.3
NO. 5 - 40UNC	2.6
NO. 6 - 32UNC	2.8
NO. 8 - 32UNC	3.4
NO.10 - 24UNC	3.9
NO.12 - 24UNC	4.5
1/4 - 20UNC	5.1
5/16 - 18UNC	6.6
3/8 - 16UNC	8
7/16 - 14UNC	9.4
1/2 - 13UNC	10.8
9/16 - 12UNC	12.2
5/8 - 11UNC	13.6
3/4 - 10UNC	16.5
7/8 - 9UNC	19.5
1 -8UNC	22.2
1 1/8 - 7UNC	25
1 1/4 - 7UNC	28.2
1 3/8 - 6UNC	30.8
1 1/2 - 6UNC	34
1 3/4 - 5UNC	39.5

Drill hole size in screw for pipe

Nominal size	Rc(PT)	Rp(PS)	G(PF)
1/8	8.2	8.5	8.8
1/4	10.9	11.4	11.87
3/8	14.4	14.9	15.38
1/2	18	18.5	19.1
5/8	—	—	21
3/4	23	24	24.6
7/8	—	—	28.3
1	29	30	30.9
1 1/8	—	—	35.5
1 1/4	38	39	39.4
1 1/2	44	45	45.4

Dia. of tap shank



Metric screw threads	Unified screw threads	Gas screw threads	φD2
φD1			
M 1~M 2.6	UNo. 0~ 4		3
M 3・M 3.5	UNo. 5・6		4
M 4・M 4.5	UNo. 8		5
M 5・M 5.5	UNo.10・12		5.5
M 6	U 1/4		6
	U 5/16		6.1
M 7・M 8			6.2
M 9・M10	U 3/8		7
M11	U 7/16	P1/16・1/8	8
M12			8.5
	U 1/2		9
M13			9.5
M14・M15	U 9/16		10.5
		P 1/4	11
	U 5/8		12
M16			12.5
M17			13
M18	U 3/4	P 3/8	14
M20			15
M22	U 7/8		17
		P 1/2	18
M24・M25		P 5/8	19
M26・M27	U1		20
M28			21
	U1 1/8		22
M30		P 3/4	23
M32	U1 1/4	P 7/8	24
M33			25
M35	U1 3/8	P1	26
M36・M38		P1 1/8	28
M39・M40	U1 1/2		30
M42	U1 5/8	P1 1/4	32
M45	U1 3/4	P1 3/8	35
M48		P1 1/2	38
M50	U2	P1 5/8	40
M52		P1 3/4	42

Dimensional tolerance of typically used mating (JIS B 0401)

The class of dimension(mm)		The tolerance of the hole dimension(μm)						The tolerance of the shaft dimension(μm)					
More than	Less than	H4	H5	H6	H7	H8	H9	h4	h5	h6	h7	h8	h9
—	3	+3 0	+4 0	+6 0	+10 0	+14 0	+25 0	0 -3	0 -4	0 -6	0 -10	0 -14	0 -25
3	6	+4 0	+5 0	+8 0	+12 0	+18 0	+30 0	0 -4	0 -5	0 -8	0 -12	0 -18	0 -30
6	10	+4 0	+6 0	+9 0	+15 0	+22 0	+36 0	0 -4	0 -6	0 -9	0 -15	0 -22	0 -36
10	18	+5 0	+8 0	+11 0	+18 0	+27 0	+43 0	0 -5	0 -8	0 -11	0 -18	0 -27	0 -43
18	30	+6 0	+9 0	+13 0	+21 0	+33 0	+52 0	0 -6	0 -9	0 -13	0 -21	0 -33	0 -52
30	50	+7 0	+11 0	+16 0	+25 0	+39 0	+62 0	0 -7	0 -11	0 -16	0 -25	0 -39	0 -62
50	80	+8 0	+13 0	+19 0	+30 0	+46 0	+74 0	0 -8	0 -13	0 -19	0 -30	0 -46	0 -74
80	120	+10 0	+15 0	+22 0	+35 0	+54 0	+87 0	0 -10	0 -15	0 -22	0 -35	0 -54	0 -87
120	180	+12 0	+18 0	+25 0	+40 0	+63 0	+100 0	0 -12	0 -18	0 -25	0 -40	0 -63	0 -100
180	250	+14 0	+20 0	+29 0	+46 0	+72 0	+115 0	0 -14	0 -20	0 -29	0 -46	0 -72	0 -115
250	315	+16 0	+23 0	+32 0	+52 0	+81 0	+130 0	0 -16	0 -23	0 -32	0 -52	0 -81	0 -130
315	400	+18 0	+25 0	+36 0	+57 0	+89 0	+140 0	0 -18	0 -25	0 -36	0 -57	0 -89	0 -140
400	500	+20 0	+27 0	+40 0	+63 0	+97 0	+155 0	0 -20	0 -27	0 -40	0 -63	0 -97	0 -155

Conversion table for International System of Units

Force

N	kgf
1	1.01972×10^{-1}
9.80665	1

Pressure

Pa	kgf/cm²
1	1.01972×10^{-5}
9.80665×10^{4}	1

Stress

Pa	kgf/mm²
1	1.01972×10^{-7}
9.80665×10^{6}	1

INDEX

	CODE	NAME	Page
A	AB – 15	Semi-finished positioning block	19
	ABF005	Positioning block for machines	7
	BT40 – AHA20 – 160	ANGLE HEAD SOLID type	16
	F190 – AHA20 – 200	ANGLE HEAD FLANGE type	17
	BT50 – AHB5 – 225	ANGLE HEAD MODULAR type	15
	BT50 – AHC10 – 245		
	BT50 – AHA25 – 250	ANGLE HEAD SOLID type	16
	BT50 – AHD30 – 195		
	BT40 – AHU10 – 175	ANGLE HEAD UNIVERSAL type	18
	AJB – M6 – L	Adjust bolt (WIRE CUT UNIT)	102
	AJC – M14	Adjust screw (COLLET HOLDER)	37
	AJN – M18L	Adjust screw (Hi-ART Milling chuck)	44
	AP40 – T30V	Adapter (Petit Ball / MY CUBE)	95
	BT50 – ART32 – 105	Hi-ART Milling chuck	42, 104
	AW – 1	Adjustable torque wrench	31,38,103
B	T50 – BL40 – 42	BLANK TOOL (Tool for turning mill)	72
C	C10 – 6	SPRING COLLET	8, 38
	C10 – A set	SPRING COLLET Standard set	38
	C10 – RM	Collet remover	38
	T63 – CAAX52 – 150	CHECKING ARBOR	72
	CAP2022	Cap dispenser	92
	CBX – 01	CLEAN BOX	88
	T63 – CC32 – 90	Set screw holders for Round shank	69
	CCD094 – PA	Insert	62
	CD40 – 01	Coolant duct (fixed)	104
	CD50 – A1	Coolant duct (Dummy duct)	104
	CD63 – 01F	Coolant duct (Adjustable)	104
	CE – CTS10	Collet remover	38
	ST6 – CEB102	Centering bar	84
	CF12 – 4 – 35	SLIMLINE collet	※
	CLP – 7E	Coolant cap	30
	CLP – 101	Clamper (WIRE CUT UNIT)	102
	NT30 – CMA – 20 – 125	TEST BAR CHECKMATE	90
	HSK32 – CMB – 25 – 175		
	CN – 103	Container box	98
	T100 – CN40 – 115	Set screw holders for Round shank	69
	CP – 14M	Coolant screw	39
	CR12-6-55	SLIMLINE collet	※
	CS12-3-80		
	CSA – M14	Coolant screw	39
	CSR – 14	Coolant screw (COLLET HOLDER)	39
	BT30 – CTA10 – 45	COLLET HOLDER	36
	BT50 – CTH10 – 105	COLLET HOLDER for high-speed	34
	E32 – CTS10 – 50		35
D	D7 – 1.5	DETa-1 COLLET	31
	A40 – DOC17.5 – 55	Dovetail clamping (SMART GRIP)	78
	A63 – DOV110I	Dovetail vise (SMART GRIP)	79
	DR – 1	Collet driver	31
	BT40 – DTA3 – 95	DETa-1 COLLET HOLDER A type	24
	BT50 – DTB7 – 75	DETa-1 COLLET HOLDER B type	26
	A50 – DTE7 – 105	DETa-1 COLLET HOLDER E type	28
	DW – 2.5 – 110	Wrench	31, 103
E	7EA – 3.5 – 3	Spacer	30
	12EBF – BL – 5		
	12EBM – 3 – 3		
	12EBS – 3.6 – 3		
	EMO – STD3 – 2	ENDMILL HOUSE	97
	ER8 – 4	SPRING COLLET	19
	7ES – A	Spacer set	30
	ESX12 – 6	SPRING COLLET	19

	CODE	NAME	Page
F	F – 38	Spanner	38, 103
	F – 38AW	Spanner for torque wrench	31, 103
	F160H32 – A40	Mounting plate (SMART GRIP)	78
	F100H21 – A40 – 50	The Manual clamping head (SMART GRIP)	78
	F100S65 – A63 – 89	The Automation clamping head (SMART GRIP)	81
	FC – 32	Spanner	38, 103
	FC – 36AW	Spanner for torque wrench	38, 103
	FCS6 – 3	Shrink-fit collet	10
	FCS6 – M4	Tap collet	10
	FKA-60	Stationary bracket (ANGLE HEAD HALF)	105 ～
	FKB-60		
	FKC-50		
	FM – 72	Spanner with ejection hook (Hi-ART MILLING CHUCK)	42, 103
	BT40 – FMH16 – 29 – 45	Cutter arbor with spindle-through coolant	53
	BT50 – FMH22 – 47 – 165H	FMH RIGID type	47
	A40 – FP40-35	Flange clamping (SMART GRIP)	79
G	GRP – 002	Grip	102
H	HB – 01	Semi-finished positioning block (ANGLE HEAD HALF)	7
	HBX – A40	TOOL HOLDER STORING CABINET	98
	HF – BT30	Tool set up stand (Vice clamping type)	95
	BT30 – HFA10 – 120	ANGLE HEAD HALF 90°type	9
	BT30 – HFCS6 – 155	ANGLE HEAD HALF mini type	10
	BT40 – HFD7 – 120	ANGLE HEAD HALF 90°type	9
	BT30 – HFT4 – 122		
	HP-50S	Positioning pin (ANGLE HEAD HALF)	105 ～
	BT40 – HUA10 – 135	ANGLE HEAD HALF UNIVERSAL type	12
	BT30 – HUD7 – 102		
	BT30 – HUT4 – 102		
I	IR 15 – A40FP	Positioner boss (SMART GRIP)	79
J	JAE – 501	Extension Jaw	100
K	KJ – 45	Insert and insert holder set	62
M	MB5 – 112	Head	15
	MBF-M12	Clamp bolt (Cutter arbor with spindle-through coolant)	54
	BT40 – MBH50 – 150	MICRO HEAD MBH type	59
	BT30 – MBJ45 – 120	MICRO HEAD MBJ45 type	61
	BT50 – MBJ70 – 165	MICRO HEAD MBJ70 type	62
	MC10 – 132	Head	15
	MDV – 501	MIDDLE VISE	99
	BT50 – MFA20 – 165	MICRO HEAD MFA type	57
	BT40 – MS – 98	Shank	15
	MS2 – 30	Extension	57
	MU – S6H	UNIVERSAL FACING BORING HEAD	73
	MY CUBE50	MY CUBE	95
N	NOZ – M6 – 12	Nozzle	42,44,103
	NUA – CTA10	Nut	37, 104
	NUB – CTH10 – 3.6	SUKIMA nut	39, 104
P	P30T – 1	Retention knob	64
	P – 445		
	P – 535/538	Retention knob (BT30-DTB12)	27
	PA – R – 1	PALETTE	96
	PCT01 – 10	Cleaning tool felt type	31
	PETIT BALL40	Petit Ball	95
	PJ – 45	Insert and insert holder set	62
	PR – DTA3	Rod (DETa-1 COLLET HOLDER DTA3 type)	25
	PTC10	Cartridge (MICRO HEAD MBH type)	60
	PTE – 001	Extension Plate	101
R	RC – 26	CTS Special wrench	38, 103
	RS – A63 – A40	Adapter (SMART GRIP)	79
	BT40 – RSG8 – 105 – M25	RED SCREW arbor	49

	CODE	NAME	Page
S	S42 – 6F	Straight collet	42
	S – STA12	Insert holder	62
	S – STV1822		
	T63 – SA2525 – 105	Insert holders for Square-shank	70
	T63 – SB2525 – 95		71
	T50 – SC2020R – 95		
	T40 – SH2020 – 75		72
	A40 – SCD20 – 55	Side clamp B(SMART GRIP)	80
	A40 – SCS10 – 40	Side clamp A(SMART GRIP)	80
	BT50 – SLFB4 – 90 – M22	SLIMLINE MONO series	※
	BT50 – SLK12 – 75	SLIMLINE 2PIECE type Master holder	※
	BT50 – SLRA4 – 110 – M42	SLIMLINE MONO series SLIMLINE STRAIGHT ARBOR	※
	BT50 – SLRB8 – 110 – M42		
	BT50 – SLSA4 – 140 – M42		
	BT50 – SLSB8 – 140 – M42		
	A100 – SLZ25 – 135	SUMMIT	44
	T50 – SN2020R – 110	Insert holders for Square-shank	71
	SRC – 501	Clamp on Slider	100
	SRL – 501	L Slider	
	SRS – 501	Sandwich Slider	
	SRV – 501	V Slider	
	SRV – 01	Dedicated bracket	92
	SS32 – 8	Sleeve for a set screw holders	69
	STB – M6 – L	Stud bolt	102
	STGP10	Cartridge	60
	STH18	Insert holder	62
	STV – C12055		61
	T40 – SV2020R – 90	Insert holders for Square-shank	70
T	TA4 – M2	Tap sleeve	8
	TBU10	Test bar	18
	TCA2022 – 10	TOOL CAP TCA type	92
	TCB0820 – 10	TOOL CAP TCB type	
	TCC0607 – 50	TOOL CAP TCC type	93
	TCC – F	Variety set	93
	TNB114 – PB	MICRO HEAD MBH type	60
	TPA082 – PA	MICRO HEAD MFA type	57
	TPC112 – PA	MICRO HEAD MBJ/MBH type	62
	TPE042 – PA	MICRO HEAD MBJ type	61
	TR – 5	Tap rod(DETa-1 COLLET HOLDERDTEtype)	30
	TW – 4	Wrench	31, 103
W	W – 206	Wrench	44, 103
	W – 135DR	Spanner・Wrench	31, 103
	WCU – A	WIRE CUT UNIT	101
Z	BT40 – ZPB – 200	Goo CHECKER (Set up the original point on the Z axis / measuring tool for reference position)	83
	BT40 – ZPM – 150		
123	6SD – 01	6S DESK	86

※See our dedicated catalog for shrink-fit holder SLIMLINE.
For details, please contact us.

INDEX

	NAME	CODE	Page
A	Adapter(Petit Ball / MY CUBE)	AP40 – T30V	95
	Adapter(SMART GRIP)	RS – A63 – A40	79
	Adjust bolt (WIRE CUT UNIT)	AJB – M6 – L	102
	Adjust screw (SUMMIT)	AJN – M18L	44
	Adjust screw (COLLET HOLDER)	AJC – M14	37
	Adjustable torque wrench	AW – 1	103
	ANGLE HEAD HALF 90°type	BT30 – HFA10 – 120	9
		BT40 – HFD7 – 120	
		BT30 – HFT4 – 122	
	ANGLE HEAD HALF mini type	BT30 – HFCS6 – 155	10
	ANGLE HEAD HALF UNIVERSAL type	BT40 – HUA10 – 135	12
		BT30 – HUD7 – 102	
		BT30 – HUT4 – 102	
	ANGLE HEAD FLANGE type	F190 – AHA20 – 200	17
	ANGLE HEAD MODULAR type	BT50 – AHB5 – 225	15
		BT50 – AHC10 – 245	
	ANGLE HEAD SOLID type	BT40 – AHA20 – 160	16
		BT50 – AHD30 – 195	
	ANGLE HEAD UNIVERSAL type	BT40 – AHU10 – 175	18
	The Automatic clamping head (SMART GRIP)	F100S65 – A63 – 89	81
B	BLANK TOOL (Tool for turning mill)	T50 – BL40 – 42	72
C	Cap dispenser	CAP2022	92
	Cartridge (MICRO HEAD MBH type)	PTC10	60
		STGP10	
	Centering bar	ST6 – CEB102	84
	CHECKING ARBOR	T63 – CAAX52 – 150	72
	Clamp bolt (Cutter arbor with spindle-through coolant)	MBF – M12	54
	Clamper (WIRE CUT UNIT)	CLP – 101	102
	CLEAN BOX	CBX – 01	88
	Cleaning tool wiper type	PCT01 – 10	31
	Collet driver	DR – 1	31
	COLLET HOLDER	BT30 – CTA10 – 45	36
	COLLET HOLDER for high-speed	BT50 – CTH10 – 105	34
		E32 – CTS10 – 50	35
	Collet remover	CE – CTS10	38
		C10 – RM	
	Container box	CN – 103	98
	Coolant screw (COLLET HOLDER)	CSA – M14	39
		CP – 14M	
		CSR – 14	
	Coolant cap	CLP – 7E	30
	Coolant duct (Adjustable)	CD63 – 01F	104
	Coolant duct (Dummy duct)	CD50 – A1	
	Coolant duct (fixed)	CD40 – 01	
	Cutter arbor with spindle-through coolant	BT40 – FMH16 – 29 – 45	53
D	Dedicated bracket (TOOL CAP TCA type)	SRV – 01	92
	DETa-1 COLLET	D7 – 1.5	31
	DETa-1 COLLET HOLDER A type	BT40 – DTA3 – 95	24
	DETa-1 COLLET HOLDER B type	BT50 – DTB7 – 75	26
	DETa-1 COLLET HOLDER E type	A50 – DTE7 – 105	28
	Dovetail clamping (SMART GRIP)	A40 – DOC17.5 – 55	78
	Dovetail vise A,B (SMART GRIP)	A63 – DOV110I	79
E	ENDMILL HOUSE	EMO – STD3 – 2	97
	Extension (MICRO HEAD MFA type)	MS2 – 30	57
	Extension Jaw (MIDDLE VISE)	JAE – 501	100
	Extension Plate (WIRE CUT UNIT)	PTE – 001	101
F	Flange clamping (SMART GRIP)	A40 – FP40-35	79
	FMH RIGID type	BT50 – FMH22 – 47 – 165H	47

	NAME	CODE	Page
G	Goo Checker	BT40 – ZPB – 200	83
		BT40 – ZPM – 150	
	Grip	GRP – 002	102
H	Head (ANGLE HEAD MODULAR type)	MB5 – 112	15
		MC10 – 132	
	Hi-ART MILLING CHUCK	BT50 – ART32 – 105	41
I	Insert holder(MICRO HEAD)	S – STA12	62
		STH18	
		STV – C12055	61
		s-STV1822	62
	Insert and insert holder set (MICRO HEAD)	KJ – 45	62
		PJ – 45	
	Insert holders for Square-shank	T63 – SA2525 – 105	70
		T63 – SB2525 – 95	71
		T50 – SC2020R – 95	
		T40 – SH2020 – 75	72
		T50 – SN2020R – 110	71
		T40 – SV2020R – 90	70
M	MICRO HEAD MBH type	BT40 – MBH50 – 150	59
		TNB114 – PB	60
	MICRO HEAD MBJ45 type	BT30 – MBJ45 – 120	61
		TPE042 – PA	
	MICRO HEAD MBJ70 type	BT50 – MBJ70 – 165	62
	MICRO HEAD MBJ/MBH type	TPC114 – PA	62
	MICRO HEAD MFA type	BT50 – MFA20 – 165	57
		TPA082 – PA	
	MIDDLE VISE	MDV – 501	99
	Mounting plate (SMART GRIP)	F160H32 – A40	78
	MY CUBE	MY CUBE50	95
N	Nozzle	NOZ – M6 – 12	42, 44, 103
	Nut (COLLET HOLDER)	NUA – CTA10	37, 104
P	PALETTE (Collet stand)	PA – R – 1	96
	PETIT BALL	PETIT BALL40	95
	Positioner boss (SMART GRIP)	IR15 – A40FP	79
	Positioning block (ANGLE HEAD HALF)	ABF005	7
	Positioning pin (ANGLE HEAD HALF)	HP – 50S	105 ～
R	RED SCREW arbor	BT40 – RSG8 – 105 – M25	49
	Retention knob	P30T – 1	64
		P – 455	
	Rod (DETa-1 COLLET HOLDER DTA3 type)	PR – DTA3	25
	Retention knob (BT30-DTB12)	P – 535/538	27
S	Semi-finished positioning block	AB – 15	19
	Semi-finished positioning block (ANGLE HEAD HALF)	HB – 01	7
	Set screw holders for Round shank	T63 – CC32 – 90	69
		T100 – CN40 – 115	
	Shank (ANGLE HEAD)	BT40 – MS – 98	15
	Shrink-fit collet (ANGLE HEAD HALF mini type)	FCS6 – 3	10
	Side clamp A (SMART GRIP)	A40 – SCS10 – 40	80
		A40 – SCD20 – 55	
	Sleeve for a set screw holder	SS32 – 8	69
	Slider (MIDDLE VISE)	SRC/SRL/SRS/SRV	100
	SLIMLINE 2PIECE type Master holder	BT50-SLK12-75	※
	SLIMLINE collet	CF12 – 4 – 35	
		CR12-6-55	
		CS12-3-80	
	SLIMLINE MONO series	BT50-SLFB4-90-M22	
	SLIMLINE MONO series SLIMLINE STRAIGHT ARBOR	BT50-SLRA4-110-M42	
		BT50-SLRB8-110-M42	
		BT50-SLSA4-140-M42	
		BT50-SLSB8-140-M42	
	Spacer (DETa-1 COLLET HOLDER DTE type)	7EA – 3.5 – 3	30
		12EBF – BL – 5	
		12EBM – 3 – 3	
		12EBS – 3.6 – 3	
	Spacer set (DETa-1 COLLET HOLDER DTE type)	7ES – A	30

	NAME	CODE	Page
	Spanner	F/FC/FF/FM	103
	SPRING COLLET (COLLET HOLDER)	C10 – 6	8, 38
		ER8 – 4	19
		ESX12 – 6	
S	SPRING COLLET Standard set (COLLET HOLDER)	C10 – A set	38
S	Stationary bracket (ANGLE HEAD HALF)	FKA – 60	105 ～
S		FKB – 60	
S		FKC – 50	
	Straight collet (Hi-ART MILLING CHUCK)	S42 – 6F	42
	Stud bolt (WIRE CUT UNIT)	STB – M6 – L	102
	Sukima nut (COLLET HOLDER)	NUB – CTH10 – 3.6	39, 104
	SUMMIT	A100 – SLZ25 – 135	44
T	Tap collet (ANGLE HEAD HALF mini type)	FCS6 – M4	10
T	Tap rod (DETa-1 COLLET HOLDER DTE type)	TR – 5	30
T	Tap sleeve (ANGLE HEAD HALF)	TA4 – M2	8
T	TEST BAR (ANGLE HEAD UNIVERSAL type)	TBU10	18
T	TEST BAR CHECKMATE	NT30 – CMA – 20 – 125	90
T		HSK32 – CMB – 25 – 175	
T	The Manual clamping head (SMART GRIP)	F160H32 – A40 – 50	78
T	Throw-away tip (MICRO HEAD MBJ type)	CCD094 – PA	62
T	TOOL CAP TCA type	TCA2022 – 10	92
T	TOOL CAP TCB type	TCB0820 – 10	
T	TOOL CAP TCC type	TCC0607 – 50	93
T	TOOL HOLDER STORING CABINET	HBX – A40	98
T	Tool set up stand (Vice clamping type)	HF – BT30	95
U	UNIVERSAL FACING BORING HEAD	MU – S6H	73
V	Variety set (TOOL CAP TCC type)	TCC – F	93
W	WIRE CUT UNIT	WCU – A	101
W	Wrench	DW/RC/TW/W	103
123	6S DESK	6SD – 01	86

※See our dedicated catalog for shrink-fit holder SLIMLINE.
For details, please contact us.

OVERSEAS NETWORK

Logistic center (J-COMPO) ●USA/Chicago ●Germany/Nuremburg ●Thai


2310

<Europe>

AUSTRIA 1 distributor

STEINDL Vertriebs GmbH
Söding
info@steindl.at
TEL 43-3137272240
FAX 43-3137272246

BELGIUM 2 distributors

DIATOOL BVBA
TURNHOUT
info@diatool.be
TEL 32-14401830
FAX 32-14438880

MachinImmo BVBA
LOKEREN
mc@machinimmo.com
TEL 32-93288811

CZECH REPUBLIC 2 distributors

Creative Tools s.r.o.
SKALKA
info@creative-tools.cz
TEL 420-725588988
FAX 420-582384485

OSG
BRATISLAVA
info@osg-belgium.com
TEL 421-43291295

ESTONIA 1 distributor

Naglis & Err SIA
RIGA
info@naglis-err.com
TEL 37-166100336

DENMARK 2 distributors

Balling Maskiner ApS
KOLDING
mbp@balling-maskiner.dk
TEL 45-24790300

OSG SCANDINAVIA A/S
ROSKILDE
osg@osg-scandinavia.com
TEL 45-46756555
FAX 45-46756700

FINLAND 1 distributor

OY FMS TOOLS AB
HELSINKI
info@fmstools.fi
TEL 358-98190950
FAX 358-981909550

FRANCE 2 distributors

DOGA S.A.
MAUREPAS
doga@doga.fr
TEL 33-130664141
FAX 33-130664199

OSG France s.a.r.l.
ROISSY
sales@osg-france.com
TEL 33-149901010
FAX 33-149901015

GERMANY 4 distributors

Aura Tools GMBH
BREIDENBACH
kontakt@aura-tools.de
TEL 49-646591119414
FAX 49-646591119429

MAKINO GMBH
TEL 49-7021503201

OSG GMBH
Göppingen
info@osg-germany.de
TEL 49-716160640
FAX 49-71616064444

Schreurs-tools GMBH
KERNEN
info@schreurs-tools.de
TEL 49-715195899-0

ITALY 4 distributors

MAKINO ITALIA S.R.L.
Cavenago di Brianza
TEL 39-(02)95948290
FAX 39-(02)95948240

MMC EMILIA ROMAGNA SRL
MODENA
info@mmcemilia.it
TEL 39-0536946687
FAX 39-0536946695

MMC ITALIA SRL
MILANO
info@mmc-italia.it
TEL 39-029377031
FAX 39-0293589093

OSG ITALIA SRL
TORINO
info@osg-italia.it
TEL 39-0117705211
FAX 39-0117071402

LATVIA 1 distributor

Naglis & Err SIA
RIGA
info@naglis-err.com
TEL 37-166100336

LITHUANIA 1 distributor

Naglis & Err SIA
RIGA
info@naglis-err.com
TEL 37-166100336

HUNGARY 1 distributor

GesKor Kft.
KUNSZIGET
office@geskor.com
TEL 36-96200075

NETHERLANDS 3 distributors

Machining Innovations NL bv-Machinno
MERSELO
info@machinno.com
TEL 31-478855400

OSG Nederland B.V.
HARMELEN
info@osg-nl.com
TEL 31-348442764

SVM Freestechniek B.V.
BERGEIJK
info@svmfreestechniek.nl
TEL 31-648490933

NORWAY 2 distributors

AS NOR-SWISS
OSLO
norswiss@norswiss.no
TEL 47-23241020
FAX 47-23241021

Promaskin AS
ALESUND
post@promaskin.no
TEL 47-97013916

PORTUGAL 1 distributor

AMTOOLS
MARINHA GRANDE
geral@amtools.pt
TEL 351-244560456
FAX 351-244560668

POLAND 3 distributors

Aura Tools GMBH
k.kosla@aura-tools.de
TEL 48-666011225
FAX 49-646591119429

MB Michał Rzepka
OBORNIKI
mb@mb-frezy.pl
TEL 48-504647666
FAX 48-616222339

MMC HARDMETAL POLAND Sp. z o.o.
WROCLAW
sales@mitsubishicarbide.com.pl
TEL 48-655467284
FAX 48-655467283

ROMANIA 2 distributors

MAZAROM IMPEX SRL
BUCHAREST
mazarom@mazarom.ro
TEL 40-212328001
FAX 40-212328002

TOP METROLOGY S.R.L
BUCHAREST
office@topmetrology.ro
TEL 40-314358402

RUSSIA 2 distributors

Company PromArsenal LLC
CHELYABINSK
sales@promarsenal.ru
TEL 7-3512253138

SodicoM-Center
MOSCOW
info@sodick.ru
TEL 7-4957870970

SLOVAKIA 2 distributors

MAKINO S.R.O.
BRATISLAVA
TEL 421-249612100
FAX 421-249612400

OSG
BRATISLAVA
info@osg-belgium.com
TEL 421-911775678
FAX 421-249612400

SLOVENIA 2 distributors

Aura Tools GMBH
ŽALEC
info@kactrade.si
TEL 386-37104080

BTS COMPANY d.o.o.
LJUBLJANA
info@bts-company.si
TEL 386-15841400
FAX 386-15249224

SPAIN 3 distributors

DELFIN COMPONENTES S.L.
VIZCAYA
delfincomponentes@delfincomponentes.com
TEL 34-944105544
FAX 34-944105544

JANA TOOLS SL
SONDIKA
info@jana-tools.com
TEL 34-944538224
FAX 34-944538225

UTILTALL S.A.
BARCELONA
comercial@utiltall.es
TEL 34-934984465
FAX 34-933086993

SWEDEN 1 distributor

OSG SCANDINAVIA A/S
BROMÖLLA
osg@osg-scandinavia.com
TEL 46-40412255
FAX 46-40413255

SWITZERLAND 1 distributor

STREULI TECHNOLOGIES AG
BIRMENSDORF
info@streuli-techno.ch
TEL 41-17394070
FAX 41-17394077

TURKEY 3 distributors

FORM TEKNIK
ISTANBUL
MR. ISMAIL CINAR — TEL 90-2122973397
info@form-teknik.com — FAX 90-2122566215

TANDEM TAKIM TEZGAHLARI
ISTANBUL
MR. TANKUT KOCAK — TEL 90-2163131413
tankut.kocak@tandem.com.tr — FAX 90-2163131411

TEKNIKA HIRDAVAT SANAVI VE TICARET LTD. STL.
ISTANBUL
MR. MEHMET AKKAYA — TEL 90-2126742864
info@teknikatools.com — FAX 90-2126742863

UK 4 distributors

MATSUURA MACHINERY LTD
LEICESTERSHIRE — TEL 44-1530511400
FAX 44-1530511442

MMC HARDMETAL U.K. LTD
TAMWORTH — TEL 44-1827312312
sales@mitsubishicarbide.co.uk — FAX 44-1827312314

OSG UK LTD.
ESSEX — TEL 44-8453051066
sales@osg-uk.com — FAX 44-8453051067

KYOCERA SGS PRECISION TOOLS EUROPE LTD.
BERKSHIRE — TEL 44-1189795200
salesEU@kyocera-sgstool.com — FAX 44-1189795295

<North America>

U.S.A. 9 distributors

Kitagawa NorthTech Inc.

HQ - Schaumburg, IL (Great Lake)
MR. SHAWN LUSCHIE — TEL 1-800-222-4138
info@kitagawa-usa.com — FAX 1-847-310-9484

Northeast
MR. MATT GENOVESE — TEL 1-203-912-8906
mgenovese@kitagawa-usa.com — FAX 1-847-310-9484

West Coast
MR. DAVID TAKAHASHI — TEL 1-562-522-9749
dtakahashi@kitagawa-usa.com — FAX 1-847-310-9484

Southwest
MR. MIKE ROBERTS — TEL 1-847-284-7626
mroberts@kitagawa-usa.com — FAX 1-847-310-9484

Southeastern
MR. ED BORSOS — TEL 1-847-254-5422
eborsos@kitagawa-usa.com — FAX 1-847-310-9484

MN, IA, ND, SD, NE
MR. REID SWANSON — TEL 1-612-281-7476
reidswans@msn.com — FAX 1-847-310-9484

SINGLE SOURCE TECHNOLOGIES, INC.

HQ - Auburn Hills, MI
sst.millingteam@singlesourcetech.com — TEL 1-248-232-6260

MI
MR. BRAD COOK
Brad.Cook@singlesourcetech.com — TEL 1-248-302-6814

OH
MR. RON DICKUM
Ronald.Dickum@singlesourcetech.com — TEL 1-814-969-6236

WI
MR. STEVE KLUG
Steve.Klug@singlesourcetech.com — TEL 1-262-202-0500

FL (SC, GA)
MR. BEN GUEST
Ben.Guest@singlesourcetech.com — TEL 1-321-319-5525

AL (TN, TX, MS, AR)
MR. BOB ASH
Bob.Ash@singlesourcetech.com — TEL 1-256-200-1100

NY (PA)
MR. PAUL MAYR
Paul.Mayr@singlesourcetech.com — TEL 1-814-833-2246

YAMAZEN INC.

HQ - Elk Grove Village, IL	TEL 1-800-228-2969	**IL (NE, MO, KS, WI, TX)**	TEL 1-800-228-2969
toolingsupport@yamazen.com	FAX 1-847-882-9056	toolingsupport@yamazen.com	FAX 1-847-882-9056
CA	TEL 1-800-228-2969	**AZ (NM, NV, UT, WA, OR, ID, MT, WY, CO)**	TEL 1-800-228-2969
toolingsupport@yamazen.com	FAX 1-847-882-9056	toolingsupport@yamazen.com	FAX 1-847-882-9056
MI	TEL 1-800-228-2969	**IN (KY)**	TEL 1-800-228-2969
toolingsupport@yamazen.com	FAX 1-847-882-9056	toolingsupport@yamazen.com	FAX 1-847-882-9056
GA (SC, AL, TN, MS, NC, VA)	TEL 1-800-228-2969	**CT (PA, MD, DE, MA, ME, RI, NY, VT, NH, NJ)**	TEL 1-800-228-2969
toolingsupport@yamazen.com	FAX 1-847-882-9056	toolingsupport@yamazen.com	FAX 1-847-882-9056

MITSUBISHI MATERIALS USA CORP.
IL
TECHNICAL SERVICE — TEL 1-800-486-2341
marketingsarvices@mmus.com — FAX 1-847-519-1732

ON TARGET TOOLING LLC
WI
MR. SCOTT SHIPPELL
Scott@ontargettooling.com — TEL 1-262-219-9129

OSG USA INC.
IL
MR. DAN VOLPE — TEL 1-800-837-2223
dan.volpe@osgtool.com — FAX 1-800-837-3334

PRECISION TOOLS SERVICE INC.
IN
MR. PAUL SCHNEPP — TEL 1-812-342-1234
pschnepp@ptservice.com — FAX 1-812-342-1235

TOMITA USA INC.
OH
TEL 1-614-873-6509 — FAX 1-614-873-6806

TRIUMPH TOOL LTD.
NC
MR. ROBIN SILVER — TEL 1-828-676-3677
robins@triumphtool.com — FAX 1-828-676-3680

CANADA 3 distributors

TRIUMPH TOOL LTD.

Guelph, ON
MR. RICH MORRISON — TEL 1-519-836-4811
richm@triumphtool.com — FAX 1-519-836-7903

Woodbridge, ON
MR. PATRICK DUFFY — TEL 1-905-850-2323
patrickd@triumphtool.com — FAX 1-905-850-2322

Windsor, ON
MR. SHAWN LESPERANCE — TEL 1-519-251-1771
shawnl@triumphtool.com — FAX 1-519-251-0770

OSG CANADA LTD.
ONTARIO, Burlington
MR. ROB ADKINS — TEL 1-905-632-8032
rob.adkins@osgcanada.com — FAX 1-905-632-8466

SINGLE SOURCE TECHNOLOGIES, INC.
Windsor, ON
MS. RACHEL HUGHSON — TEL 1-519-999-0719
rachel.hughson@singlesourcetech.com

MEXICO 6 distributors

AHNSA TOOLS s.a.
MONTERREY
MR. HORACIO CAMPOS — TEL 52-81-8126-1000
hcampos@ahnsa.com — FAX 52-81-8126-1001

Kitagawa NorthTech Inc.
QUERETARO
MR. ARTURO LOZANO — TEL 52-81-2029-0349
alozano@kitagawa-usa.com

MMC METAL DE MEXICO S.A. DE C.V
QUERETARO
MR. GUILLERMO ORTIZ — TEL 52-442 192 6800
lortiz@mmcmex.com — FAX 52-442 221 6134

OSG / ROYCO, S.A. DE C.V.
MEXICO CITY
MR. TOSHITAKA YOSHIZAKI — TEL 52-55-51-19-3363
toshi@osgroyco.com.mx — FAX 52-55-51-19-3370

SINGLE SOURCE TECHNOLOGIES, de R.L.de C.V.

QUERETARO
MR. MAURICIO MONTESINOS — TEL 52-442-824-9399
mauricio.montesinos@singlesourcetech.com

MONTERREY
MR. ROMAN CAMPOS — TEL 52-442-101-6009
roman.campos@singlesourcetech.com

YAMAZEN MEXICANA S.A. DE C.V
LEON
MR. GERARDO PLASCENCIA — TEL 52-477-3910280
gerardo.perez@yamazen.com.mx — FAX 52-477-3910278

<South America>

BRAZIL 2 distributors

OSG FERRAMENTAS DE PRECISAO LTDA.
SAN PAULO
SALES DEPARTMENT — TEL 55-11-6190-0900
osgsp@nethall.com.br — FAX 55-11-6190-0901

INNOVATE TECHNOLOGIES Brasil LTDA
SAN PAULO
MR. LUCIANO CHIQUETTE — TEL 55-19-3829-9280
luciano.chiquette@innovatetech.com.br

<Oceania>

New Zealand 1 distributor

MANUFACTURING QUALITY TOOLING LIMITED
AUCKLAND
MR. Phil MITCHELL — TEL 64-21610909
sales@mqtooling.com

<East Asia>

CHINA 21 distributors

AUTOFACT MACHINERY LTD.
亞動機械有限公司

DONGGUAN 東莞
MS. LILY GUAN 关 星 — TEL 86-769-81157228
lily@autofact.com.hk — FAX 86-769-81157229

DONGGUAN YAJIYA Precision machinery Co., Ltd
東莞八字屋精密机械有限公司

DONGGUAN 東莞
MR. JASON LEE 李 忠信 — TEL 86-769-8530-7420
sales@yajiya.cn — FAX 86-769-8530-7470

Dongguan Integrity Precision Machinery Co.,Ltd.
东莞市诚晋精密机械有限公司

DONGGUAN 東莞
MR. YANG YABIN 楊 亞兵 — TEL 86-769-82288607
frank.yang@chengjinjm.com.cn — FAX 86-769-82288609

Fineness Corporation
匯穎國際貿易(上海)有限公司

SHANGHAI 上海
MR. STEVE HU 胡上千/ MR. ROY LU 呂旺勳 — TEL 86-21-64282885
steve@fct-tools.com — FAX 86-21-64391906

DONGGUAN 東莞
MR. ALAN CHEN 陳 宏 儒 — TEL 86-769-82284785
alan@fct-tools.com — FAX 86-769-8228-4797

CHENGDU 成都
MR. JASON HUANG 黃 琳 琳 — TEL 86-28-83112969
jasonhuang1121@163.com — FAX 86-28-8311-2969

TIANJIN 天津
MR. YANG JIAN 楊 建 — TEL 86-22-8739-5825
isabat_yang@fct-tools.com — FAX 86-22-8739-5827

KUNSHAN KUNQIAO TRADING CO.,LTD.
坤僑貿易有限公司

KUNSHAN 昆山
MR. CHOU TING SHENG 周 廷升 — TEL 86-512-57507151
kjcorp@ms56.hinet.net — FAX 86-512-57507153

SHENZHEN 深圳
MR. GHENG-NAN,YEH 葉 正男 — TEL 86-755-81786391~2
kj.com@msa.hinet.net — FAX 86-755-8178-6670

GALAXY PRECISION MACHINERY LTD
佳力精密机械有限公司

SHENZHEN 深圳
MR. LIANG MING 梁 明 — TEL 86-755-2966-0881
gp613@galaxy-mt.com — FAX 86-755-2966-0882

JECO PRECISION LTD.
捷高精機有限公司

HONGKONG 香港
MS. CATHY WONG 黃 玉珍 — TEL 852-2428-8328
cathy@jeco.hk — FAX 852-2428-3683

OSG SHANGHAI
歐士機(上海)精密工具有限公司

SHANGHAI 上海
MS. JI MIN 嵇 敏 — TEL 86-21-5888-6600
jimin@chinaosg.com — FAX 86-21-5888-3300

PRO-TECHNIC MACHINERY LTD.
寶力機械有限公司

HONG KONG 香港
MR. ALDO, S.K. CHEUNG 張 四繼 — TEL 852-2428-2727
aldocheung@protechnic.com.hk — FAX 852-2480-4764

JIANZE MACHINERY TECHNOLOGY CO.,LTD
上海建澤机械技術有限公司

SHANGHAI 上海
MR. XUE JIANMING 薛 建明 — TEL 86-21-5155-7657
xuejianming@jianze.net — FAX 86-21-5155-7668

RSE (DALIAN) INTERNATIONALTRADING CO LTD
美立吉(大連)国際貿易有限公司

DALIAN 大连
MR. LI GANG 李 剛 — TEL 86-411-8750-8552
01@chinarse.com — FAX 86-411-8750-8553

SHANGHAI FUDIAN HARDWARE TOOLS CO.,LTD
上海富点五金工具有限公司

SHANGHAI 上海
MR.PAN JUNJUN 潘 军军 — TEL 86-21-5081-6127-127
ada@shanghaifd.com — FAX 86-21-6876-6870

MAKINO CHINA CO.,LTD.
牧野機床(中國)有限公司

KUNSHAN 昆山
MR. LIU HAORAN 劉 浩然 — TEL 86-512-5777-8000
info@makino.com.cn — FAX 86-512-5777-9900

SHENZHENSHI YINGFENGDA TRADING CO.,LTD
深圳市盈峰達貿易有限公司

SHENZHEN 深圳
MR. ZHANG CHENGZHONG 张 承忠 — TEL 86-755-25109822
Kelvin@yfd-group.com.cn — FAX 86-755-23286077

Shenzhen SCZY Technology Co.,Ltd
深圳思誠資源科技有限公司

SHENZHEN 深圳
MR. Fog Zhong 鐘 福泰 — TEL 86-769-22186189
sales@sczy.com — FAX 86-769-22186191

SHANGHAI ELT TRADING CO.,LTD.
上海勛策貿易有限公司

SHANGHAI 上海
MR. PETER LI 李 饶刚 — TEL 86-21-6071-3668
peter@shelt.com.cn — FAX 86-21-6071-3669

QINGDAO 青岛
MR. PETER LI 李 饶刚 — TEL 86-532-5897-7052
peter@shelt.com.cn — FAX 86-532-8093-0907

SONDER TOOLS & MACHINERY(HK)LTD.
晨達(香港)有限公司

HONG KONG 香港
MR. JOHNNY NG 吳 偉良 — TEL 852-2-964-0233
johnnyng@sondertools.com — FAX 852-2-964-0604

DONGGUAN 東莞
MR. JOHNNY NG 吳 偉良 — TEL 86-769-22699687
johnnyng@sondertools.com — FAX 86-769-22699487

SHANGHAI REBAR CUTTINGTOOLS CO., LTD
上海鋭覇切削工具有限公司

SHANGHAI 上海
MR. CUI YANJUN 崔 岩軍 — TEL 86-21-5108-5980
steven_rb@126.com — FAX 86-21-5763-2329

YAMAZEN CORPORATION
山善(上海)貿易有限公司

SHANGHAI 上海
MR. KOZAWA 小澤 — TEL 86-21-5445-2266
kozawa@yamazensh.com. — FAX 86-21-5445-2066

SHENZHEN 深圳
MR. ONO 小野 — TEL 86-755-8280-5000
ono@yamazen.com.cn — FAX 86-755-8280-5100

DALIAN 大连
MR. ZHUANG 庄 震 — TEL 86-411-8762-6323
zhuangzhen@yamazensh.com — FAX 86-411-8762-6332

CHONGQING 重庆
MR. MORII 森井 — TEL 86-23-6308-2799
morii@yamazensh.com — FAX 86-23-6308-2711

GUANGZHOU 广州
MR. YASUNO 安野 — TEL 86-20-8732-1601
yasuno@yamazen.com.cn — FAX 86-20-8732-1232

TIANJIN 天津
MR. ZHUANG 庄 震 — TEL 86-22-2840-8710
zhuangzhen@yamazensh.com — FAX 86-22-2840-8712

SHANGHAI RIJIN CNC TOOLS CO., LTD.
上海日进数控刀具有限公司

ZHEJIANG 浙江
MS. YE LI HONG 叶 丽红 — TEL 86-576-84232178
cnrijin15@126.com — FAX 86-576-84232178

TOJU MACHINE-ELECTRICITY CO.,LTD
上海東佳机電科技有限公司

SHANGHAI 上海
MR. TIAN JUN 田軍 — TEL 86-21-6413-8038
sh_toju@163.com — FAX 86-21-5230-8016

TAIWAN 2 distributors

KUNJUNG CORPORATION
坤嶸企業有限公司

TAIPEI 台北
MR.CHUNG-WEI,HUANG 黃 崇維 — TEL 886-2-22902500
kjcorp@ms56.hinet.net — FAX 886-2-22902515

KAOSHUNG 高雄
MR. TSUNG-LIEH, HO 何 宗烈 — TEL 886-7-7231101
chdhor@pchome.com.tw — FAX 886-7-7236088

TAICHUNG 台中
MR. MING-CHIEH,YEN 顏 明傑 — TEL 886-4-27026477
kj.com@msa.hinet.net — FAX 886-4-24520439

CENTURY TRADING CORPORATION
世紀貿易股份有限公司

TAIPEI 台北
MR. YAN YUNGTA 顏 永達 — TEL 886-2-2298-8336
ytyan@centra.com.tw — FAX 886-2-2298-8338

KOREA 7 distributors

KUK SUNG INTERNATIONAL CO.,LTD.
국성인터내셔널주식회사

DAEGU 대구
MR. CHOI BYUNG HOON 최병훈 — TEL 82-53-604-0521
kuksung@kuksung.com — FAX 82-53-604-0525

HWA JIN TRADING CO.,LTD.
(주) 화진교역

SEOUL 서울
MR. KANG YONG KWON 강용권 — TEL 82-2-803-2127
hwajin-mhte@naver.com — FAX 82-2-803-2129

ITM KOREA

SUWON 수원
MR. LEE SANGKWAN 이상관 — TEL 82-31-291-0917
itmkorea2015@gmail.com — FAX 82-50-4465-7218

MIRAE TECHNO 미래테크노

GWANGMYEONG 광명
MR. PARK HO SUNG 박호성 — TEL 82-2-899-0531
miraetechno@hanmail.net — FAX 82-2-899-0532

NS KOREA CO.,LTD. (주)앤에스코리아

ANYANG 안양
MR. BAI JAMES 배성진 — TEL 82-31-450-3335
info@ns-korea.com — FAX 82-31-450-3339

OSG KOREA CORPORATION 한국OSG주식회사

DAEGU 대구
MR. JANG JUN YOUNG 장준영 — TEL 82-53-589-2054
jyjang1@osg.co.kr — FAX 82-53-583-5553

YAMAZEN (KOREA) LTD. (주)야마젠코리아

SEOUL 서울
MR. SEO SANG DUK 서상덕 — TEL 82-2-864-1755
yamazen@yamazenkorea.co.kr — FAX 82-2-864-1758

<South Asia>

INDIA 12 distributors

MAKINO INDIA PVT. LTD.
BANGALORE/CHENNAI/GURGAON/PUNE/COIMBATOR
MR. B.V. SRIDHAR TEL 91-8067419500
sridhar@makino.co.in

ANANTHA TOOLTECH
BANGALORE
MR. SREEDHAR S SHENOY TEL 91-9845040071
techsupport@ananthatooltech.com

ICON INDUSTRIAL SOLUTIONS
CHENNAI
MR. M. SRINIVASAN TEL 91-4422351336
srinivasan@icontoolings.com

MERAKI TOOLS
MUMBAI / AHMEDABAD
MR. ASHLIE D'BRITTO TEL 91-8806511818
sales@merakitools.in

METACUT TECHNOLOGIES
DELHI
MR. RAJAT VERMA TEL 91-9911310300
rajat.metacut@gmail.com

MMC HARDMETAL INDIA PVT. LTD.
BANGALORE
MR. HIROSHI YURI TEL 91-802308-3400
mmcindia@mmc.co.jp

NETRA TECHNOLOGIES
AHMEDABAD
MR. CHIRAG PATEL TEL 91-9722323111
netratechno@gmail.com

ORION INNOTECH PVT. LIMITED
GURGAON / CHENNAI / PUNE
MR. VISHAL VERMA TEL 91-1244225210
vishal@oriongroup.in

OSG (INDIA) PVT. LTD.
GURGAON
MR. ANUP KUMAR DAS TEL 91-1244009737
anup@osg-india.com

PASS TECH
COIMBATORE
MR. BOOPATHY K. TEL 91-9600906000
boopathy@passtech.in

VALIANT INDIA
PUNE
MR. VIRENDRA MAYNALE TEL 91-9371672785
sales@valiantindia.in

YAMAZEN MACHINERY & TOOLS INDIA PVT. LTD.
GURGAON / BANGALORE / CHENNAI / PUNE / AHMEDABAD
MR. RYO AKIYAMA TEL 91-1244605900
india1@yamazen.co.jp

INDONESIA 4 distributors

PT. ASIA PHINISI MANDIRI
TANGERANG / CIKARANG
MR. HERI TEL 62-2155661357
heri@asiaphinisi.co.id

PT. JAVATEC TRIMITRA MACHINERY
JAKARTA
MR. JONATAN ARIF SANTOSO TEL 62-21-4584-9988
jonatan@javatec-machinery.com FAX 62-21-4584-8899

PT. RUKUN SEJAHTERA TEKNIK
JAKARTA
MR. FRANKIE ANGGADHA TEL 62-21-628-1615
marketing@rsttools.com FAX 62-21-626-5559

PT. YAMAZEN INDONESIA
JAKARTA/CIKARANG
MR. KENTA YOSHIMIZU TEL 62-21-451-3345
yoshimizu@yamazen.co.id FAX 62-21-451-3346

MALAYSIA 4 distributors

MEC-MART TOOLINGS SDN. BHD
KUALA LUMPUR / PENANG / JOHOR
MR. NICHOLAS TOH TEL 60-356330932
nicholastoh@mecmart.com.my

NEWLINE MACHINE TOOL SDN.BHD.
KUALA LUMPUR
MR. JEFFREY P.W CHOON TEL 60-3-8961-1973
jeff@newlinemachine.com

ROBO TECH MACHINERY SDN. BHD
KUALA LUMPUR
MR. TEO CHENG CHUAH TEL 60-355697877
ccteo@haasmalaysia.com

YAMAZEN (MALAYSIA) SDN.BHD.
KUALA LUMPUR/PENANG/JOHOR
MR. YOSHITAKA KUWABARA TEL 60-3-5569-5099
kuwabara@yamazen.com.my

SINGAPORE 4 distributors

MAKINO ASIA PTE LTD.
MR. SAM SHUKOR TEL 65-6861-5722
sam@makino.com.sg

NOBELTECH PTE LTD
MR. ERIC CHAN TEL 65-6749-3636
eric@nbel.com.sg

OSG ASIA PTE LTD.
MR. YASUTAKA YONEDA TEL 65-6844-4350
yasuyoneda@osgasia.com.sg

YAMAZEN (SINGAPORE)PTE LTD.
MR. KAZUNORI WATASHIGE TEL 65-6276-9488
watashige@yamazen.com.sg

PHILIPPINES 3 distributors

YAMAZEN MACHINERY & TOOLS PHILIPPINES, INC.
LAGUNA
MR. RYO SONISHI TEL 63-49-543-1958
r.sonishi@yamazen.com.ph FAX 63-49-508-0893

KAMOGAWA LAGUNA PHILIPPINES.INC
LAGUNA
MR. TAKAHIRO FUNAKUBO TEL 63-49-576-4931
t.funakubo@kamog.co.jp FAX 63-49-508-3199

NICKLAUS MACHINERY CORPORATION
MANILA
MS. CAMIE CHEN TEL 63-27-118-414
nicklaus-machinery@pldtdsl.net FAX 63-27-121-225

THAILAND 7 distributors

FACTORY MAX CO.,LTD.
BANGKOK
MR. S. TANGTARATORN TEL 66-2333-8888
sales@factorymax.co.th FAX 66-2759-9009

MAKINO (THAILAND) CO.,LTD.
BANGKOK
MR. SHOGO NAKASUMA TEL 66-2-017-0123
nakasuma@makino.co.th FAX 66-2-971-5751

PRECISION TOOLS SERVICE (THAILAND) CO.,LTD.
BANGKOK
MR. HIROAKI ISHIKAWA TEL 66-2-186-4970
h_ishikawa@toyo-tos.com FAX 66-2-308-2471

RETRA ENGINEERING (THAILAND) CO.,LTD.
BANGKOK / CHONBURI
MR. KAZUHIRO SOEJIMA TEL 66-2-726-9535
soejima@retra-co-th.com FAX 66-2-726-9759

N-TECH MACHINERY CO.,LTD.
SAMUTPRAKARN
MS. JENNY TEL 66-2-136-5333
thaintech@yahoo.com FAX 66-2-136-5334

YAMAZEN (THAILAND) CO.,LTD.
BANGKOK / CHONBURI / KORAT
MR. KAZUYA OKADA TEL 66-2-374-5522
okada@yamazen.co.th FAX 66-2-374-3192

YONEZAWA ENGINEERING ASIA (THAILAND) CO.,LTD.
BANGKOK / RAYONG
MR. YUICHI MIKAMI TEL 66-2-769-5681
mikami@yea.co.th FAX 66-2-769-5683

VIETNAM 7 distributors

BM SYSTEM SOLUTION CO.,LTD.
HANOI
MR. WON RYANG HUR TEL 84-97-774-5488
bmssvina@daum.net

KAMOGAWA VIETNAM CO.,LTD
HANOI
MR. DAISUKE KATSURA TEL 84-24-378-550-22/23
katsura@kamog.co.jp FAX 84-24-378-550-23
HO CHI MINH
MR. TAKUMI TAFU TEL 84-28-391-054-77/78/79
tafu@kamog.co.jp FAX 84-8-3910-5480

KHANG THINH TECHNOLOGY IMPORT EXPORT CO.,LTD.
HO CHI MINH
Ms. ZOEY TEL 84-86-7743-986
sales1@kttech.vn

TFM TOOLS CO.,LTD.
BINH DUONG
MR. THANH TEL 84-9087666600
thanh@tfmvn.vn

T&B TECHNICAL SERVICES AND TRADING CO.,LTD
HANOI / HO CHI MINH
MR. LUU QUANG THOA TEL 84-24-6659-5103
thoa-luu@tbvn.com.vn

WOLFRAM INDUSTRIAL SERVICE JSC
HANOI / HO CHI MINH
MR. NGOC TEL 84-24-3793-2350
giangoc.nguyen@wolfram.vn FAX 84-24-3793-2320

YAMAZEN VIETNAM CO.,LTD
HANOI
MR. ATSUSHI KIKUCHI TEL 84-24-3728-6292
kikuchi@yamazenvn.com FAX 84-24-3766-4137
HO CHI MINH
MR. DAISUKE TOCHIGI TEL 84-28-5417-9229
tochigi@yamazenvn.com FAX 84-28-3820-2784


高精度保証
GURANTEED AC
超精密級 5μ
GRADE
級 10
DARD
MST corp.
EMERGENCY EXIT
SHRINK-FIT HOLDER
MST
MAKINO D300
MONO CURVE
HALF
B


NAGOYA
OSAKA
TOKYO
N
3hr.30min.
0
100km
KYOTO
MST corporation
1738 Kitatahara Ikoma Nara
630-0142 Japan
KOBE
OSAKA
NARA
1hr.
Kansai
International
Airport
1hr. 45min.
0
10km



HEAD OFFICE & FACTORY
1738 Kita-tahara, Ikoma,
Nara 630-0142 Japan
Tel : +81 743 78 1931
Fax : +81 743 78 3854
: info@mst-corp.co.jp

MST corporation

http://www.mst-corp.co.jp

190104100160MS